## CONSTRUCTION INSPECTION CHECK-OFF LIST FOR SEPARATOR SAND FILTERS (SEPSF's)

STAGE	DESIGN	GEOTECHNIC	COUNTY	MNCP&PC
	ENGINEER	AL ENGINEER	INSPECTOR	&
	(DE)	(GEO)		OTHER
* MANDATORY NOTIFICATION: Inspection and approval by the parties indicated is required	INITIALS/DATE	INITIALS/DATE	INITIALS/DATE	INITIALS/DATE
at these points prior to proceeding with construction. The permittee is required to give the				
required inspection parties twenty-four (24) hours notice (DPS telephone 240-777-0311). The				
DPS inspector may waive an inspection, provided the design engineer and/or geotechnical				
engineer makes the required inspection per a prior scheduled arrangement which has been				
confirmed with the DPS inspector. Work completed without the necessary party's approval				
may result in the permittee having to remove and reconstruct the unapproved work. The				
permittee must maintain a "record set" of approved SC/SM plans on-site.	*	*	*	*
1. Pre-construction meeting.	•	•	*	^
2. Sediment control installation.		<u> </u>	•	
3. Excavation for stormwater management structure (GEO)			*	
4. Footing subgrade (GEO)		*		
5. Footing steel and forms per approved shop drawings/plans (DE)	*		*	
6. Side steel and forms per approved shop drawings/plans (DE)	*		*	
7. Concrete pouring and testing (slabs and walls) (GEO)		*	*	
8. Internal components except filter media (DE)	*		*	
9. Site is permanently stabilized. All sediment and debris flushed from structure and			*	
sediment control measures removed.				
10. Installation of filter media (DE) or (GEO)	*		*	
11. Top slab with access (**) dimensions forms, and steel placement (DE); concrete	*	*	*	
testing (GEO)				
- Lifts, compaction, soil material (GEO)				
- Location, dimensions (DE)				
12. Remove temporary blocking) (DE) and (GEO)	*	*	*	
13. Submit record drawing and documentation (DE)	*	*		
14. Final Inspection.	*	*	*	

## NOTES:

- 1. Should pre-cast structures be used, a design certification from the manufacturer must be supplied to the Design Engineer and the County Inspector prior to installation indicating that the structure was built in conformance with design plans.
- 2. Permittee to supply Design Engineer with delivery tickets for all materials used in the SEPSF construction.
- 3. See construction specifications this plan for detailed requirements.
- 4.\*\* Top slab can be placed earlier should adequate access and ability to place filter media be made available. DE to inspect placement of removable top slab section(s), if required.
- 5. A copy of this completed checklist must be submitted as part of the stormwater management as-built package.

DPS Inspection Telephone: (240)777-0311

MNCPPC Inspection Telephone: (301) 495-4571