Tree Protection - new sidewalk	5.24.21			Note: refer to *Tree Protection Requirements For The Department*

Tree Protection - new sidewalk   5.24.21
Decatur Rd   Rick Holley
*All root pruning shall be done to a maximum depth of 6"
DBH = diamater (in.) at breast height (4.5 ft above ground)
Location: F = front, S = side, R = rear, I = island, M = Median, O = Opposite, P = Private, ms = multi-stem
Pruning: s/w = sidewalk, elev = elevation pruning, DW = dead wood removal, d/w = driveway
 cli - clear light, csi = clear sign, cpt = clear private tree, clh = clear house, rd = road
Tree Protection: F = fencing required, n/a = no action

Note: refer to *Tree Protection Requirements For The Department*
Of Transportation for Standard Tree Protection Measures
Note: Inspection of worksite tree protection measures required
by MC-DOT Arborist prior to construction activities
Note: ROW not to be utilized for staging area unless otherwise permitted
by MC-DOT Arborist prior to construction activities

ADDRESS	SPECIES	LOCATION	DBH	RECOMMENDATIONS
Decatur Rd				
3808	Red Maple	1F	21	**REMOVE:** proposed contruction would compromise health/structural stability of tree
	Cutleaf Japanese Maple	2F	3	**REMOVE**: proposed contruction would compromise health/structural stability of tree
	Dogwood	3F	1	F
3812	Black Oak	1F	39	**REMOVE:** proposed contruction would compromise health/structural stability of tree
	White Oak	1F-P	29	F, Root prune along edge of proposed s/w
	White Oak	2F-P	25	F, Root prune along edge of proposed s/w
3814	White Oak	1F	27	**REMOVE:** proposed contruction would compromise health/structural stability of tree
	Stump	2F	56	remove stump
3816	White Oak	1F	28	**REMOVE:** proposed contruction would compromise health/structural stability of tree
3818	White Oak	1F	35	**REMOVE:** proposed contruction would compromise health/structural stability of tree
	Dogwood	2F	4	F, Elevate 8' over proposed s/w
3900	White Pine	1F	12.5	

ADDRESS	SPECIES	LOCATION	DBH	RECOMMENDATIONS
				Note: Per Montgomery County Roadside Tree Protection Law, allocation of $3,750.00 into
				the **Street Tree Replacement Fund** is required.
				1. Hand prune roots where noted above.
				2. Any roots 2" diameter or larger exposed by air excavation or by hand pruning activities,
				that require removal due to sidewalk construction, shall be inspected by ISA certified
				arborist with the Tree Maintenance Section, Montgomery County, prior to removal.
				3. An approved contractor certified in the State of Maryland for air excavation will be
				required to conduct all excavation where "Air Excavation required" is noted above.
				4. Arborist (Tree Maintenance Section, Division of Highway Services) shall be notified
				by Project Manager of root pruning and air excavation schedule prior to scheduled work.
				5. Root pruning shall be to the depth of excavation (no more than 6" depth)
				6. Excavation for proposed sidewalk shall be no more than 6"