

Oaks Landfill Landfill Gas Monitoring Report 2nd Quarter 2016 April 2016 – June 2016



Presented to:

Montgomery County

Department of Environmental Protection

Division of Solid Waste Services

16101 Frederick Road

Derwood, MD 20855

Presented by:

CBI

16406 US Route 224 East Findlay, Ohio 45840

June 2016

Oaks Landfill

Landfill Gas Monitoring Report

Second Quarter 2016 (April 2016 – June 2016)

Prepared By:

CB&I 16406 U.S. Route 224 East Findlay, Ohio 45840

For the:

Oaks Landfill 6001 Olney-Laytonsville Road Laytonsville, Maryland 20882

Presented To:

Maryland Department of the Environment 1800 Washington Blvd. Suite 605 Baltimore, MD 21230

June 8th, 2016

Table of Contents

| Section | | Page | |
|---------|--|------|--|
| 1 | Background | 1 | |
| 2 | Subsurface Methane Monitoring | 1 | |
| 3 | Explosive Gas Monitoring within On-Site Structures | . 2 | |

List of Tables

Table 1 – Summary of Quarterly Subsurface Methane Monitoring

1 Background

The Montgomery County Department of Environmental Protection (DEP), Division of Solid Waste Services (DSWS) is responsible for the post-closure care and maintenance of the Oaks Landfill. The Landfill property is nearly 545 acres, with a waste disposal footprint of approximately 170 acres. The Landfill operated from 1982-1995 (in receiving mixed municipal solid waste) and 1995-1997 (in receiving ash residue) from the County's Waste-to-Energy Facility (Resource Recovery Facility) and other non-processible (non-burnable) materials. The Landfill was closed in 2001 in accordance with Environmental Protection Agency (EPA) Subtitle D requirements of the Resource Conservation and Recovery Act (RCRA). The Oaks Landfill is located at 6001 Olney-Laytonsville Road, Laytonsville, Maryland 20882.

This Landfill Gas (LFG) Monitoring Report has been prepared in accordance with the Oaks Landfill Closure and Post-Closure Care Plan that was submitted to the Maryland Department of the Environment (MDE) on January 31, 2001 by DEP. In addition, existing field procedures were updated for this monitoring event from the Updated Environmental Monitoring Plan that was submitted to MDE on January 17, 2012 by DEP.

The existing Closure and Post-Closure Care Plan (and future Environmental Monitoring Plan) requires quarterly LFG monitoring of the monitoring wells/probes located along the perimeter property boundary of the Oaks Landfill and within on-site structures. LFG monitoring is performed to assess the potential for subsurface migration of LFG, specifically, for the presence of methane gas beyond the landfill property.

The regulatory standard concerning the collection and monitoring of explosive gases (i.e. methane) at solid waste landfills in Maryland is established in the Code of Maryland Regulations (COMAR) Title 26, Subtitle 4, Chapter 7, Part 03B(9) – COMAR 26.04.07.03B(9) – "A facility may not be designed or operated in such a manner that the concentration of explosive gases generated by the facility exceeds 25 percent of the lower explosive limits for the gases in facility structures, excluding gas control or recovery system components, and the lower explosive limit for the gases at the property boundary." According to this standard, methane concentrations resulting from the presence of LFG in on-site structures at Oaks Landfill cannot exceed 25 percent of the lower explosive limit (LEL) (1.25 percent by volume), and methane concentrations cannot exceed 100 percent of the LEL (5.00 percent by volume) at the Oaks Landfill property boundary.

2 Subsurface Methane Monitoring

The Oaks Landfill currently maintains twenty five (25) permanent landfill gas monitoring wells that are used for compliance with explosive gas requirements in COMAR. The monitoring wells contain single depth probes that are located along the perimeter property boundary of the Landfill. The monitoring wells provide a media through which LFG can be measured from the adjacent waste fill area.

On May 26, 2016, CB&I Staff performed the Second Quarter 2016 (May – June 2016) monitoring event of the LFG monitoring wells along the Oaks Landfill property boundary. CB&I Staff used a GEM 5000 from Landtec to conduct the monitoring activities. The GEM 5000 measures methane (% vol.), carbon dioxide (% vol.), oxygen (% vol.) and gas balance (% vol.). CB&I Staff recorded the peak measurement of methane concentration (taken after 60 seconds of well purging) as well as relative pressure. For LFG monitoring compliance purposes, level measurements for methane, carbon dioxide, oxygen, and balanced gas were recorded (taken after 180 seconds of well purging).

For a summary of the quarterly LFG monitoring data using the level measurements, refer to **Table 1 – Summary of Quarterly Subsurface Methane Monitoring**.

No methane exceedances were found in the LFG monitoring wells during this quarterly monitoring event.

3 Explosive Gas Monitoring Within On-Site Structures

At the Oaks Landfill, seven (7) on-site structures are monitored for the presence of explosive gas as part of the quarterly LFG monitoring event:

- 1. Maintenance Building (hallway, front office, large side office, men's room, women's room, storage room, records storage room, and garage).
- 2. Security Guard Shack.
- 3. Monitoring Well Maintenance Shed.
- 4. Landfill Gas Flare Station.
- 5. Landfill Gas-to-Energy Switchgear Enclosure.
- 6. Landfill Gas-to-Energy Equipment Storage Building.
- 7. Leachate Pretreatment Plant (Control Room, Lab, Restroom, Mechanical Room, and Equipment Area).

On May 26, 2016, CB&I Staff performed the Second Quarter 2016 (May – June 2016) monitoring event of the on-site structures at the Oaks Landfill. Using the GEM 5000 and a Combustible Gas Monitor with sample pump, CB&I conducted methane monitoring inside the on-site structures located at the Oaks Landfill. The GEM 5000 measures methane (% vol.), carbon dioxide (% vol.), oxygen (% vol.), and gas balance (% vol.). The Combustible Gas Monitor measures CH4 (ppm) and O2 (% volume). CB&I Staff walked through the interiors of the structures and monitored the perimeter wall interface, floor to wall interface in hallways and rooms, floor penetrations, and other likely potential gas pathways as well as the exterior perimeter of the structures.

No combustible gas (e.g. methane) was detected in any of the seven (7) on-site structures at the Oaks Landfill during the quarterly monitoring event.

| Oaks Landfill – LFG Monitoring Report | Second Quarter 2016 |
|---------------------------------------|---------------------|
| | |
| | |
| | |
| | |
| | |
| TABLE 1 | |
| SUMMARY OF QUARTERLY SUBSURFACE METHA | NE MONITORING |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

TABLE 1
SUMMARY OF QUARTERLY SUBSURFACE METHANE MONITORING
(May 26, 2015)

| Monitoring Well Name | CH₄ %vol | CO ₂ %vol | O ₂ %vol | Balance (%vol) | Relative Pressure (in. H ₂ O) |
|-------------------------|-------------|-------------------------|------------------------|-------------------|--|
| MW2 | 0.1 | 3.7 | 14.3 | 81.9 | 0.33 |
| MW1 | 0.1 | 1.9 | 17.1 | 80.9 | 0.4 |
| MW3 | 0.1 | 1.9 | 16.4 | 81.6 | -0.21 |
| MW3A | 0.1 | 3.3 | 15.6 | 81 | 0.41 |
| MW4 | 0.1 | 1.9 | 17.2 | 80.8 | 0.46 |
| MW5 | 0.0 | 2.3 | 16.4 | 81.3 | 0.6 |
| MW8A | 0.0 | 6.9 | 10.7 | 82.4 | 0.56 |
| MW8 | 0.0 | 1.4 | 17.1 | 81.5 | 0.5 |
| MW7 | 0.0 | 0.9 | 18.6 | 80.5 | 0.67 |
| MW6 | 0.0 | 2.3 | 17.4 | 80.3 | 0.59 |
| MW8B | 0.0 | 5.1 | 12.6 | 82.3 | 0.18 |
| MW9 | 0.0 | 2.9 | 15.6 | 81.5 | 0.68 |
| MW10 | 0.0 | 2.6 | 16.4 | 81 | 0.71 |
| MW11 | 0.0 | 6.6 | 10.6 | 82.8 | 0.56 |
| MW12 | 0.0 | 0.8 | 18.8 | 80.4 | 0.67 |
| MW13 | 0.1 | 0.1 | 19.8 | 80 | 0.72 |
| MW14 | 0.1 | 5.4 | 11.5 | 83 | -5.64 |
| MW15 | 0.0 | 2.4 | 18.8 | 78.8 | -1.05 |
| MW16 | 0.1 | 0 | 19.9 | 80 | 0.03 |
| MW17 | 0.1 | 0 | 19.9 | 80 | 0.01 |
| MW18 | 0.1 | 0.9 | 19.4 | 79.6 | -1.87 |
| MW19 | 0.1 | 0.1 | 15.9 | 83.9 | -0.13 |
| MW20 | 0.1 | 1.7 | 9.2 | 89 | -2.65 |
| MW21 | 0.7 | 6.4 | 0.1 | 92.8 | 16.56 |
| MW22 | 0.1 | 3.1 | 16 | 80.8 | -0.01 |

Note 1. % vol. = Percent by Volume

Note 2. in. H_2O . = Inches of Water



EXPLOSIVE GAS MONITORING PROBE REPORT

NAME OF SANITARY LANDFILL: Oaks/ Montgomery County LOCATION: 6001 Olney Laytonsville Rd Laytonsville, MD 20882

TEST DONE BY: Jason Martin DATE: 05/26/2016

GAS SENSING DEVICE: Landtec GEM MODEL NO: 5000 DATE LAST CALIBRATED: 5/26/2016

CALIBRATION GAS: 15% CH₄, 15% CO₂

PRESSURE SENSING DEVICE: Landtec GEM MODEL NO: 5000

AMBIENT AIR TEMPERATURE: **RELATIVE HUMIDITY**: 1 79° **AMBIENT BAROMETRIC PRESSURE: 29.48** PRECIPITATION (LAST 24 HRS): 0.00in **OBSERVED WEATHER CONDITIONS: Clear** WIND: 5 mph Relative CH₄ Initial CH4 PROBE NO. LEL (%) CH4 Time CO2 02 Bal Pressure COMMENTS Sustain (%) (%) ("WC) MW2 11:18 AM 2 3.7 14.3 81.9 0.33 0.1 0.1 0.1 MW1 11:24 AM 1.9 2 0.1 0.1 0.1 17.1 80.9 0.4 MW3 11:30 AM 2 0.1 0.1 0.1 1.9 16.4 81.6 -0.21MW3A 11:45 AM 2 0.1 3.3 15.6 81 0.41 0.1 0.1 MW4 11:53 AM 2 17.2 0.46 1.9 80.8 0.1 0.1 0.1 MW5 11:55 AM 2.3 16.4 81.3 0 0 0.6 0 0 MW8A 12:01 PM 82.4 0.56 0 0 10.7 0 0 6.9 MW8 12:07 PM 0 0 81.5 0.5 0 0 1.4 17.1 MW6 12:10 PM 0 0 0 0 2.3 17.4 80.3 0.59 MW7 12:13 PM 18.6 0 0 0 0 0.9 80.5 0.67 MW8B 12:18 PM 0 0 0 0 5.1 12.6 82.3 0.18 MW9 12:21 PM 0 0 2.9 15.6 81.5 0.68 0 0 12:25 PM 0 **MW10** 0 2.6 16.4 81 0.71 0 0 MW11 12:30 PM 82.8 0 0 0 0 6.6 10.6 0.56 **MW12** 12:33 PM 0 0 0.67 0 0 8.0 18.8 80.4 **MW13** 12:37 PM 2 0.1 0.1 0.1 0.1 19.8 80 0.72 **MW14** 12:42 PM -5.64 2 0.1 0.1 0.1 5.4 11.5 83 **MW15** 12:47 PM 2.4 78.8 -1.05 0 0 0 0 18.8 **MW16** 12:51 PM 2 19.9 0.1 0.1 0.1 0 80 0.03 **MW17** 12:57 PM 2 0 19.9 80 0.01 0.1 0.1 0.1 **MW18** 1:00 PM 2 0.1 0.1 0.9 19.4 79.6 -1.87 0.1 **MW19** 1:10 PM 2 15.9 83.9 -0.13 0.1 0.1 0.1 0.1 **MW20** 1:15 PM 2 0.1 1.7 9.2 89 -2.65 0.1 0.1 MW21 1:21 PM 14 0.7 0.7 0.7 6.4 0.1 92.8 16.56 **MW22** 1:26 PM 2 16 -0.01 0.1 0.1 0.1 3.1 8.08

COMMENTS: