



1. INSTALL SILT FENCE OR SILT SOCKS DOWNSLOPE OF AREA OF STOCKPILE.
2. PLACE STOCKPILE IN AREAS SHOWN ON EROSION CONTROL PLAN WITHOUT BLOCKING NATURAL DRAINAGE PATTERNS.
3. FOLLOW DIMENSIONS SHOWN ABOVE. HEIGHT SHOULD NOT EXCEED 35 FT. SIDE SLOPES SHOULD NOT BE STEEPER THAN 3H:1V.
4. SEED IMMEDIATELY IF MATERIAL IS NOT TO BE USED WITHIN 20 DAYS. FOLLOW "TEMPORARY SEEDING ON ES-1".
5. LOCATION(S) AND SIZE(S) OF SOIL STOCKPILES ARE APPROXIMATE AND SHALL BE ADJUSTED PER FIELD AND CONSTRUCTION SEQUENCE CONDITIONS. CONTRACTOR SHALL VERIFY REQUIRED SIZE(S). REQUIREMENTS FROM THE STANDARDS DETAIL MUST BE FOLLOWED FOR

NOTE:
CHANNEL MUST BE COMPLETELY STABILIZED WITHIN
SEVEN (7) DAYS OF CHANNEL CONSTRUCTION.

HARDINESS ZONE (FROM FIGURE B.3): BB SEED MIXTURE (FROM TABLE B.3): 11			FERTILIZER RATE (10-20-20)				LIME RATE	
No.	SPECIES	APPLICATION RATE (lb/sf)	SEEDING DEPTHS	N	P ₂ O ₅	K ₂ O		
1	CREEPING RED FESCUE (FESTUCA RUBRA VAR. RUBRA)	0.69lb/1000sf	1/4 - 1/2 in	45 lb/oc (1lb/1000 sf)	90 lb/oc (2lb/1000 sf)	90 lb/oc (2lb/1000 sf)	2 TONS/AC (90lb/1000 sf)	
2	CHWING FESCUE (FESTUCA RUBRA SSP. COMMUTATA)	0.69lb/1000sf						
3	KENTUCKY BLUE GRASS (POA PRATENSIS)	0.48lb/1000sf						

HARDNESS ZONE (FROM FIGURE B.3): 6B					FERTILIZER RATE (10–20–20)	LIME RATE
No.	SPECIES	APPLICATION RATE (lb/af)	SEEDING DATES	SEEDING DEPTHS		
1	CERIAL RYE (SECALE CEREALE)	2.8lb/1000sf	MAR.01/MAY15 AUG.1/NOV.15	1 in	436 lb/ac (10lb/1000 sf)	2 TONS/AC (90lb/1000 sf)
2	FOXTAIL MILLET (SETARIA ITALICA)	0.7lb/1000sf	MAY.16/JUL.31	0.5 in		

TENTATIVE ACTIVITY SCHEDULE		MONTH 1			MONTH 2		
		1	2	3	1	2	3
OBTAINING PERMIT	X						
PRECONSTRUCTION MEETING ON SITE	X						
INSTALL INITIAL PHASE E&S BMP'S (START-UP)	X						
INSTALL INTERMEDIATE PHASE E&S BMP'S					X	X	X
INSTALL FINAL PHASE E&S BMP'S							X
ROUGH GRADING	X	X					
FOUNDATION INSTALLATION					X	X	X
UNDERGROUND UTILITIES					X	X	X
FINAL GRADING						X	X
INSTALL AND MAINTAIN TEMPORARY GRASSING DS-2		X	X	X	X	X	X
REMOVE ALL TEMPORARY BMP'S							X
CLOSEOUT PERMIT							

CONDITIONAL USE APPLICATION
BOA-XX-XX-XXXX

