SEE SHEETS I-01 FOR FULL SHEET INDEX

MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION FLOWER AVENUE SEPARATED BIKE LANES

OWNER'S CERTIFICATION

I HEREBY CERTIFY THAT ALL CLEARING, GRADING, CONSTRUCTION AND/OR DEVELOPMENT WILL BE DONE PURSUANT TO THIS PLAN AND THAT ANY RESPONSIBLE PERSONNEL INVOLVED IN THE CONSTRUCTION PROJECT WILL HAVE A CERTIFICATE OF ATTENDANCE AT A DEPARTMENT OF NATURAL RESOURCES APPROVED TRAINING PROGRAM FOR THE CONTROL OF SEDIMENT AND EROSION BEFORE BEGINNING THE PROJECT.

JOSEPH MOGES, P.E. CHIEF, DIVISION OF TRANSPORTATION ENGINEERING

DESIGN CERTIFICATION

I HEREBY CERTIFY THAT THIS PLAN HAS BEEN PREPARED IN ACCORDANCE WITH THE "1994 MARYLAND" STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL", MONTGOMERY COUNTY DEPARTMENT OF PERMITTING SERVICES EXECUTIVE REGULATIONS 5-90, 7-02AM AND 36-90, AND MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION "STORM DRAIN DESIGN CRITERIA" DATED AUGUST 1988.

DATE

CARRIE CASTO, P.E. MD. REGISTRATION NO. 28397

CERTIFICATION OF THE QUANTITIES

I HEREBY CERTIFY THAT THE ESTIMATED TOTAL AMOUNT OF EXCAVATION AND FILL AS SHOWN ON THESE PLANS HAS BEEN COMPUTED TO 724 CUBIC YARDS OF EXCAVATION, 179 CUBIC YARDS OF FILL AND THE TOTAL AREA TO BE DISTURBED AS SHOWN ON THESE PLANS HAS BEEN DETERMINED TO BE 62,629 SQUARE FEET.

DATE

CARRIE CASTO, P.E. MD. REGISTRATION NO. 28397

The following standards (construction and temporary traffic control) are required for this project:

- Standard C O G Inlets 5', 10', 15' & 20'

- Precast or Cast-In-Place C O G/C O S Opening for 8" Curb 5' or 10' Only

MD 383.0I - Standard Manhole

D. MD 386.II - Standard Junction Box

MD 620.02-01 - Standard Types C And D Concrete Curb and Combination Concrete Curb & Gutter

- Depressed Curb for Combination Curb and Gutter and Depressed Curb for Sidewalk Ramps - Standard Entrance Construction Residential & Commerial Method No. I

MD 630.02 - Standard Entrance Construction Residential & Commercial Method No. 2

MD 655.II - Sidewalk Ramps Perpendicular

- Sidewalk Ramps Parallel MD 655.12

K. MD 655.13 - Sidewalk Ramps Combination

L. MD 655.40 - Detectable Warning Surfaces

- Combination Concrete Curb and Gutter - Type A M. MC-100.01 N. MC-102.01 - Depressed Curb Entrance

O. MC-III.OI - Business District Sidewalk

For all standards referred to on the plans the contractor must go to the MDOT SHA Book of Standards or Montgomery County design standards which will have the most current version.


https://www.montgomerycountymd.gov/dot-dte/common/standards.html

The Book of Standards can be accessed at:

http://apps.roads.maryland.gov/businesswithsha/bizStdsSpecs/desManualStdPub/ publicationsonline/ohd/bookstd/index.asp

FROM PINEY BRANCH ROAD TO ARLISS STREET

CIP PROJECT NO. 502004 65% SUBMITTAL, FEBRUARY 2025



SCALE: 1'' = 1000'

OWNER - MONTGOMERY COUNTY DEPT. OF TRANSPORTATION

100 Edison Park Drive, 4th Floor

joseph.moges@montgomerycountymd.gov

Gaithersburg, MD 20878

JOSEPH MOGES

227-251-1268

IT IS THE RESPONSIBILTY OF PERMITTEE/OWNER OF THIS SITE TO OBTAIN ALL REQUIRED PERMITS PRIOR TO ISSUANCE OF APPROVED SEDIMENT CONTROL PERMIT EXPRIATION PERMIT NO. Floodplain District WATERWAY/WETLAND(S) a. Corps of Engineers b. MDE Χ . MDE Water MDE Dam Safety Χ Approval Date DPS Roadside Tree Protection Plan NOTICE OF INTENT FEMA LOMR (Required Post Construction) SHA Access Permit: MCDPS SEDIMENT CONTROL

RELATED REQUIRED PERMITS

SHA PERMIT NUMBER: 24APM0001XX

TREE CANOPY REQ To be completed by the consultant of Sediment Control/Stormwater Man	and placed on the first sheet of the	Area (sq. f of Disturba Erom	er of Shade Trees Number of Shade Trees Required	
Exempt: Yes • No • If exempt under Section applicable exemption category below this table.	55-5 of the Code, please list the	1 6,001 8,001	Io 6,000 8,000 12,000	3 6 9
Project is subject to Chapter 22A-9 of the Mor	nt. Co. Forest Conservation Law	12,001 14,001	14,000 40,000	12 15
Total Property Area	Total Disturbed Area	If the square footage of th	ne limits of disturbar	nce is more than 40,000, then the
70,600 _square feet	70,600 square feet			lated using the following formula:
		(Number of S	quare Feet in Limits	s of Disturbance / 40,000) x 15
Shade Trees Required	Shade Trees Proposed to be Planted			
26	22	*Please list th	e square footage of	each proposed planting area on the firs
		sheet of the	plan set.	
Fee in Lieu (Trees Required – Trees Proposed) x \$250	Total Disturbed Area \$\$1,000	7		

MISS UTILITY

THE CONTRACTOR SHALL CALL "MISS UTILITY" AT 1-800-257-7777, 48 HOURS PRIOR TO THE START OF WORK. THE CONTRACTOR IS RESPONSIBLE FOR ENSURING THAT ALL UNDERGROUND UTILITIES IN THE AREA OF PROPOSED WORK ARE LOCATED PRIOR TO COMMENCING CONSTRUCTION WORK. THE CONTRACTOR IS RESPONSIBLE FOR COMPLIANCE WITH REQUIREMENTS OF CHAPTER 36A OF THE MONTGOMERY COUNTY CODE.

THE CONTRACTOR IS ALSO RESPONSIBLE FOR LOCATING ALL PRIVATE UTILITIES (NOT LOCATED BY MISS UTILITY) WITHIN HOA PROPERTY AT THEIR EXPENSE. ALL UTILITIES SHOWN ON THE PLANS ARE PROVIDED FOR INFORMATION ONLY AND SHALL BE CONSIDERED APPROXIMATE. HOA SHALL NOT BE RESPONSIBLE FOR LOCATING UNDERGROUND UTILITIES. ANY UTILITIES OR OTHER UNDERGROUND FACILITIES DAMAGED DURING CONSTRUCTION SHALL BE REPAIRED/REPLACED AT THE CONTRACTOR'S SOLE EXPENSE.

DESIGN TRAFFIC DATA

ROADWAY	FLOWER	AVENUE	
CONTROLS / YEARS	2022	2045	
AVERAGE DAILY TRAFFIC (A.D.T.)	11900	13400	
DESIGN HOURLY VOLUME (D.H.V.)	1080	1300	
DIRECTIONAL DISTRIBUTION	50.7%	50.7%	
% TRUCKS - A.D.T.	2.8%	2.8%	
% TRUCKS - D.H.V.	1.7%	1.7%	
DESIGN SPEED M.P.H.	30 MPH		
FUNCTIONAL CLASSIFICATION	urban majof	R COLLECTOR	
CONTROL OF ACCESS	NONE		
INTENSITY OF DEVELOPMENT	URBAN		
TERRAIN	ROLLING		
ANTICIPATED POSTED SPEED	25	MPH	

TI-OI

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES TITLE SHEET

Stantec

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

Bicycle and Pedestrian Priority Areas

DESIGNED BY: UMK DATE: FEBRUARY, 2025 APP'D DATE REVISION DRAWN BY: UMK DATE: FEBRUARY, 2025 CHECKED BY: CC DATE: FEBRUARY, 2025 DRAWING NO .: DATE: RECOMMENDED FOR APPROVAL Chief, Design Section Date APPROVED Date Division of Transportation Engineering

PROJECT MANAGER

240-777-7266

KHURSHEED BILGRAMI. PE

Gaithersburg, MD 20878

100 Edison Park Drive, 4th Floor

khursheed.bilgramil@montgomerycountymd.gov

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

EXPIRATION DATE: _

SCALE: N.T.S.

SHEET<u>OI</u> of <u>87</u>

LICENSE NO:

01 TI-01 TITLE SHEET 02 I-01 INDEX OF SHEETS 03 GN-01 GENERAL NOTES 04 AB-01 ABBREVIATIONS AND SYMBOLS 05 GS-01 GEOMETRIC LAYOUT 06 GS-02 GEOMETRIC LAYOUT	
03 GN-01 GENERAL NOTES 04 AB-01 ABBREVIATIONS AND SYMBOLS 05 GS-01 GEOMETRIC LAYOUT 06 GS-02 GEOMETRIC LAYOUT	
04 AB-01 ABBREVIATIONS AND SYMBOLS 05 GS-01 GEOMETRIC LAYOUT 06 GS-02 GEOMETRIC LAYOUT	
05 GS-01 GEOMETRIC LAYOUT 06 GS-02 GEOMETRIC LAYOUT	
06 GS-02 GEOMETRIC LAYOUT	
07 70 04 70 000 000 000 000	
07 TS-01 TYPICAL SECTIONS	
08 TS-02 TYPICAL SECTIONS	
09 TS-03 TYPICAL SECTIONS	
10 DT-01 ROADWAY SCHEDULES	
11 DT-02 ROADWAY SCHEDULES	
12 DT-03 ROADWAY SCHEDULES	
13 DT-04 PAVEMENT DETAILS	
14 DT-05 ROADWAY DETAILS	
15 DT-06 ROADWAY DETAILS	
16 HD-KY ROADWAY KEY PLAN	
17 PS-01 ROADWAY PLAN	
18 PS-02 ROADWAY PLAN	
19 PS-03 ROADWAY PLAN	
20 HP-01 ROADWAY PROFILE	
21 HP-02 ROADWAY PROFILE	
22 ID-01 INTERSECTION DETAIL	
23 ID-02 INTERSECTION DETAIL	
24 ID-03 INTERSECTION DETAIL	
25 DD-01 DRAINAGE SCHEDULES	
26 DA-01 EXISTING CONDITIONS DRAINAGE AREA MAP	
27 DA-02 EXISTING CONDITIONS DRAINAGE AREA MAP	
28 DA-03 PROPOSED CONDITIONS DRAINAGE AREA MAP	
29 DA-04 PROPOSED CONDITIONS DRAINAGE AREA MAP	
30 DP-01 STORM DRAIN PROFILES	
31 DP-02 STORM DRAIN PROFILES	
32 DP-03 STORM DRAIN PROFILES	
33 ESN-01 EROSION AND SEDIMENT CONTROL NOTES	
34 ESN-02 EROSION AND SEDIMENT CONTROL NOTES AND DETAILS	
35 ES-01 EROSION AND SEDIMENT CONTROL/STORMWATER MANAGEME	
36 ES-02 EROSION AND SEDIMENT CONTROL/STORMWATER MANAGEME	
37 ES-03 EROSION AND SEDIMENT CONTROL/STORMWATER MANAGEME	:NI PLAN
38 LP-01 LANDSCAPE PLAN	
39 LP-02 LANDSCAPE PLAN	
40 LP-03 LANDSCAPE PLAN	
41 LP-04 LANDSCAPE PLAN NOTES AND DETAILS	
42 SND-01 SIGNING AND MARKING DETAILS	
43 SND-02 SIGNING AND MARKING DETAILS	
44 SN-01 SIGNING AND MARKING PLAN	
45 SN-02 SIGNING AND MARKING PLAN	
46 SN-03 SIGNING AND MARKING PLAN	
47 SN-04 SIGNING AND MARKING PLAN	
48 SN-05 SIGNING AND MARKING SCHEDULE	
49 SN-06 SIGNING AND MARKING SCHEDULE	
50 SN-07 SIGNING AND MARKING SCHEDULE	
51 SG-01 SIGNALIZATION PLAN 52 SG-02 SIGNALIZATION DETAILS	
53 SG-03 SIGNALIZATION NOTES 54 SG-04 SIGNALIZATION PLAN	
54 SG-04 SIGNALIZATION PLAN 55 LT-01 LIGHTING PLAN	
56 LT-02 LIGHTING PLAN	
56 LT-02 LIGHTING PLAN 57 LT-03 LIGHTING PLAN	
57 LI-03 LIGHTING PLAN 58 LT-04 LIGHTING PLAN	
60 MT-01 MAINTENANCE OF TRAFFIC - PHASE 1A	

Sheet No.	Drawing No.	Sheet Name
61	MT-02	MAINTENANCE OF TRAFFIC - PHASE 1A
62	MT-03	MAINTENANCE OF TRAFFIC - PHASE 1B
63	MT-04	MAINTENANCE OF TRAFFIC - PHASE 1B
64	MT-05	MAINTENANCE OF TRAFFIC - PHASE 1B
65	MT-06	MAINTENANCE OF TRAFFIC - PHASE 2
66	MT-07	MAINTENANCE OF TRAFFIC - PHASE 2
67	MT-08	MAINTENANCE OF TRAFFIC - PHASE 2
68	MT-09	MAINTENANCE OF TRAFFIC - PHASE 2
69	MT-10	MAINTENANCE OF TRAFFIC - PHASE 3
70	MT-11	MAINTENANCE OF TRAFFIC - PHASE 3
71	MT-12	MAINTENANCE OF TRAFFIC - PHASE 3
72	MT-13	MAINTENANCE OF TRAFFIC - PHASE 3
73	MT-14	MAINTENANCE OF TRAFFIC - PHASE 4
74	MT-15	MAINTENANCE OF TRAFFIC - PHASE 4
75	MT-16	MAINTENANCE OF TRAFFIC - PHASE 4
76	MT-17	MAINTENANCE OF TRAFFIC - PHASE 5
77	MT-18	MAINTENANCE OF TRAFFIC - PHASE 5
78	MT-19	MAINTENANCE OF TRAFFIC - PHASE 5
79	XS-01	ROADWAY CROSS SECTIONS
80	XS-02	ROADWAY CROSS SECTIONS
81	XS-03	ROADWAY CROSS SECTIONS
82	XS-04	ROADWAY CROSS SECTIONS
83	XS-05	ROADWAY CROSS SECTIONS
84	XS-06	ROADWAY CROSS SECTIONS
85	XS-07	ROADWAY CROSS SECTIONS
86	XS-08	ROADWAY CROSS SECTIONS
87	XS-09	ROADWAY CROSS SECTIONS

|-0|

Stantec BPR

rity Areas	

	REVISION	BY	APP'D	DATE	DESIGNED BY: UMK	DATE: FEBRUARY,	2025	
1					DRAWN BY: UMK	DATE: FEBRUARY,	2025	_
+					CHECKED BY: CC	DATE: FEBRUARY,	2025	D
+					DRAWING NO.:	DATE:		1
					RECOMMENDED FOR APPROVAL			
					Chief, Design Section		 Date	
					APPROVED			
					Chief,		 Date	
					Division of Transportation Engi	ineering		SCALI

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES INDEX OF SHEETS

SHEET<u>02</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

LICENSE NO: _ _ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

ALE: NONE

2. FOR CONSTRUCTION, HORIZONTAL SHALL BE BASED ON NAD 83/91DATUM AND VERTICAL SHALL BE BASED ON NAVD 1988 DATUM.

3. INFORMATION CONCERNING UNDERGROUND UTILITIES WAS OBTAINED FROM AVAILABLE RECORDS, BUT THE CONTRACTOR MUST DETERMINE THE EXACT LOCATIONS AND ELEVATIONS OF THE LINES BY DIGGING TEST PITS BY HAND AT ALL UTILITY CROSSINGS, WELL IN ADVANCE OF TRENCHING. IF CLEARANCES ARE LESS THAN SHOWN OR SIX (6) INCHES, WHICHEVER IS LESS, CONTACT MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION'S PROJECT INSPECTOR AND THE APPROPRIATE UTILITY OWNER BEFORE PROCEEDING WITH CONSTRUCTION.

4. RFPAIRS TO UTILITIES OR PROPERTY DAMAGE AS A RESULT OF THE CONTRACTOR'S NEGLIGENCE OR METHOD OF OPERATION MUST BE MADE AT THE CONTRACTOR'S EXPENSE BEFORE PROCEEDING WITH CONSTRUCTION.

5. CALL "MISS UTILITY" AT I-800-257-7777 FORTY-EIGHT (48) HOURS PRIOR TO BEGINNING EXCAVATION TO DETERMINE THE EXACT LOCATION OF EXISTING UTILITIES.

6. CLEARING IS TO BE LIMITED TO THE "LIMIT OF DISTURBANCE" AS SHOWN ON THE PLANS.

7. ALL GRADING SHALL BE DONE IN SUCH A MANNER AS TO PROVIDE POSITIVE DRAINAGE.

8. DISTURBED AREAS ADJACENT TO ESTABLISHED LAWNS AND WATER QUALITY SWALES SHALL BE SODDED. OTHER DISTURBED AREAS SHALL BE SEEDED AND MULCHED.

9. THE CONTRACTOR SHALL OBTAIN A ROADSIDE TREE PERMIT FOR ANY MAINTENANCE, TREATMENT, PLANTING, REMOVAL, OR ROOT CUTTING ON TREES WITHIN THE PUBLIC RIGHT OF WAY. PERMIT REQUIREMENTS MAY BE OBTAINED FROM THE DEPARTMENT OF NATURAL RESOURCES, MARYLAND FOREST, PARK AND WILDLIFE SERVICE, TELEPHONE 301-854-6060

IO. THE LOCATION OF RIGHT-OF-WAY AND EASEMENT LINES SHOWN ON THE PLANS ARE FOR INFORMATION AND GUIDANCE ONLY. NO GUARANTEE IS MADE AS TO THE ACCURACY OF SAID LOCATIONS. PLEASE REFER TO THE APPROPRIATE RIGHT-OF-WAY PLATS.

II. THE CONTRACTOR SHALL INSTALL PEDESTRIAN DETECTABLE WARNING SURFACES AT ALL SIDEWALK & PEDESTRIAN CROSSINGS. LOCATIONS AS DIRECTED BY THE ENGINEER. THE WARNING SURFACES SHALL BE IN CONFORMANCE WITH ADA REQUIREMENTS AND THE PROJECT SPECIAL PROVISION.

12. THE DESIGN FOR THIS PROJECT HAS INCORPORATED FACILITIES FOR THE ELDERLY AND HANDICAPPED IN COMPLIANCE WITH STATE AND FEDERAL LEGISLATION.

13. ALL PROPOSED BUS STOPS SHALL BE ADA COMPLIANT.

14. FOR NEW CURB AND GUTTER ALONG MD 320 (PINEY BRANCH ROAD) AND MD 594-D (ARLISS STREET) REFER TO MD 580.03 NEW COMBINATION CURB AND GUTTER PLACEMENT ALONG EXISTING PAVEMENT. IN NOTE FOR MD 580.03. REPLACE PCC MIX NO. 3 WITH PCC MIX NO. 13.

SURVEY

I. HORIZONTAL DATUM: MARYLAND STATE PLANE COORDINATE SYSTEM

NAD 83/91

VERTICAL DATUM: NAVD 1988 SURVEY UNIT: SURVEY FEET

2. DATE OF SURVEY: SEPTEMBER, 2022

SURVEY PERFORMED BY: MONTGOMERY COUNTY DEPARTMENT OF TRANSPORTATION

100 EDISON PARK DRIVE, 4TH FLOOR GAITHERSBURG, MD 20878

AUGUST, 2022

AMT AND ASSOCIATES, INC. CONSULTING ENGINEERS

800 KING FARM BOULEVARD, 4TH FLOOR

ROCKVILLE, MD 20850

INVERT INFORMATION FOR EX-MH-2 AND EX-MH-3 PROVIDED BY AMT. AMT MAKES NO REPRESENTATION, WARRANTY OR GUARANTEE

OF THE INVERT ELEVATIONS FOR THIS PROJECT.

3. ALL DIMENSIONS, STATIONS, AND ELEVATIONS ARE IN SURVEY FEET UNLESS OTHERWISE SHOWN.

THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING EXISTING TOPOGRAPHIC FEATURES AND ELEVATIONS, ABOVE AND BELOW GROUND, PRIOR TO BEGINNING CONSTRUCTION IN THE FIELD.

THE CONTRACTOR SHALL BRING TO THE NOTICE OF THE ENGINEER ANY DISCREPANCY BETWEEN THE PLANS AND ACTUAL FIELD CONDITIONS.

4. A BOUNDARY SURVEY WAS PERFORMED. IF ANY DISPUTE ARISES AS TO THE LOCATION OF RIGHT-OF-WAY LINES. PROPERTY LINES. OWNERSHIP. ETC.. ADDITIONAL CONSULATATION WITH A MARYLAND-LICENSED SUREVEYOR IS ADVISED.

UTILITES

I. DATE OF INVESTIGATION: UTILITY INVESIGATION

OCTOBER, 2022

PERFORMED BY:

AB CONSULTANTS, INC. 9450 ANNAPOLIS ROAD LANHAM, MD 20706

PHONE: (301) 306-3091 FAX: (301) 306-3092

ALL UTILITY MAPPING (QUALITY LEVEL D) WAS PREPARED BASED ON RECORDS PROVIDED BY UTILITY OWNERS FOR THIS PROJECT.

2. THE CONTRACTOR SHALL NOTIFY MISS UTILITY ONE CALL (811 OR 800-257-7777) 48 HOURS BUT NOT MORE THAN 10 DAYS PRIOR TO ANY EXCAVATION WORK.

3. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE ALL UTILITIES PRIOR TO BEGINNING EXCAVATION.

4. THE FOLLOWING UTILITY COMPANIES SHALL ALSO BE SPECIFICALLY NOTIFIED SIX WEEKS PRIOR TO THE BEGINNING OF CONSTRUCTION:

> PEPCO, ED KOVAR, 301-548-4340 AT&T, GARY WIGFIELD, 301-874-1180 FIBERLIGHT, MIKE JOHNSON, 678-347-9265 WASHINGTON GAS LIGHT COMPANY, COLIN BURKE, 703-750-5541 COMCAST, DWAYNE DOUTY, 301-456-8957 WASHINGTON SUBURBAN SANITARY COMMISSION, KEVIN LETHBRIDGE, 301-206-7339 VERIZON, JON BOBEL, 301-282-2942 VERIZON BUSINESS, ADAM RICE, 571-220-8978

5. NO MECHANIZED EQUIPMENT SHALL BE USED FOR EXCAVATION IN CLOSE PROXIMITY TO UTILITIES. CONTRACTOR SHALL HAND DIG ONLY.

6. THE CONTRACTOR SHALL USE HAND EXCAVATION METHODS WHEN EXCAVATION OCCURS WITHIN 24 INCHES OF A GAS FACILITY.

7. THE CONTRACTOR IS RESPONSIBLE FOR SUPPORTING AND PROTECTING EXISTING UTILITIES AS DIRECTED BY THE ENGINEER AND UTILITY OWNER. THE CONTRACTOR IS RESPONSIBLE FOR ANY DAMAGES TO EXISTING UTILITIES DUE TO NEGLIGENCE.

8. MD 320 (PINEY BRANCH ROAD) HAS AN ESIMTAED PAVEMENT STRUCTURE OF 8.5" ASPHALT OVER 6" STONE. PLEASE REFER TO MD 587.01 REPAIRING PAVEMENT OPENINGS FOR UTILITY TRENCHES AND USE SUPERPAVE ASPHALT MIX 19.0MM FOR FULL DEPTH PATCH. PG 64S-22. LEVEL 2 FOR UTILITY PATCHING.

GN-01



810 Gleneagles Court, Suite 300

Baltimore, MD 21286

www.stantec.com



) .	REVISION	BY	APP'D	DATE	DESIGNED BY: UMK	DATE: FEBRUARY,	2025	
					DRAWN BY: UMK	DATE: FEBRUARY,	2025	
					CHECKED BY: CC	DATE: FEBRUARY,	2025	
					DRAWING NO.:	DATE:		
					RECOMMENDED FOR APPROVAL			
					Chief, Design Section		Date	
					APPROVED			
					Chief, Division of Transportation Engli	neering	Date	
						-		

FLOWER AVENUE SEPARATED BIKE LANES

GENERAL NOTES

DEPARTMENT OF TRANSPORTATION

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

SHEET<u>03</u> of <u>87</u>

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO:

EXPIRATION DATE:

ABBREVIATIONS

A.A.S.H.T.O.	American Association of State Highway	H.D.P. High Density Polyetheyle	ne R	Radius
	Transportation Officials	HDWLHeadwall		Reinforcement
ABUT	Abutment	H.E.R.C.P Horizontal Elliptical Reinfo		Required
	Average Daily Traffic	Concrete Pipe		Rock Fragments
AHD		H.P. High Point	RT	
	Approximate	H.S.D. Headlight Sight Distance		/ Right of Way
B_ or B∕L		INInch		Reinforced Cement Pipe
	Back /Book	I.S.TInlet Sediment Trap		Reinforced Cement Concrete Pipe
BIT		INVInvert		Rock Quality Desgnation
	Bituminous Concrete	J.BJunction Box		Rootmat
	Bench Mark	KK Inlet	S	
	Bottom of Footing	LLength		Sanitary Sewer
ВОТ		L.F. Linear Feet		Southbound
BRG	_	L.L. Liquid Limit		Storm Drain
	Center of Curve	LODLimit of Disturbance		Surface Drain Ditch
	Cable Television	LONGLongitudinal		Super Elevation
	California Bearing Ratio	L.PLight Pole		Silt Fence
	Contraction Joint	LTLeft	S.F	Square Feet
© or C∕L		MAC Macadam	SHLDR	Shoulder
	Class or Clear	MC Moisture Content	SHA	State Highway Administration
	Chainlink Fence	MAX Maximum	SHT	Sheet
	Corrugated Metal Pipe	MDDMaximum Dry Content	S.P.P	Structural Plate Pipe
C.O		MOD Modified		Standard Penetration Testing
	Combination	MIN Minimum	S.S	Stainless Steel
CONC.		MN Managed Roadway		Stopping Sight Distance
	Construction	M.S.EMechanically Stablilized		Super Silt Fence
COR		NNorth		Standard
CORR.		NBNorthbound		Station
	Cubic Yard	NE Northeast	STIFF	Stiffener
	Degree of Curve	NONumber		Single Opening
	Design Hourly Volume	NP Non–Plastic		Square Yards
D.I		N.T.S		Stormwater Management
DIA		O.COn Center		Tangent
	Double Opening	OH Overhead		Telephone
	Design Speed	OMC Optimum Moisture		To Be Removed
DWG		PAV'T		Top of Cover
E		PC Point of Curvature		Temporary
E		PCC Point of Compound Curva		Top of Grate
	External Distance	P/CPoint of Crown		Traverse Line
EA		P/GE Profile Grade Elevation		Top of Manhole
EB		P.G.L Profile Grade Line		Top of Footing
	Expansion Joint	P/GL Profile Ground Line		Traverse
EL. or ELEV.		PPlate		Temporary Swale
E.R.C.C.P	Elliptical Reinforced Cement	P/RPoint of Rotation		Top of Slab
FO	Concrete Pipe	P.I. Plasticity Index		Topsoil
	End Section	P.I Point of Intersection		Typical
EX. or EXIST.	_	POC Point On Curve		Under Drain
FT		POTPoint On Tangent		Underground
F or FL		PRProposed		Unless Otherwise Noted
	Flat Bottom Ditch	PR. ROW Proposed Right of Way		Utility Pole
	Fire Hydrant	PROP. Proposed		Unified Soil Classification
	Fiber Optic	PRCPoint of Reverse Curve		United States Department of Agriculture
	Face of Curb	PTPoint		Vertical Clearance
	Full Super Elevation	PT Point of Tangency		Vertical Curve Length
FWD		PVC Point of Vertical Curve	W	
G		P.V.C. Polyvinyl Chloride	W	
GL		PVI Point of Vertical Intersection	_	Westbound
	General Purpose Roadway	PVRC Point of Vertical Reverse (Water Meter
G.V	Gas Valve	PVTPoint of Vertical Tangency	W.S	Wrapped Steel
	1.1 11			

SYMBOLS

ISTING RIGHT OF WAY LINE		CUT SLOPE	····-
ROPOSED RIGHT OF WAY LINE		FILL SLOPE	
PROPOSED TRAFFIC BARRIER		LIMIT OF DISTURBANCE	
EXISTING TRAFFIC BARRIER		SILT FENCE	
EXISTING WOOD FENCE LINE	T	SUPER SILT FENCE	
EXISTING CHAIN LINK FENCE LINE		DIVERSION FENCE	
BASE OR SURVEY LINE	31 +50 32	STONE CHECK DAM	
EXISTING FIRE HYDRANT		TEMPORARY STONE OUTLET STRUCTURE	
PROPOSED STORM DRAIN		TEMPORARY GABION OUTLET STRUCTURE	
EXISTING STORM DRAIN		AT-GRADE INLET PROTECTION	
EXISTING INLET		CURB INLET PROTECTION	
EXISTING UTILITY POLE	\Diamond	COMBINATION INLET PROTECTION	
EXISTING TREE	\bigcirc	MEDIAN INLET PROTECTION	
EXISTING TREE LINE		STANDARD INLET PROTECTION	
EXISTING TREE TO BE REMOVED	X	TEST HOLE LOCATION	
EXISTING GAS LINE (QUALITY LEVEL D)	G	STABILIZED CONSTRUCTION ENTRANCE	
EXISTING GAS LINE (QUALITY LEVEL B /C)			
EXISTING ELECTRIC LINE (QUALITY LEVEL D)	E	TEMPORARY ORANGE CONSTRUCTION FENCE	T
EXISTING ELECTRIC LINE (QUALITY LEVEL B /C)			IP
EXISTING TELEPHONE LINE (QUALITY LEVEL D)			
EXISTING TELEPHONE LINE (QUALITY LEVEL B /C)			
EXISTING SANITARY SEWER LINE (QUALITY LEVEL D)			`
·	*		,
EXISTING SANITARY SEWER LINE (QUALITY LEVEL B /C)	— — SAN — — — — — — — — — — — — — — — — — — —	CRITICAL ROOT ZONE	[
EXISTING WATER LINE (QUALITY LEVEL D)			\
EXISTING WATER LINE (QUALITY LEVEL B /C)	w		
		TREE REMOVAL	

AB-01

Stantec

									AB-OI
	REVISION	BY	APP'D	DATE	DESIGNED BY: UMK	DATE: FEBRU	ARY, 2025	DEDARTMENT	F TRANSPORTATION
					DRAWN BY: UMK	DATE: FEBRU	ARY, 2025		
+					CHECKED BY: CC	DATE: FEBRU	ARY, 2025		PORTATION ENGINEERING
+					DRAWING NO.:	DATE:		MONTGOMERY	COUNTY, MARYLAND
					RECOMMENDED FOR APPROCE Chief, Design Section APPROVED	OVAL	Date	SEPARATED	R AVENUE) BIKE LANES ONS & SYMBOLS
					Chief, Division of Transportation	n Engineering	Date	SCALE: NONE	SHEET <u>04</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED
PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE


LICENSE NO: _


H.B. Handbox

OF MARYLAND.

__ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com





		BASELIN	IE DATA		
CURVE	POINT NO.	STATION	NORTH	EAST	BEARING
	PT	100 + 00.00	484786.2772	1311340.8211	N 11° 02' 02.6383" \
	PC	108 + 01.90	485573.3552	1311187.3429	N 11° 02' 02.6383"
EA 01	PI	109 + 47.57	485716.3285	1311159.4635	
FA-01	CC		483937.4200	1302797.8201	
	PCC	110 + 93.21	485858.2689	1311126.7286	N 12° 59' 12.2413"
	PCC	110 + 93.21	485858.2689	1311126.7286	N 12° 59' 12.2413" \
FA 00	PI	111 + 89.09	485951.6955	1311105.1822	
FA-02	CC		485198.2945	1308265.0430	
	PT	112 + 84.90	486043.5178	1311077.5878	N 16° 43' 35.4820"

	TRAVERSE POINTS				
POINT NO.	NORTH	EAST	ELEVATION		
546240	484878.7417	1311283.4065	272.31		
546250	484907.1757	1311356.2199	274.49		
546260	484972.5848	1311281.7822	274.85		
54630	485091.7017	1311242.7621	277.65		
546230	485116.5786	1311299.7306	278.75		
546210	485165.0790	1311237.4348	280.13		
546220	485212.4705	1311282.3385	282.93		
546200	485352.4756	1311209.6440	282.77		
546190	485399.1821	1311248.8661	290.39		
54627	485420.2558	1311243.7496	291.49		
546180	485473.5875	1311186.0421	293.94		
546160	485829.8925	1311165.5251	307.00		
546150	485915.3238	1311144.7781	309.50		

Stantec / 810 Gleneagles Court, Suite 300

SCALE: 1" = 20'

۷0.	REVISION	BY	APP'D	DATE	DESIGNED BY: UMK DATE: FE	EBRUARY, 2025	
					DRAWN BY: UMK DATE: FE	BRUARY, 2025	
					CHECKED BY: CC DATE: FE	EBRUARY, 2025	
					DRAWING NO.: DATE:		
					RECOMMENDED FOR APPROVAL		
					Chief, Design Section	Date	
					APPROVED		
					Chief,	 Date	
					Division of Transportation Engineering		SC

FLOWER AVENUE SEPARATED BIKE LANES GEOMETRY SHEET

DEPARTMENT OF TRANSPORTATION

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

SHEET<u>06</u> of <u>87</u> SCALE: I"=20'

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

OF MARYLAND. LICENSE NO: _

EXPIRATION DATE:

Baltimore, MD 21286 www.stantec.com

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO: _ _ EXPIRATION DATE: _



DRAWN BY: UMK DATE: FEBRUARY, 2025 DATE: FEBRUARY, 2025 CHECKED BY: CC DRAWING NO .: DATE: RECOMMENDED FOR APPROVAL Chief, Design Section Date APPROVED Date Division of Transportation Engineering

DEPARTMENT OF TRANSPORTATION MONTGOMERY COUNTY, MARYLAND

TS-01 DIVISION OF TRANSPORTATION ENGINEERING

APP'D DATE DESIGNED BY: UMK DATE: FEBRUARY, 2025 BY REVISION

BRICK LANE BRICK BUFFER BUFFER SEE NOTE 3 — 2% --- SEE NOTE 3 MATCH EX. 2% MATCH EX. MATCH EX. · CONCRETE SIDEWALK (TYP.) SEE DETAIL C ON DT-04 PROPOSED CONCRETE CURB, TYPE D MOD (TYP.) P/GL, PGL, P/GE, PGE — MILL AND OVERLAY 9.33' **VARIES** SEE DETAIL A ON DT-05 SEE DETAIL B ON DT-04 PROPOSED CONCRETE PROPOSED FLOATING SIDEWALK ASPHALT BIKE LANE (TYP.) -CURB AND GUTTER, TYPE D (TYP.) LANE CONCRETE CURB PATCH (TYP.) -BUS STOP SEE DETAIL D ON DT-04 SEE STD. MD 620.02-01 SEE DETAIL E ON DT-04 PROPOSED CONCRETE — CURB, TYPE C (TYP.) 2% SEE STD. MD 620.02-01 2% FLOWER AVENUE FROM PINEY BRANCH ROAD (MD 320) TO FLOWER AVENUE URBAN PARK BRICK PAVERS (TYP.) — - SEE NOTE 3 SEE STD MC-111.02 STA 99 + 74 - STA 101 + 50 CONCRETE SIDEWALK **B** CONSTRUCTION SEE DETAIL C ON DT-04 FLOWER AVENUE STA. 100 + 17 TO 100 + 60 40' TO 70' EXISTING RIGHT-OF-WAY BRICK BRICK PAVĘRS PAVERS **VARIES** VARIES PROPOSED BIKE SIDEWALK SIDEWALK PARKING SB THRU LANE SB LEFT TURN LANE NB THRU LANE PARKING LANE BRICK BRICK BUFFER BUFFER SEE NOTE 3 MATCH MATCH SEE NOTE 3 — 2% EX. MATCH EX. MATCH EX. CONCRETE SIDEWALK (TYP.) SEE DETAIL C ON DT-04 PROPOSED CONCRETE P/GL, PGL, P/GE, PGE — - BRICK PAVERS (TYP.) CURB, TYPE D MOD (TYP.) --- PROPOSED CONCRETE SEE STD MC-111.02 SEE DETAIL A ON DT-05 CURB, TYPE C (TYP.) MILL AND OVERLAY CURB AND GUTTER, TYPE D (TYP.) ASPHALT BIKE LANE (TYP.) -SEE STD. MD 620.02-01 SEE DETAIL B ON DT-04 SEE STD. MD 620.02-01 SEE DETAIL D ON DT-04 FULL DEPTH PAVING (TYP.) BRICK SEE DETAIL A ON DT-04 **PAVERS VARIES PAVERS** PROPOSED SIDEWALK 13.67 **VARIES** LANDSCAPE LANE BIKE SIDEWALK PROPOSED BUFFER LANE BRICK SEE NOTE 3 BUFFER 2% ——— SEE NOTE 3 2% 2% 2% PROPOSED CONCRETE CURB, TYPE D MOD (TYP.) CONCRETE SIDEWALK (TYP.) SEE DETAIL C ON DT-04 SEE DETAIL A ON DT-05 - PROPOSED CONCRETE ASPHALT BIKE LANE (TYP.) — BRICK PAVERS (TYP.) CURB AND GUTTER, TYPE D (TYP.) SEE DETAIL D ON DT-04 CONCRETE CURB PATCH (TYP.) -SEE STD MC-111.02 SEE STD MC-111.02 SEE STD. MD 620.02-01 SEE DETAIL E ON DT-04 PROPOSED CONCRETE — CURB, TYPE C (TYP.) SEE STD. MD 620.02-01 STA. 101 + 91 TO 102 + 51 STA. 101 + 74 TO 102 + 34 FLOWER AVENUE

B CONSTRUCTION FLOWER AVENUE

70' EXISTING RIGHT-OF-WAY

NB THRU LANE

2' - 9.33'

PROPOSED

VARIES

SIDEWALK

10'

NB LEFT TURN LANE

FROM PINEY BRANCH ROAD (MD 320) TO FLOWER AVENUE URBAN PARK STA 101+50 - STA 104+43

SEE PLAN SHEETS FOR LIMITS AND PAVEMENT TYPE. SEE DT-01 FOR PAVEMENT DETAILS. SEE PLAN SHEETS FOR LIMITS AND TYPE OF PROPOSED

VARIES

SIDEWALK

2' – 12'

PROPOSED

13' – 17'


SB THRU LANE

FLOWER AVENUE SEPARATED BIKE LANES TYPICAL SECTIONS

SCALE: I"=5'

SHEET<u>07</u> of <u>87</u>





FLOWER AVENUE FROM PINEY BRANCH ROAD (MD 320) TO FLOWER AVENUE URBAN PARK STA 104 + 43 - STA 106 + 34


TS-02 SEE PLAN SHEETS FOR LIMITS AND PAVEMENT TYPE. APP'D DATE DESIGNED BY: UMK DATE: FEBRUARY, 2025 REVISION BY DEPARTMENT OF TRANSPORTATION SEE DT-01 FOR PAVEMENT DETAILS. DATE: FEBRUARY, 2025 DRAWN BY: UMK SEE PLAN SHEETS FOR LIMITS AND TYPE OF PROPOSED DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND DATE: FEBRUARY, 2025 CHECKED BY: CC SCALE: 1'' = 5'DATE: DRAWING NO .: RECOMMENDED FOR APPROVAL FLOWER AVENUE Stantec Chief, Design Section Date SEPARATED BIKE LANES APPROVED TYPICAL SECTIONS Bicycle and Pedestrian Priority Areas 810 Gleneagles Court, Suite 300 Date Baltimore, MD 21286 Division of Transportation Engineering

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

LICENSE NO: _ _ EXPIRATION DATE: _

www.stantec.com

SCALE: I"=5' SHEET<u>08</u> of <u>87</u>



B CONSTRUCTION FLOWER AVENUE

PAVERS

LANE

2%

PROPOSED

BRICK

BUFFER

SB THRU LANE

2% MATCH EX.

MILL AND OVERLAY

SEE DETAIL B ON DT-04

SEE DETAIL E ON DT-04

SEE DETAIL A ON DT-04

FULL DEPTH PAVING

CONCRETE CURB PATCH (TYP.) —

VARIES

SIDEWALK

SEE NOTE 3 —

PROPOSED CONCRETE

CURB, TYPE D MOD (TYP.)

ASPHALT BIKE LANE (TYP.) —

PROPOSED CONCRETE —

BRICK PAVERS (TYP.) —

SEE STD MC-111.02

CURB, TYPE C (TYP.)

SEE STD. MD 620.02-01

SEE DETAIL D ON DT-04

SEE DETAIL A ON DT-05

70' EXISTING RIGHT-OF-WAY

NB THRU LANE

/ P/GL, PGL, P/GE, PGE

MATCH EX.

PROPOSED

BRICK

BUFFER

PROPOSED CONCRETE

9.33'

PROPOSED FLOATING

BUS STOP

SEE STD. MD 620.02-01

PAVERS

CURB AND GUTTER, TYPE D (TYP.)

BIKE

LANE

VARIES

SIDEWALK

- BRICK PAVERS (TYP.)

VARIES

SIDEWALK

BRICK

PAVERS

SEE NOTE 3

- CONCRETE SIDEWALK (TYP.)

SEE DETAIL C ON DT-04

	MODIFIED TYPE D CURB (ITEM NO. 600000-A)		
QTY (LF)	STATION / OFFSET	REMARKS	
80	STA. 99+94.39 /27.44' RT TO STA. 100+70.64 /38.33' RT	SEE DETAIL A ON DT-05	
117	STA. 100 + 29.03 /11.47' LT TO STA. 101 + 03.73 /72.77' LT	SEE DETAIL A ON DT-05	
53	STA. 100 + 83.65 /38.33' RT TO STA. 101 + 26.49 /52.19' RT	SEE DETAIL A ON DT-05	
117	STA. 101 + 75.86 /56.91 LT TO STA. 102 + 78.92 /35 LT	SEE DETAIL A ON DT-05	
72	STA. 101 + 91.08 /50' RT TO STA. 102 + 54.94 /37.67' RT	SEE DETAIL A ON DT-05	
106	STA. 102+72.56 /37.67' RT TO STA. 103+70.34 /37.67' RT	SEE DETAIL A ON DT-05	
96	STA. 103+08.92 /35' LT TO STA. 103+98.39 /35' LT	SEE DETAIL A ON DT-05	
199	STA. 103 + 90.97 /37.67' RT TO STA. 105 + 86.59 /35.04' RT	SEE DETAIL A ON DT-05	
44	STA. 104+13.39 /35' LT TO STA. 104+49.15 /36.73' LT	SEE DETAIL A ON DT-05	
24	STA. 104+62.24 /33.04 LT TO STA. 104+79.09 /28.39 LT	SEE DETAIL A ON DT-05	

STANDARD TYPE C CURB 8 INCH X 11 INCH MINIMUM (ITEM NO. 634131)		
QTY (LF)	STATION / OFFSET	REMARKS
73	STA. 99 + 96.50 /22.91' RT TO STA. 100 + 67.10 /30.33' RT	SEE STD MD 620.02-01
33	STA. 100 + 83.31 /30.33' RT TO STA. 101 + 12.63 /25.97' RT	SEE STD MD 620.02-01
15	STA. 101 + 17.56 /25.14' RT TO STA. 101 + 29.20 / 30.33' RT	SEE STD MD 620.02-01
70	STA. 100 + 42.09 /17.57 LT TO STA. 101 + 04.41 /22.94 LT	SEE STD MD 620.02-01
13	STA. 101 + 09.34 /23.77' LT TO STA. 101 + 15.60 /30.26' LT	SEE STD MD 620.02-01
45	STA. 101 + 08.73 /72.73' LT TO STA. 101 + 15.60 /35.26' LT	SEE STD MD 620.02-01
25	STA. 101 + 29.20 /35.33' RT TO STA. 101 + 31.02 /50.07' RT	SEE STD MD 620.02-01
38	STA. 101 + 70.94 /55.94 LT TO STA. 101 + 83.40 /32 LT	SEE STD MD 620.02-01
17	STA. 101 + 83.40 /27' LT TO STA. 101 + 95.17 /20.15' LT	SEE STD MD 620.02-01
8	STA. 101 + 87.99 /34.67' RT TO STA. 101 + 90.75 /38.14' RT	SEE STD MD 620.02-01
13	STA. 101 + 87.99 /29.67' RT TO STA. 101 + 95.17 /21.93' RT	SEE STD MD 620.02-01
44	STA. 102+00.17 /21.93' RT TO STA. 102+44.93 /29.67' RT	SEE STD MD 620.02-01
71	STA. 102+00.17 /20.15' LT TO STA. 102+78.92 /27' LT	SEE STD MD 620.02-01

SEE STD MD 620.02-01

STA. 102 + 70.59 /29.67' RT TO STA. 103 + 72.32 /29.67' RT

STA. 103 + 08.92 /27' LT TO STA. 103 + 98.39 /27' LT

STA 104+13.39 /27' LT TO STA 104+49.15 /26.81' LT

STATION / OFFSET

STA. 100 + 91.99 /28.26' LT TO STA. 100 + 93.35 /20.19' LT STA. 101+00.72 /23.67' RT TO STA. 101+01.48 /28.33' RT

STA. 101+10.46 /42.93 LT TO STA. 101+18.67 /42.94 LT

STA. 102 + 11.67 /18.67' LT TO STA. 102 + 16.67 /25' LT

STA. 102 + 11.67 /19.33' RT TO STA. 102 + 11.67 /27.67' RT

STA. 101 + 29.90 /44.10' RT TO STA, 101 + 34.58 /41.82' RT

QTY (LF)

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _

THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED

EXPIRATION DATE:

OR APPROVED BY ME, AND THAT IAM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

16

STA. 103 + 92.97 /29.67' RT TO STA. 105 + 86.59 /27' RT

STA. 104 + 62.24 /23.96' LT TO STA. 104 + 77.51 /20.55' LT

DETE	CTABLE WARNING SURFACE FOR CURB RAN	MPS (ITEM NO. 655120)
QTY (SF)	STATION / OFFSET	REMARKS
10	STA. 100 + 22.03 /33.20' LT	SEE STD MD 655.40
10	STA. 100 + 53.36 /29.67 RT	SEE STD MD 655.40
10	STA. 100 + 53.36 /36' RT	SEE STD MD 655.40
16	STA. 100 + 91.82 /36' LT	SEE STD MD 655.40
16	STA. 101 + 91.82 /30.26 LT	SEE STD MD 655.40
16	STA. 100 + 93.66 /18.21 LT	SEE STD MD 655.40
16	STA. 101 + 00.44 /21.67' RT	SEE STD MD 655.40
16	STA. 101 + 01.86 /30.33' RT	SEE STD MD 655.40
16	STA. 101 + 02.80 /43.21 LT	SEE STD MD 655.40
16	STA. 101 + 02.97 /36' RT	SEE STD MD 655.40
16	STA. 101 + 08.46 /43' LT	SEE STD MD 655.40
16	STA. 101 + 20.72 /43' LT	SEE STD MD 655.40
16	STA. 101 + 23.30 /48' RT	SEE STD MD 655.40
16	STA. 101 + 28.52 /45.63' RT	SEE STD MD 655.40
16	STA. 101 + 36.59 /42' RT	SEE STD MD 655.40
16	STA. 101 + 74.46 /40.82 LT	SEE STD MD 655.40
16	STA. 101 + 80.45 /42.98' LT	SEE STD MD 655.40
16	STA. 101 + 82.97 /41.18' RT	SEE STD MD 655.40
16	STA. 101 + 88.25 /41.96' RT	SEE STD MD 655.40
16	STA. 101 + 84.71 /46.74 LT	SEE STD MD 655.40
10	STA. 101 + 93.30 /44.59' RT	SEE STD MD 655.40
16	STA. 102 + 11.67 /32.67 LT	SEE STD MD 655.40
16	STA. 102 + 11.67 /27' LT	SEE STD MD 655.40
16	STA. 102 + 11.67 /16.67' LT	SEE STD MD 655.40
16	STA. 102 + 11.67 /16.67' RT	SEE STD MD 655.40
16	STA. 102 + 11.67 /29.67 RT	SEE STD MD 655.40
16	STA. 102 + 11.67 /35.33' RT	SEE STD MD 655.40

DETECTABLE DIRECTIONAL STRIP (ITEM NO. 600000-B)

	METAL HANDRAIL (ITEM NO. 600000-C)			
QTY (LF)	STATION / OFFSET	REMARKS		
33	STA. 100 + 17.90 /21.67' RT TO STA. 100 + 58.86 /21.67' RT	SEE DETAIL B ON DT-06		
	5 INCH CONCRETE SIDEWALK (ITEM NO. 655105)			
QTY (SF)	STATION / OFFSET	REMARKS		
900	STA. 99 + 73.85 /21.11' RT	SEE DETAIL C ON DT-04		
300	STA. 100 + 16.90 /21.67' RT	SEE DETAIL C ON DT-04		
97	STA. 100 + 20.12 /24.85 LT	SEE STD MD 655.11		
800	STA. 100 + 26.60 /38.20' LT	SEE DETAIL C ON DT-04		
49	STA. 100 + 53.36 /29.67' RT	SEE STD MD 655.11		
49	STA. 100 + 53.36 /36' RT	SEE STD MD 655.11		
360	STA. 100 + 86.55 /36' RT	SEE DETAIL C ON DT-04		
100	STA. 100 + 93.66 /18.21' LT	SEE DETAIL C ON DT-04		
71	STA. 101 + 00.44 /21.67 RT	SEE DETAIL C ON DT-04		
150	STA. 100 + 91.82 /35.93 LT	SEE STD MD 655.11		
81	STA. 101 + 02.97 /36' RT	SEE STD MD 655.11		
77	STA. 101 + 23.65 /48.54 RT	SEE STD MD 655.11		
98	STA. 101 + 08.43 /40' LT	SEE DETAIL C ON DT-04		
75	STA. 101 + 27.91 /45' RT	SEE DETAIL C ON DT-04		
54	STA. 101 + 74.46 /41' LT	SEE DETAIL C ON DT-04		
40	STA. 101 + 82.97 /41' RT	SEE DETAIL C ON DT-04		
968	STA. 101 + 75.46 /61.71 LT	SEE DETAIL C ON DT-04		
74	STA. 101 + 84.88 /46.58 LT	SEE STD MD 655.11		
51	STA. 101 + 93.30 /44.59 RT	SEE STD MD 655.11		
481	STA. 101 + 96.27 /40.06' RT	SEE DETAIL C ON DT-04		
73	STA. 102+11.67 /32.67 LT	SEE STD MD 655.11		
84	STA. 102 + 11.67 /16.67 LT	SEE DETAIL C ON DT-04		
105	STA. 102+11.67 /16.67' RT	SEE DETAIL C ON DT-04		
73	STA. 102 + 11.67 /35.33 RT	SEE STD MD 655.11		

8 INCH PORTLAND CEMENT CONCRETE PAVEMENT			
FOR DRIVEWAY MIX 9 (ITEM NO. 561118)			
QTY (SY)	STATION / OFFSET	REMARKS	
38.5	STA. 100 + 73.29 /21.67 RT	SEE DETAIL C ON DT-05	
42.5	STA. 102 + 59.93 /24.67 RT	SEE DETAIL C ON DT-05	
48.5	STA. 102 + 93.92 /24.67 LT	SEE DETAIL C ON DT-05	
43.5	STA. 103 + 82.83 /24.67 RT	SEE DETAIL C ON DT-05	
24	STA. 104+05.89 /24.67 LT	SEE DETAIL C ON DT-05	

SEE DETAIL C ON DT-04

STA. 102 + 73.00 /37.67' RT

STA. 103 + 90.97 /37.67' RT

STA. 103 + 08.92 /35' LT

STA. 104 + 13.39 /35' LT

2752

291

	10 INCH REINFORCED CONCRETE SIDEWAL	_K (ITEM NO. 600000-D)
QTY (SF)	STATION / OFFSET	REMARKS
84	STA. 100 + 32.87 /27.67 RT	SEE DETAIL G ON DT-04

	BRICK SIDEWALK (ITEM NO. 655383)			
QTY (SF)	STATION / OFFSET	REMARKS		
460	STA. 99 + 96.92 /21' RT TO STA. 101 + 37.35 /66.47' RT	SEE STD MC-111.02		
387	STA. 100 + 29.03 /11.46 LT TO STA. 100 + 85.21 /35.93 LT	SEE STD MC-111.02		
690	STA. 100 + 39.67 /12.44 LT TO STA. 101 + 10.69 /74.53 LT	SEE STD MC-111.02		
361	STA. 101 + 67.80 /58.12' LT TO STA. 102 + 78.92 /27' LT	SEE STD MC-111.02		
522	STA. 101 + 81.31 /67.53' RT TO STA. 102 + 51.19 /34.67' RT	SEE STD MC-111.02		
207	STA. 102+15.67 /37' LT TO STA. 102+78.92 /42' LT	SEE STD MC-111.02		
485	STA. 102 + 70.59 /29.67' RT TO STA. 103 + 72.32 /29.67' RT	SEE STD MC-111.02		
244	STA. 103 + 09.58 /34 LT TO STA. 103 + 97.72 /34 LT	SEE STD MC-111.02		
883	STA. 103 + 91.90 /36.67' RT TO STA. 105 + 85.93 /32.77' RT	SEE STD MC-111.02		
163	STA. 104+14.05 /32.67' LT TO STA. 104+48.50 /36.91' LT	SEE STD MC-111.02		
140	STA. 104 + 62.91 /32.86 LT TO STA. 104 + 78.44 /28.48 LT	SEE STD MC-111.02		
405	STA. 104 + 98.57 /23' LT TO STA. 105 + 92.54 /23' LT	SEE STD MC-111.02		

CONCRETE STEPS (ITEM NO. 697009)			
QTY (CY)	STATION / OFFSET		REMARKS
5	STA. 103 + 72.72 /42' LT		SEE STD MD 657.00
		BUS SHELTER (ITEM NO. 70	00000–A)

REMARKS

SEE DETAIL C ON DT-06

	ANDARD TIPE D CURB 8 INCH X 14 INCH	1VIII VIIVIOIVI (ITEIVI 140: 00+140)
QTY (LF)	STATION / OFFSET	REMARKS
18	STA. 99 + 78.78 20.62' RT TO STA. 99 + 97.39 27.44' RT	SEE STD MD 620.02-01
3	STA. 99 + 96.50 22.91' RT TO STA. 99 + 96.92 21' RT	SEE STD MD 620.02-01
37	STA. 100 + 23.35 41.99' LT TO STA. 100 + 29.03 11.45' LT	SEE STD MD 620.02-01
8	STA. 100 + 39.67 12.44' LT TO STA. 100 + 42.09 17.57' LT	SEE STD MD 620.02-01
13	STA. 100 + 59.71 21' RT TO STA. 100 + 67.10 30.33' RT	SEE STD MD 620.02-01
13	STA. 100 + 83.31 30.33' RT TO STA. 100 + 86.86 21' RT	SEE STD MD 620.02-01
15	STA. 100 + 86.73 30.26' LT TO STA. 100 + 88.73 17.07' LT	SEE STD MD 620.02-01
11	STA. 100 + 95.37 21' RT TO STA. 101 + 06.74 30.33' RT	SEE STD MD 620.02-01
14	STA. 100 + 96.89 30.26' LT TO STA. 100 + 98.71 18.02' LT	SEE STD MD 620.02-01
11	STA. 101 + 05.51 21' RT TO STA. 101 + 06.74 30.33' RT	SEE STD MD 620.02-01
5	STA. 101 + 03.86 18.50' LT TO STA. 101 + 04.41 22.94' LT	SEE STD MD 620.02-01
15	STA. 101 + 08.42 37.94' LT TO STA. 101 + 21.95 37.9' LT	SEE STD MD 620.02-01
13	STA. 101 + 08.51 47.94 LT TO STA. 101 + 19.72 48.25 LT	SEE STD MD 620.02-01
5	STA. 101 + 09.34 23.77' LT TO STA. 101 + 11.19 20.67' LT	SEE STD MD 620.02-01
6	STA. 101 + 10.95 21' RT TO STA. 101 + 12.63 25.97' RT	SEE STD MD 620.02-01
6	STA. 101 + 15.60 30.26' LT TO STA. 101 + 19.48 28.78' LT	SEE STD MD 620.02-01
7	STA. 101 + 15.60 35.26' LT TO STA. 101 + 21.83 36.15' LT	SEE STD MD 620.02-01
5	STA. 101 + 17.56 25.14' RT TO STA. 101 + 18.09 21' RT	SEE STD MD 620.02-01
7	STA. 101 + 26.49 52.19' RT TO STA. 101 + 28.65 58.78' RT	SEE STD MD 620.02-01
14	STA. 101 + 25.37 41.19' RT TO STA. 101 + 36.80 36.99' RT	SEE STD MD 620.02-01
6	STA. 101 + 29.20 35.33' RT TO STA. 101 + 36.59 36.09' RT	SEE STD MD 620.02-01
8	STA. 101 + 29.20 35.33' RT TO STA. 101 + 36.59 36.09' RT	SEE STD MD 620.02-01
9	STA. 101 + 30.73 49.45' RT TO STA. 101 + 37.41 47.17' RT	SEE STD MD 620.02-01
21	STA. 101 + 31.02 50.07' RT TO STA. 101 + 37.35 66.47' RT	SEE STD MD 620.02-01
7	STA. 101 + 67.80 /58.12 LT TO STA. 101 + 70.94 /55.90 LT	SEE STD MD 620.02-01
7	STA. 101 + 72.07 /45.71 LT TO STA. 101 + 76.72 /46.67 LT	SEE STD MD 620.02-01
11	STA. 101 + 75.56 /35.55 LT TO STA. 101 + 84.15 /39.33 LT	SEE STD MD 620.02-01
5	STA. 101 + 74.81 /61.57 LT TO STA. 101 + 75.86 /56.91 LT	SEE STD MD 620.02-01
8	STA. 101 + 76.55 /32.67 LT TO STA. 101 + 83.40 /32 LT	SEE STD MD 620.02-01
6	STA. 101 + 79.55 /25.47' LT TO STA. 101 + 83.40 /27' LT	SEE STD MD 620.02-01
20	STA. 101 + 84.04 /63.45' LT TO STA. 101 + 97.29 //52' LT	SEE STD MD 620.02-01
5	STA. 101 + 94.04 /16.16' LT TO STA. 101 + 95.17 /20.15' LT	SEE STD MD 620.02-01
5	STA 102+00.17 /20.15' LT TO STA 102+01.17 /16' LT	SEE STD MD 620.02-01
95	STA. 102 + 03.72 / 52.42' LT TO STA. 102 + 78.92 / 42' LT	SEE STD MD 620.02-01
13	STA. 102 + 06.67 /16' LT TO STA. 102 + 06.67 /27' LT	SEE STD MD 620.02-01
13	STA. 102+16.67 /16' LT TO STA. 102+16.67 /27' LT	SEE STD MD 620.02-01
30	STA. 101 + 81.31 /67.53 RT TO STA. 101 + 82.12 /46.15 RT	SEE STD MD 620.02-01
9	STA. 101 + 82.50 /36.15' RT TO STA. 101 + 90.75 /38.14' RT	SEE STD MD 620.02-01
6	STA. 101 + 82.52 /35.63' RT TO STA. 101 + 87.99 /34.67' RT	SEE STD MD 620.02-01
5	STA. 101 + 84.07 /28.28' RT TO STA. 101 + 87.99 /29.67' RT	SEE STD MD 620.02-01
5	STA. 101 + 93.73 /18.03' RT TO STA. 101 + 95.17 /21.93' RT	SEE STD MD 620.02-01
7	STA. 102 + 00.17 /21.93' RT TO STA. 102 + 01.10 /16.05' RT	SEE STD MD 620.02-01
15	STA. 102 + 06.67 /16' RT TO STA. 102 + 06.67 /29.67' RT	SEE STD MD 620.02-01
15 6	STA. 102+16.67 /16' RT TO STA. 102+16.67 /29.67' RT STA. 102+48.28 /24' RT TO STA. 102+49.93 /29.67' RT	SEE STD MD 620.02-01
2	STA. 102+48.28 / 24	SEE STD MD 620.02-01 SEE STD MD 620.02-01
9	STA. 102+53.70 /44.67 RT TO STA. 102+54.06 /46.67 RT STA. 102+70.59 /29.67 RT TO STA. 102+75.54 /24 RT	SEE STD MD 620.02-01 SEE STD MD 620.02-01
<u>9</u> 19	STA. 102+70.39 /29.67 NT TO STA. 102+73.34 /24 NT STA. 102+74.32 /45.33' RT TO STA. 102+79.45 /45.33' RT	SEE STD MD 620.02-01 SEE STD MD 620.02-01
95	STA. 102+74.32 /45.33 RT TO STA. 102+79.43 /45.33 RT STA. 102+74.33 /44.67 RT TO STA. 103+68.58 /44.67 RT	SEE STD MD 620.02-01 SEE STD MD 620.02-01
95 19	STA. 102+74.33 / 44.67	SEE STD MD 620.02-01 SEE STD MD 620.02-01
40	STA. 103+63.57 /69.14' RT TO STA. 103+89.21 /44.67' RT	SEE STD MD 620.02-01
9	STA. 103+65.37 / 09.14 RT TO STA. 103+69.21 / 44.07 RT STA. 103+67.37 / 24' RT TO STA. 103+72.32 / 29.67' RT	SEE STD MD 620.02-01 SEE STD MD 620.02-01
9	STA. 103+07.37 / 24 111 10 STA. 103+72.32 / 23.07 111 STA. 103+93.98 / 29.67 RT TO STA. 103+98.30 / 24 RT	SEE STD MD 620.02-01
9 5	STA. 102 + 75.92 /24' LT TO STA. 102 + 78.92 /27' LT	SEE STD MD 620.02-01
5	STA. 103 + 08.92 /27' LT TO STA. 103 + 11.92 /24' LT	SEE STD MD 620.02-01
19	STA. 103 + 08.92 /42' LT TO STA. 103 + 25.67 /44.74' LT	SEE STD MD 620.02-01
5	STA. 103 + 95.39 /24' LT TO STA. 103 + 98.39 /27' LT	SEE STD MD 620.02-01
5	STA. 104 + 13.39 /27' LT TO STA. 104 + 16.39 /24' LT	SEE STD MD 620.02-01
8	STA. 103 + 98.39 /42' LT TO STA. 103 + 98.39 /49.49' LT	SEE STD MD 620.02-01
	STA. 104 + 12.06 /44' LT TO STA. 104 + 12.41 42' LT	SEE STD MD 620.02-01
2	STA. 104 + 44.34 /15.97 LT TO STA. 104 + 49.15 /26.81 LT	SEE STD MD 620.02-01
14 2		SEE STD MD 620.02-01
14 2	STA. 104 + 49.15 /45' LT TO STA. 104 + 49.15 /47' LT	SEE STD MD 620.02-01
14		

STANDARD TYPE D CURB 8 INCH X 14 INCH MINIMUM (ITEM NO. 634146)

STANDARD TYPE D COMBINATION CURB AND GUTTER					
12 INCH GUTTER PAN 8 INCH MINIMUM (ITEM NO. 634344)					
QTY (LF)	STATION / OFFSET	REMARKS			
5	STA. 99 + 73.85 /20.45' RT TO STA. 99 + 78.78 /20.62' RT	SEE STD MD 620.02-01			
178	STA. 99 + 96.92 /21' RT TO STA. 101 + 37.35 /66.47' RT	SEE STD MD 620.02-01			
132	STA. 100 + 39.67 /12.45 LT TO STA. 101 + 10.69 /74.53 LT	SEE STD MD 620.02-01			
41	STA. 100 + 90.83 /47.33' RT TO STA, 101 + 18.87 /66.20' RT	SEE STD MD 620.02-01			
12	STA. 100 + 99.75 /83.89 LT TO STA. 101 + 03.73 /72.77 LT	SEE STD MD 620.02-01			
344	STA. 101 + 67.80 /58.12' LT TO STA. 104 + 75.00 /12.38' LT	SEE STD MD 620.02-01			
339	STA. 101 + 81.31 /67.53' RT TO STA. 104 + 75.00 /24' RT	SEE STD MD 620.02-01			



REMARKS

SEE DETAIL A ON DT-06

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com



QTY (EA) STATION / OFFSET

STA. 100 + 39.86 26.39' RT

REVISION	BY	APP'D	DATE	DESIGNED BY: UMK	DATE: FEBRU	ARY, 2025
				DRAWN BY: UMK	DATE: FEBRU	ARY, 2025
				CHECKED BY: CC	DATE: FEBRU	ARY, 2025
				DRAWING NO.:	DATE:	
				RECOMMENDED FOR APPRO	DVAL	
				Chief, Design Section APPROVED		Date
				Chief, Division of Transportation	Engineering	Date

FLOWER AVENUE SEPARATED BIKE LANES ROADWAY SCHEDULES

DEPARTMENT OF TRANSPORTATION

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

SHEET<u>10</u> of <u>87</u>

STANDARD	TVPF	\cap	CLIRR	Ω	IVICH	Y 11	INICH	NATIVITIVITATIVA	/ITEN/	NO 63/131)
JIANIJADIJ		١,		()	11 /1 / / / 1	\wedge	11 /1/ /1 1	IVIII VIII VIII JIVI		14() ().)4(.)1

QTY (LF)	STATION / OFFSET	REMARKS
96	STA. 104+97.90 /16.15' LT TO STA. 106+93.21 /16' LT	SEE STD MD 620.02-01
33	STA. 106+08.21 /16' LT TO STA. 106+41.04 /19.15' LT	SEE STD MD 620.02-01
30	STA. 106+11.36 /24.43' RT TO STA. 106+41.30 /21.32' RT	SEE STD MD 620.02-01
101	STA. 107 + 53.19 /19.33' LT TO STA. 107 + 54.00 /16' LT	SEE STD MD 620.02-01
68	STA. 107 + 53.19 /21.33' RT TO STA. 107 + 20.11 /18' RT	SEE STD MD 620.02-01
16	STA. 107 + 40.09 /18' RT TO STA. 107 + 55.52 /18' RT	SEE STD MD 620.02-01
38	STA. 107 + 65.57 /16' LT TO STA. 108 + 03.02 /16' LT	SEE STD MD 620.02-01
18	STA. 107 + 80.23 /18' RT TO STA. 107 + 98.32 /18' RT	SEE STD MD 620.02-01
44	STA. 108 + 08.44 /18' RT TO STA. 108 + 51.89 /18' RT	SEE STD MD 620.02-01
58	STA. 108 + 11.68 /16' LT TO STA. 108 + 63.19 /16' LT	SEE STD MD 620.02-01
159	STA. 108 + 76.85 /18' RT TO STA. 110 + 34.74 /20' RT	SEE STD MD 620.02-01
35	STA. 108 + 81.54 /16' LT TO STA. 109 + 16.02 /16' LT	SEE STD MD 620.02-01
38	STA. 109 + 32.77 /16' LT TO STA. 109 + 70.73 /16' LT	SEE STD MD 620.02-01

DETECTABLE WARNING SURFACE FOR CURB RAMPS (ITEM NO. 655120)

QTY (SF)	STATION / OFFSET	REMARKS
16	STA. 106 + 47.19 /25' LT	SEE STD MD 655.40
16	STA. 106 + 47.19 /19.33' LT	SEE STD MD 655.40
16	STA. 106 + 47.19 /10.67' LT	SEE STD MD 655.40
16	STA. 106 + 47.19 /12.67' RT	SEE STD MD 655.40
16	STA. 106 + 47.19 /21.33' RT	SEE STD MD 655.40
16	STA. 106 + 47.19 /27' RT	SEE STD MD 655.40
10	STA. 106 + 96.69 /25' LT	SEE STD MD 655.40
10	STA. 106 + 96.69 /18.67' LT	SEE STD MD 655.40
10	STA. 106 + 96.69 /20.67' RT	SEE STD MD 655.40
10	STA. 106 + 96.69 /27' RT	SEE STD MD 655.40

DETECTABLE DIRECTIONAL STRIP (ITEM NO. 600000-B)

QTY (LF)	STATION / OFFSET	REMARKS
5	STA. 106 + 47.19 /12.67 LT TO STA. 106 + 47.19 /17.33 LT	SEE DETAIL A ON DT-06
5	STA. 106 + 47.19 /14.67' RT TO STA. 106 + 47.19 /19.33' RT	SEE DETAIL A ON DT-06
5	STA. 106 + 53.19 /10.67 LT TO STA. 106 + 58.19 /10.67 LT	SEE DETAIL A ON DT-06
5	STA. 106 + 94.19 /12.67' RT TO STA. 106 + 99.19 /12.67' RT	SEE DETAIL A ON DT-06

METAL HANDRAIL (ITEM NO. 600000-C)

QTY (LF)	STATION / OFFSET	REMARKS
41	STA. 106 + 55.86 /17.67 LT TO STA. 107 + 02.19 /10.67 LT	SEE DETAIL B ON DT-06
41	STA. 106 + 55.86 /19.67' RT TO STA. 107 + 02.19 /12.67' RT	SEE DETAIL B ON DT-06

8 INCH PORTLAND CEMENT CONCRETE PAVEMENT FOR DRIVEWAY MIX 9 (ITEM NO. 561118)

QTY (SY)	STATION / OFFSET	REMARKS
37.5	STA. 104 + 55.20 /15.33' LT	SEE DETAIL C ON DT-05
42	STA. 104 + 88.22 /11.53 LT	SEE DETAIL C ON DT-05
63	STA. 105 + 98.66 /15.29' RT	SEE DETAIL C ON DT-05
30	STA. 106 + 00.71 /10.67 LT	SEE DETAIL C ON DT-05
39.5	STA. 107 + 30.10 /12.67' RT	SEE DETAIL C ON DT-05
48.5	STA. 107 + 67.88 /12.67' RT	SEE DETAIL C ON DT-05
18	STA. 108 + 03.56 /12.67' RT	SEE DETAIL C ON DT-05
49	STA, 108 + 67,37 /16,67 BT	SEE DETAIL C ON DT-05

5 INCH CONCRETE SIDEWALK (ITEM NO. 655105) QTY (SF) STATION / OFFSET REMARKS

145	STA. 104 + 62.24 /33' LT	SEE DETAIL C ON DT-04
762	STA. 104 + 97.90 /24.20' LT	SEE DETAIL C ON DT-04
1315	STA. 106 + 08.21 /24' LT	SEE DETAIL C ON DT-04
1025	STA. 106 + 11.36 /34.47' RT	SEE DETAIL C ON DT-04
88	STA. 106 + 47.24 /10.67' LT	SEE DETAIL C ON DT-04
88	STA. 106 + 47.24 /12.67' RT	SEE DETAIL C ON DT-04
378	STA. 106 + 53.19 /10.67' LT	SEE DETAIL C ON DT-04
352	STA. 106 + 53.19 /12.67' RT	SEE DETAIL C ON DT-04
123	STA. 107 + 40.09 /26' RT	SEE DETAIL C ON DT-04
224	STA. 107 + 65.57 /24' LT	SEE DETAIL C ON DT-04
145	STA. 107 + 80.23 /26' RT	SEE DETAIL C ON DT-04
350	STA. 108 + 08.43 /26' RT	SEE DETAIL C ON DT-04
345	STA. 108 + 11.68 /24' LT	SEE DETAIL C ON DT-04
1770	STA. 108 + 76.84 ?/26' RT	SEE DETAIL C ON DT-04
205	STA. 108 + 81.54 /24' LT	SEE DETAIL C ON DT-04
226	STA. 109 + 32.77 /24' LT	SEE DETAIL C ON DT-04

6 INCH PORTLAND CEMENT CONCRETE PAVEMENT EOD DDIVENAV MIV O (ITEM NO 561110)

	FOR DRIVEWAY MIX 9 (ITEM	NO. 561119)
QTY (SY)	STATION / OFFSET	REMARKS
18	STA. 107 + 59.79 /10.67' LT	SEE STD MD 630.02
14	STA. 108 + 07.35 /10.67 LT	SEE STD MD 630.02
19	STA. 108 + 75.36 /10.67 LT	SEE STD MD 630.02
26	STA. 109 + 24.39 /10.67 LT	SEE STD MD 630.02

10 INCH REINFORCED CONCRETE SIDEWALK (ITEM NO. 600000-D) QTY (SF) | STATION / OFFSET REMARKS STA, 106 + 68.68 /16.67 LT SEE DETAIL G ON DT-04

STA. 106 + 68.68 /18.67' RT

SEE DETAIL G ON DT-04

	BRICK SIDEWALK (ITEM NO. 655383)				
QTY (SF)	STATION / OFFSET	REMARKS			
477	STA. 106+08.87 /23' LT TO STA. 107+53.34 /23' LT	SEE STD MC-111.02			
384	STA. 106+12.03 /31.40' RT TO STA. 107+19.42 /25.16' RT	SEE STD MC-111.02			
77	STA. 107 + 40.75 /25' RT TO STA. 107 + 54.85 /25' RT	SEE STD MC-111.02			
163	STA. 107 + 66.23 /23' LT TO STA. 108 + 02.36 /23' LT	SEE STD MC-111.02			
93	STA. 107 + 80.90 /25' RT TO STA. 107 + 97.75 /25' RT	SEE STD MC-111.02			
173	STA. 108 + 09.11 /25' RT TO STA. 108 + 51.22 /25' RT	SEE STD MC-111.02			
264	STA. 108 + 12.35 /23' LT TO STA. 108 + 68.52 /23' LT	SEE STD MC-111.02			
750	STA. 108 + 77.51 /25' RT TO STA. 110 + 34.07 /27' RT	SEE STD MC-111.02			
145	STA. 108 + 82.20 /23' LT TO STA. 109 + 15.35 /23' LT	SEE STD MC-111.02			
147	STA. 109 + 33.44 /23' LT TO STA. 109 + 70.06 /23' LT	SEE STD MC-111.02			

CONCRETE STEPS (ITEM NO. 697009)					
QTY (CY)	STATION / OFFSET	REMARKS			
1	STA. 107 + 70.92 /29' LT	SEE STD MD 657.00			
1	STA. 108 + 34.65 /29' LT	SEE STD MD 657.00			
1	STA. 108 + 93.49 /29' LT	SEE STD MD 657.00			

STANDARD TYPE D COMBINATION CURB AND GUTTER 12 INCH GUTTER PAN 8 INCH MINIMUM (ITEM NO. 634344) STATION / OFFSET REMARKS QTY (LF) STA. 104 + 75.00 /12.38 LT TO STA. 109 + 50.00 /10 LT SEE STD MD 620.02-01 STA. 104 + 75.00 /24' RT TO STA. 109 + 50.00 /12' RT SEE STD MD 620.02-01

BUS SHELTER (ITEM NO. 700000-A)			
QTY (EA)	STATION / OFFSET	REMARKS	
1	STA. 106 + 74.66 17.39' RT	SEE DETAIL C ON DT-06	
1	STA. 106 + 75.70 15.39' LT	SEE DETAIL C ON DT-06	

STANDARD TYPE D CURB 8 INCH X 14 INCH MINIMUM (ITEM NO. 634146) QTY (LF) | STATION / OFFSET REMARKS STA. 104 + 97.90 /16.15' LT TO STA. 105 + 02.90 /10' LT SEE STD MD 620.02-01 STA, 105 + 81,39 /15,87' RT TO STA, 105 + 86,59 /27' RT SEE STD MD 620.02-01 STA. 106+11.36 /24.43' RT TO STA. 106+16.00 /13.36' RT SEE STD MD 620.02-01 STA. 105 + 88.21 /10' LT TO STA. 105 + 93.21 /16' LT SEE STD MD 620.02-01 STA. 106 + 08.21 /16' LT TO STA. 106 + 13.21 /10' LT SEE STD MD 620.02-01 STA. 106+08.21/31' LT TO STA. 106+08.21/41.33' LT SEE STD MD 620.02-01 STA. 106 + 12.03 /40.11' RT TO STA. 107 + 20.09 /33' RT SEE STD MD 620.02-01 STA. 106 + 41.19 /10' LT TO STA. 106 + 41.19 /19.33' LT SEE STD MD 620.02-01 STA. 106 + 51.19 /10' LT TO STA. 106 + 51.19 /19.33' LT SEE STD MD 620.02-01 STA. 106 + 41.19 /12' RT TO STA. 106 + 41.19 /21.33' RT SEE STD MD 620.02-01 STA. 106 + 51.19 /12' BT TO STA. 106 + 51.19 /21.33' BT SEE STD MD 620.02-01 STA. 107 + 15.11 / 12 RT TO STA. 107 + 20.11 / 18.04 RT SEE STD MD 620.02-01 STA. 107 + 40.09 /18' RT TO STA. 107 + 45.09 /12' RT SEE STD MD 620.02-01 STA. 107 + 49.00 /10' LT TO STA. 107 + 54.00 /16' LT SEE STD MD 620.02-01 STA. 107 + 65.57 /16' LT TO STA. 107 + 70.57 /10' LT SEE STD MD 620.02-01 STA. 107 + 50.52 /12' RT TO STA. 107 + 55.52 /18' RT SEE STD MD 620.02-01 STA. 107 + 80.23 /18' RT TO STA. 107 + 85.23 /12' RT SEE STD MD 620.02-01 STA. 107 + 93.30 /12' RT TO STA. 107 + 98.30 /18' RT SEE STD MD 620.02-01 STA. 108 + 08.44 /18' RT TO STA. 108 + 13.44 /12' RT SEE STD MD 620.02-01 STA. 107 + 98.02 /10' LT TO STA. 108 + 03.02 /16' LT SEE STD MD 620.02-01 STA. 108 + 11.68 /16' LT TO STA. 108 + 16.68 /10' LT SEE STD MD 620.02-01 SEE STD MD 620.02-01 STA. 108 + 08.43 /33' RT TO STA. 108 + 44.36 /33' RT SEE STD MD 620.02-01 STA. 108 + 46.90 /12' RT TO STA. 108 + 51.90 /18' RT STA. 108 + 76.85 /18' RT TO STA. 108 + 81.85 /12' RT SEE STD MD 620.02-01 STA. 108 + 64.18 /10' LT TO STA. 108 + 69.18 /16' LT SEE STD MD 620.02-01 STA. 108 + 81.54 /16' LT TO STA. 108 + 86.54 /10' LT SEE STD MD 620.02-01 STA, 108 + 76,83 /33' RT TO STA, 108 + 76,83 /53,28' RT SEE STD MD 620.02-01 STA. 109 + 11.01 /10' LT TO STA. 109 + 16.01 /16' LT SEE STD MD 620.02-01

SEE STD MD 620.02-01

STA. 109 + 32.77 /16' LT TO STA. 109 + 37.77 /10' LT

Stantec



o .	REVISION	BY	APP'D	DATE	DESIGNED BY: UMK	DATE: FEBRUARY	, 2025
					DRAWN BY: UMK	DATE: FEBRUARY	, 2025
				<u> </u>	CHECKED BY: CC	DATE: FEBRUARY	, 2025
					DRAWING NO.:	DATE:	
					RECOMMENDED FOR APPROVAL		
					Chief, Design Section		Date
					APPROVED		
					Chief, Division of Transportation Engi	ineering	Date

FLOWER AVENUE SEPARATED BIKE LANES ROADWAY SCHEDULES

DEPARTMENT OF TRANSPORTATION

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

SHEET<u>II</u> of <u>87</u>

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO: _ EXPIRATION DATE:

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

	MODIFIED TYPE D CURB (ITEM NO. 600000-A)			
QTY (LF) STATION / OFFSET		REMARKS		
30	STA. 109 + 93.24 /24' LT TO STA. 110 + 17.24 /24' LT	SEE DETAIL A ON DT-05		
35	STA. 110+34.55 /24' LT TO STA. 110+73.06 /21' LT	SEE DETAIL A ON DT-05		
39	STA. 110 + 54.71 /28' RT TO STA. 110 + 90.05 /25' RT	SEE DETAIL A ON DT-05		
30	STA. 111 + 23.86 /25.11' RT TO STA. 111 + 52.46 /20.30' RT	SEE DETAIL A ON DT-05		

STAND	STANDARD TYPE C CURB 8 INCH X 11 INCH MINIMUM (ITEM NO. 634131)			
QTY (LF)	STATION / OFFSET	REMARKS		
24	STA. 109 + 93.24 /16' LT TO STA. 110 + 17.24 /16' LT	SEE STD MD 620.02-01		
32	STA. 110 + 34.55 /16' LT TO STA. 110 + 73.06 /16' LT	SEE STD MD 620.02-01		
26	STA. 110 + 54.71 /20' RT TO STA. 110 + 87.59 /20' RT	SEE STD MD 620.02-01		
30	STA. 111 + 26.21 /20.12' RT TO STA. 111 + 54.93 /13.93' RT	SEE STD MD 620.02-01		

DETECTABLE WARNING SURFACE FOR CURB RAMPS (ITEM NO. 655120)		
QTY (SF)	STATION / OFFSET	REMARKS
10	STA. 110 + 63.53 /21' LT	SEE STD MD 655.40
10	STA. 110 + 63.53 /16' LT	SEE STD MD 655.40
10	STA. 110 + 63.53 /10' LT	SEE STD MD 655.40
10	STA. 110 + 63.53 /12' RT	SEE STD MD 655.40
10	STA. 110 + 63.53 /20' RT	SEE STD MD 655.40
10	STA. 110 + 63.53 /25.67' RT	SEE STD MD 655.40
10	STA. 110 + 90.26 /34.64 RT	SEE STD MD 655.40
10	STA. 111 + 23.22 /34.49' RT	SEE STD MD 655.40

l		DETECTABLE DIRECTIONAL STRIP (ITEM 1	NO. 600000–B)
	QTY (LF)	STATION / OFFSET	REMARKS
	4	STA. 110 + 63.53 /14' RT TO STA. 110 + 63.53 /18' RT	SEE DETAIL A ON DT-06
	2	STA. 110 + 63.53 /12' LT TO STA. 110 + 63.53 /14' LT	SEE DETAIL A ON DT-06
Г			

	5 INCH CONCRETE SIDEWALK (ITEM NO. 655105)				
QTY (SF)	STATION / OFFSET	REMARKS			
145	STA. 109 + 93.24 /24' LT	SEE DETAIL C ON DT-04			
140	STA. 110 + 34.55 /24 LT	SEE DETAIL C ON DT-04			
330	STA. 110 + 54.71 /26' RT	SEE DETAIL C ON DT-04			
77	STA. 110 + 63.53 /21' LT	SEE STD MD 655.11			
31	STA. 110 + 63.53 /10' LT	SEE DETAIL C ON DT-04			
41	STA. 110 + 63.53 /12' RT	SEE DETAIL C ON DT-04			
49	STA. 110 + 63.53 /25.67 RT	SEE STD MD 655.11			
120	STA. 110 + 69.05 /23' LT	SEE DETAIL C ON DT-04			
93	STA. 110 + 90.22 /35' RT	SEE STD MD 655.11			
93	STA. 111 + 23.23 /34' RT	SEE STD MD 655.11			
370	STA. 111 + 23.52 /26.09' RT				

8 INCH PORTLAND CEMENT CONCRETE PAVEMENT				
FOR DRIVEWAY MIX 9 (ITEM NO. 561118)				
QTY (SY)	STATION / OFFSET	REMARKS		
44.5	STA. 110 + 44.72 /12.67 RT	SEE DETAIL C ON DT-05		

6 INCH PORTLAND CEMENT CONCRETE PAVEMENT FOR DRIVEWAY MIX 9 (ITEM NO. 561119)				
QTY (SY)	STATION / OFFSET	REMARKS		
34	STA. 109 + 81.98 /10.67' LT	SEE STD MD 630.02		
26.5	STA. 110 + 25.90 /10.67' LT	SEE STD MD 630.02		

BRICK SIDEWALK (ITEM NO. 655383)			
QTY (SF)	STATION / OFFSET	REMARKS	
129	STA. 109 + 93.90 /23' LT TO STA. 110 + 16.58 /23' LT	SEE STD MC-111.02	
196	STA. 110 + 35.22 /23' LT TO STA. 110 + 87.84 /20.88' LT	SEE STD MC-111.02	
150	STA. 110 + 55.37 /19.33' RT TO STA. 110 + 87.59 /19.33' RT	SEE STD MC-111.02	
127	STA. 111 + 26.21 /19.46' RT TO STA. 111 + 54.56 /12.67' RT	SEE STD MC-111.02	

		CONCRETE STEPS (ITEM NO	O. 697009)
QTY (CY)	STATION / OFFSET		REMARKS
1	STA. 109 + 19.68 /29' LT		SEE STD MD 657.00

SEE STD MD 657.00

STANDARD TYPE D CURB 8 INCH X 14 INCH MINIMUM (ITEM NO. 634146)				
QTY (LF)	STATION / OFFSET	REMARKS		
9	STA. 109 + 65.72 /10' LT TO STA. 109 + 70.72 /16' LT	SEE STD MD 620.02-01		
9	STA. 109 + 93.24 /16' LT TO STA. 109 + 98.24 /10' LT	SEE STD MD 620.02-01		
9	STA. 110 + 12.24 /10' LT TO STA. 110 + 17.24 /16' LT	SEE STD MD 620.02-01		
9	STA. 110 + 35.55 /16' LT TO STA. 110 + 39.55 /10' LT	SEE STD MD 620.02-01		
11	STA. 110 + 29.75 /12' RT TO STA. 110 + 34.75 /20' RT	SEE STD MD 620.02-01		
11	STA. 110 + 54.71 /20' RT TO STA. 110 + 59.71 /12' RT	SEE STD MD 620.02-01		
10	STA. 110 + 60.04 /12' RT TO STA. 110 + 60.04 /20' RT	SEE STD MD 620.02-01		
8	STA. 110 + 60.04 /10' LT TO STA. 110 + 60.04 /16' LT	SEE STD MD 620.02-01		
10	STA. 110 + 67.03 /12' RT TO STA. 110 + 67.03 /20' RT	SEE STD MD 620.02-01		
8	STA. 110 + 67.03 /10' LT TO STA. 110 + 67.03 /16' LT	SEE STD MD 620.02-01		
8	STA. 110 + 73.06 /10'; LT TO STA. 110 + 73.06 /16' LT	SEE STD MD 620.02-01		
8	STA. 111 + 52.46 /20.30' RT TO STA. 111 + 59.98 /19.78' RT	SEE STD MD 620.02-01		

STA. 110 + 48.64 /29' LT

STANDARD TYPE D COMBINATION CURB AND GUTTER					
12 INCH GUTTER PAN 8 INCH MINIMUM (ITEM NO. 634344)					
QTY (LF)	STATION / OFFSET	REMARKS			
120	STA. 109 + 50.00 /10' LT TO STA. 110 + 73.06 /10' LT	SEE STD MD 620.02-01			
169	STA. 109 + 50.00 /12' RT TO STA. 110 + 90.66 /45.42' RT	SEE STD MD 620.02-01			
20	STA. 110 + 73.06 /21' LT TO STA. 110 + 92.43 /20.21' LT	SEE STD MD 620.02-01			
60	STA. 111 + 22.21 /44.96' RT TO STA. 111 + 54.56 /12' RT	SEE STD MD 620.02-01			



810 Gleneagles Court, Suite 300

Baltimore, MD 21286

www.stantec.com

Pedestrian Priority Areas	

REVISION	BY	APP'D	DATE	DESIGNED BY: UMK	DATE: FEBRUARY,	2025	
				DRAWN BY: UMK	DATE: FEBRUARY,	2025	
				CHECKED BY: CC	DATE: FEBRUARY,	2025	
				DRAWING NO.:	DATE:		
				RECOMMENDED FOR APPROVAL			
				Chief, Design Section		Date	
				APPROVED			
				Chief, Division of Transportation Engin		Date	

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES ROADWAY SCHEDULES

> > SHEET<u>12</u> of <u>87</u>

OF MARYLAND.

LICENSE NO: _

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE


_ EXPIRATION DATE: _

NOTES


- 1. SUBGRADE PREPARATION SHALL BE AS PER SECTION 204 OF MDOT SHA SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS; PRIOR TO PLACEMENT OF PROPOSED BASE COURSE, SUBGRADE SHALL BE PROOF-ROLLED.
- 2. UNDERCUT FOR REMOVAL OF SOFT AND/OR UNSUITABLE MATERIALS AND BACKFILLED WITH GRADED AGGREGATE BASE SHALL BE AS DIRECTED BY THE ENGINEER.

DETAIL A


FULL DEPTH ASPHALT PAVEMENT



DETAIL B MILLING AND OVERLAY



DETAIL C PORTLAND CEMENT CONCRETE SIDEWALK




NOTES

- 1. SUBGRADE PREPARATION SHALL BE AS PER SECTION 204 OF MDOT SHA SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS; PRIOR TO PLACEMENT OF PROPOSED BASE COURSE, SUBGRADE SHALL BE PROOF-ROLLED.
- 2. UNDERCUT FOR REMOVAL OF SOFT AND/OR UNSUITABLE MATERIALS AND BACKFILLED WITH GRADED AGGREGATE BASE SHALL BE AS DIRECTED BY THE ENGINEER.

DETAIL D


ASPHALT BIKE LANE PAVEMENT SECTION




DETAIL E CONCRETE CURB PATCH

LEGEND

- 2" HOT MIX ASPHALT SUPERPAVE, 9.5MM SURFACE COURSE, P.G. 64S-22, LEVEL 2
- 5" HOT MIX ASPHALT SUPERPAVE, 19.0MM BASE COURSE, P.G. 64S-22, LEVEL 2
- 2.5" HOT MIX ASPHALT SUPERPAVE, 19.0MM BASE COURSE, P.G. 64S-22, LEVEL 2
- 8 INCH GRADED AGGREGATE BASE, TWO EQUAL LAYERS
- LIMIT OF CLASS LEXCAVATION
- MILL EXISTING PAVEMENT TO 2 INCH DEPTH OR SURFACE OF EXISTING RIGID BASE
- 5 INCH PLAIN PORTLAND CEMENT CONCRETE MIX NO. 7
- 4 INCH AGGREGATE BASE COURSE
- 8 INCH PLAIN PORTLAND CEMENT CONCRETE MIX NO. 7 (INCIDENTAL)
- 10 INCH REINFORCED CONCRETE
- 6 INCH GRADED AGGREGATE BASE (INCIDENTAL)
- 8" HOT MIX ASPHALT SUPERPAVE, 9.5MM SURFACE COURSE, HDFC P.G. 64S-22, LEVEL 2 (2" LIFTS FOR RAISED CYCLE TRACK)



DETAIL F PAVEMENT OVERLAY



DETAIL G PCC BUS SHELTER PAD

DT-04

Stantec

Bicycle and Pedestrian Priority Areas

REVISION	BY	APP'D	DATE	DESIGNED BY: UMK DA	TE: FEBRUARY, 2025	
				DRAWN BY: UMK DA	TE: FEBRUARY, 2025	
				CHECKED BY: CC DA	TE: FEBRUARY, 2025	
				DRAWING NO.: DA	TE:	
				RECOMMENDED FOR APPROVAL Chief, Design Section		_
				APPROVED Chief, Division of Transportation Engineer		_
	REVISION	REVISION BY	REVISION BY APP'D	REVISION BY APP'D DATE	DRAWN BY: UMK CHECKED BY: CC DA DRAWING NO.: RECOMMENDED FOR APPROVAL Chief, Design Section APPROVED Chief,	DRAWN BY: UMK DATE: FEBRUARY, 2025 CHECKED BY: CC DRAWING NO.: RECOMMENDED FOR APPROVAL Chief, Design Section APPROVED Chief, Date

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES PAVEMENT DETAILS


> > SHEET<u>13</u> of <u>87</u>

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO:


_ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com









BY APP'D DATE REVISION DATE: FEBRUARY, 2025 DRAWN BY: UMK DATE: FEBRUARY, 2025 CHECKED BY: CC DATE: DRAWING NO .: RECOMMENDED FOR APPROVAL Chief, Design Section Date APPROVED Chief, Division of Transportation Engineering Date

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND


FLOWER AVENUE SEPARATED BIKE LANES


SHEET<u>14</u> of <u>87</u>

DT-05


PROPOSED **BIKEWAY** 8" PLAIN PORTLAND -CEMENT CONCRETE MIX NO.3

DETAIL A MODIFIED TYPE D CURB





DETAIL B RAISED CROSSWALK



DETAIL C COMMERCIAL DRIVEWAY

Bicycle and Pedestrian Priority Areas


__ EXPIRATION DATE: _

Baltimore, MD 21286

PAVEMENT FOR DRIVEWAY MIX 9

DESIGNED BY: UMK DATE: FEBRUARY, 2025

ROADWAY DETAILS



Bicycle and Pedestrian Priority Areas

APPROVED

Division of Transportation Engineering

Date

SEPARATED BIKE LANES

ROADWAY DETAILS

SHEET<u>15</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE


_ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300


Baltimore, MD 21286

www.stantec.com

OR APPROVED BY ME, AND THAT IAM A DULY LICENSED



\\US0527-PPFSS0|\shared_projects\20262|3||6\700 CADD\700 Sheet\pHD-KEY_F



www.stantec.com

315

310

+50

-- PROFILE - GRADE - LINE -

PROFILE GROUND -

ELEVATION

111+00

HORIZONTAL SCALE: 1" = 20'

VERTICAL SCALE: 1" = 4'

PVI STA. 112+25.00 ELEV. = 312.23

+50

113+00

PROFILE GRADE ELEVATION

112+00

(PGE)

+50

	DRAWN BY: UMK CHECKED BY: CC DRAWING NO.:	DATE: FEBRUARY, 2025 DATE: FEBRUARY, 2025 DATE:		DEPARTMENT OF TO DIVISION OF TRANSPORT MONTGOMERY COU	TATION ENGINEERING
	RECOMMENDED FOR APPROVAL Chief, Design Section APPROVED		Date	FLOWER AVENUE SEPARATED BIKE LANES ROADWAY PROFILE	
	Chief, Division of Transportation Engi	neering	Date	SCALE: H: I"=20' V: I"=4'	SHEET <u>21</u> of <u>87</u>

DESIGNED BY: UMK

DATE: FEBRUARY, 2025

APP'D DATE

DEPARTMENT OF TRANSPORTATION

315

310

300


HP-02

SHEET<u>21</u> of <u>87</u>


Stantec PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE 810 Gleneagles Court, Suite 300 OF MARYLAND. Baltimore, MD 21286 LICENSE NO: _ _ EXPIRATION DATE: _ SCALE: H: I"=20' V: I"=4' www.stantec.com

NO.


REVISION



2/26/2025 \\!IS0527-PPESSOI\sharad arajects\20262|3||6\700 CADD\700 Shaat`



2/26/2025



2/26/2025 \\||S0527-PPFSSO|\shared_projec+s\20262|⁻

	et/pDD-S001_FlowerAve.dgn
	Shee.
	CADD\700
	1700
	12026213116
	jects\
	nared_proj
	SOINSH
)	7-PPFS
7 7	US052

			STRUCTURE SC	HEDULE			
STRUCTURE	STATION	OFFSET	TYPE	TOP ELEV.	INVERT OUT	STANDARD	REMARKS
I-1	110+83	20.61' LT	REVERSE "B" INLET (B-10)	307.92	302.40	MC-502.02	10' THROAT OPENING
I-2	109+41	10.00' LT	REVERSE "B" INLET (B-10)	304.10	295.20	MC-502.02	10' THROAT OPENING
I-3	108+20	10.00' LT	REVERSE "B" INLET (B-10)	299.21	289.50	MC-502.02	10' THROAT OPENING
I-4	106+61	10.00' LT	REVERSE "B" INLET (B-10)	292.68	285.00	MC-502.02	10' THROAT OPENING
I-5	105+06	10.00' LT	REVERSE "B" INLET (B-10)	286.40	280.00	MC-502.02	10' THROAT OPENING
I-6	103+18	24.00' LT	REVERSE "B" INLET (B-10)	278.00	271.88	MC-502.02	10' THROAT OPENING
I-7	102+37	24.00' LT	"B" INLET (B-10)	276.33	271.03	MC-502.01	10' THROAT OPENING
I-8	108+85	12.00' RT	REVERSE "B" INLET (B-10)	301.23	294.23	MC-502.02	10' THROAT OPENING
I-9	108+22	12.00' RT	REVERSE "B" INLET (B-15)	298.73	292.70	MC-502.02	15' THROAT OPENING
I-10	106+62	12.00' RT	"B" INLET (B-15)	292.39	286.09	MC-502.01	15' THROAT OPENING
I-11	102+83	24.00' RT	REVERSE "B" INLET (B-15)	277.38	272.02	MC-502.02	15' THROAT OPENING
I-12	102+23	16.00' RT	"B" INLET (B-10)	275.76	271.38	MC-502.01	10' THROAT OPENING
I-13	102+23	29.67' RT	COG INLET (COG-5)	276.15	271.51	MD-374.51	5' THROAT OPENING
I-14	111+44	20.04' LT	REVERSE "B" INLET (B-15)	309.34	303.14	MC-502.02	15' THROAT OPENING
MH-1	101+72	32.96' LT	60" DIAMETER PRECAST MANHOLE	273.63	270.33	MD-384.03	
MH-2	111+42	5.43' LT	MCDOT TYPE "A" MANHOLE	309.38	302.81	MC-510.01	
MH-3	104+46	23.71' LT	MCDOT TYPE "A" MANHOLE	282.76	274.44	MC-510.01	
MH-4	110+82	6.67' LT	MCDOT TYPE "A" MANHOLE	307.68	299.50	MC-510.01	

				PIPE SCHEI	DULE		
UPSTREAM	DOWNSTREAM	SIZE	TYPE	LENGTH	UPSTREAM	DOWNSTREAM	COMMENTS
STRUCTURE	STRUCTURE		1112	(FT)	INVERT	INVERT	
I-14	MH-2	15"	RCP CLASS IV	8	303.14	303.06	
MH-2	MH-4	18"	RCP CLASS IV	55	302.81	302.26	
I-1	MH-4	15"	RCP CLASS IV	7	302.40	302.26	
MH-4	I-2	18"	RCP CLASS IV	136	299.50	297.68	
I-2	I-3	18"	RCP CLASS IV	115	295.50	292.50	
I-8	1-9	15"	RCP CLASS IV	57	294.23	293.09	
I-9	I-3	18"	RCP CLASS IV	13	292.70	292.58	
I-3	1-4	24"	RCP CLASS IV	152	289.50	286.66	
I-10	1-4	15"	RCP CLASS IV	17	286.09	285.75	
1-4	I-5	24"	RCP CLASS IV	149	285.00	280.10	
I-5	MH-3	24"	RCP CLASS IV	57	280.00	277.75	
MH-3	I-6	24"	RCP CLASS IV	123	274.44	271.98	
I-6	I-7	24"	RCP CLASS IV	75	271.88	271.13	
I-7	MH-1	24"	RCP CLASS V	60	271.03	270.43	
I-11	I-12	15"	RCP CLASS IV	54	272.02	271.48	
I-13	I-12	15"	RCP CLASS IV	4	271.51	271.48	
I-12	EX-MH-3	18"	RCP CLASS IV	37	271.38	271.01	
EX-MH-4	EX-MH-3	21"	RCP CLASS IV	30	271.51	271.10	

GENERAL NOTES

- I. STATION AND OFFSETS FOR MANHOLES IS GIVEN TO THE GEOMETRIC CENTER OF THE MANHOLE AND THE TOP ELEVATION IS GIVEN TO THE TOP OF MANHOLE COVER.
- 2.STATIONS FOR COG INLETS IS GIVEN TO THE GEOMETRIC CENTER OF THE BASE UNIT STRUCTURE, THE OFFSET IS GIVEN TO THE FACE OF CURB AT CENTER OF TROUGH AND THE TOP ELEVATION IS GIVEN TO THE TOP OF CURB.
- 3.CONTRACTOR TO VERIFY ALL EX.STORM DRAIN INVERTS PRIOR TO ORDERING AND FABRICATION ALL PROPOSED INLETS AND MANHOLES.

	20
Stantec	
ileneagles Court. Suite 300	Bicycle

	20'	0	20'	40'	-110
		SCALE:	" = 20'		
Bicyc	leand	Pedestr	ian Priori	ty Areas	

NO.	REVISION	BY	APP'D	DATE	DESIGNED BY: SMH	DATE: FEBRUARY,	2025	
					DRAWN BY: SMH	DATE: FEBRUARY,	2025	_
					CHECKED BY: CC	DATE: FEBRUARY,	2025	
					DRAWING NO.:	DATE:		
					RECOMMENDED FOR APPROVAL Chief, Design Section APPROVED		 Date	
					Chief, Division of Transportation Engine	ering	Date	SCA

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES DRAINAGE SCHEDULES

CALE: N.T.S.

SHEET<u>25</u> of <u>87</u>


DD-01

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT LAM A DULY LICENSED
PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE
OF MARYLAND.


LICENSE NO: ___

__ EXPIRATION DATE: _ www.stantec.com


810 Gleneagles Court, Suite 300 Baltimore, MD 21286



2/26/2025




2/26/2025



MH-1 TO I-4 SEE PLAN SHEET PS-01-PS-02

REVISION

NO.



DP-01

Stantec

20'	0 SCA	20' E: 1" = 20'	40'
Bicycle	and Pede	strian Prior	ity Areas

	DRAWN BY: SMH	DATE: FEBRUARY, 2025	
	CHECKED BY: CC	DATE: FEBRUARY, 2025	
	— DRAWING NO.:	DATE:	
	RECOMMENDED FOR APPROVAL		
	Chief, Design Section		
	APPROVED		
	Chief, Division of Transportation Engir	 Date neering	
			上

DATE: FEBRUARY, 2025

APP'D DATE DESIGNED BY: SMH

FLOWER AVENUE SEPARATED BIKE LANES STORM DRAIN PROFILES

DEPARTMENT OF TRANSPORTATION


DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND


SHEET<u>30</u> of <u>87</u> SCALE: N.T.S.

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED
PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

_ EXPIRATION DATE: _ LICENSE NO: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com





- 2. The permittee must obtain inspection and approval by dps at the following points:
 - A. At the required pre-construction meeting.
 - B. Following installation of sediment control measures and prior to any other land disturbing activity.
 - C. During the installation of a sediment basin or stormwater management structure at the required inspection points (see inspection checklist on plan). Notification prior to commencing construction is mandatory.
 - D. Prior to removal or modification of any sediment control structure(s).
 - E. Prior to final acceptance.

3. The permittee shall construct all erosion and sediment control measures per the approved plan and construction sequence, shall have them inspected and approved by the department prior to beginning any other land disturbances, shall ensure that all runoff from disturbed areas is directed to the sediment control devices, and shall not remove any erosion or sediment control measure without prior permission from the department.

- 4. The permittee shall protect all points of construction ingress and egress to prevent the deposition of materials onto traversed public thoroughfare(s). All materials deposited onto public thoroughfare(s) shall be removed immediately.
- 5. The permittee shall inspect periodically and maintain continuously in effective operating condition, all erosion and sediment control measures until such time as they are removed with prior permission from the department. The permittee is responsible for immediately repairing or replacing any sediment control measures which have been damaged or removed by the permittee or any other person.

6. Following initial soil disturbance or re-disturbance, permanent or temporary stabilization must be completed within:

- A. three (3) calendar days as to the surface of all perimeter dikes. swales, ditches, perimeter slopes and all slopes steeper than 3 horizontal to 1 vertical (3:1); and
- B. seven (7) calendar days as to all other disturbed or graded areas on the project site not under active grading.
- All areas disturbed outside of the perimeter sediment control system must be minimized and stabilized immediately. Maintenance must be performed as necessary to ensure continued stabilization.
- 7. The permittee shall apply sod, seed, and anchored straw mulch, or other approved stabilization measures to all disturbed areas within seven (7) calendar days after stripping and grading activities have ceased on that area. Maintenance shall be performed as necessary to ensure continued stabilization. Active construction areas such as borrow or stockpile areas, roadway improvements, and areas within fifty (50) feet of a building under construction may be exempt from this requirement, provided that erosion and sediment control measures are installed and maintained to protect those areas.
- 8. Prior to removal of sediment control measures, the permittee shall stabilize all contributory disturbed areas with required soil amendments and topsoil, using sod or an approved permanent seed mixture and an approved anchored mulch. Wood fiber mulch may only be used in seeding season when the slope does not exceed 10% and grading has been done to promote sheet flow drainage. Areas brought to finished grade during the seeding season shall be permanently stabilized within seven (7) calendar days of establishment. When property is brought to finished grade during the months of november through february, and permanent stabilization is found to be impractical, an approved temporary seed and straw anchored mulch shall be applied to disturbed areas. The final permanent stabilization of such property shall be completed prior to the following april 15.
- 9. The site permit, work, materials, approved sc/sm plans, and test reports shall be available at the site for inspection by duly authorized officials of montgomery county.
- 10. Surface drainage flows over unstabilized cut and fill slopes shall be controlled by either preventing drainage flows from traversing the slopes or by installing mechanical devices to lower the water down slope without causing erosion. Dikes shall be installed and maintained at the top of cut or fill slopes until the slope and drainage area to it are fully stabilized, at which time they must be removed and final grading done to promote sheet flow drainage. Mechanical devices must be provided at points of concentrated flow where erosion is likely to occur.
- 11. Permanent swales or other points of concentrated water flow shall be stabilized within 3 calendar days of establishment with sod or seed with an approved erosion control matting or by other approved stabilization measures.
- 12. Sediment control devices shall be removed, with permission of the department, within thirty (30) calendar days following establishment of permanent stabilization in all contributory drainage areas. Stormwater management structures used temporarily for sediment control shall be converted to the permanent configuration within this time period as well.

13. No permanent cut or fill slope with a gradient steeper than 3:1 will be permitted in lawn maintenance areas or on residential lots. A slope gradient of up to 2:1 will be permitted in non- maintenance areas provided that those areas are indicated on the erosion and sediment control plan with a low-maintenance ground cover specified for permanent stabilization. Slope gradient steeper than 2:1 will not be permitted with vegetative stabilization.

14. The permittee shall install a splashblock at the bottom of each downspout unless the downspout is connected by a drain line to an acceptable outlet.

15. For finished grading, the permittee shall provide adequate gradients so as to prevent water from standing on the surface of lawns more than twenty-four (24) hours after the end of a rainfall, except in designated drainage courses and swale flow areas, which may drain as long as forty-eight (48) hours after the end of a rainfall.

16. Sediment traps or basins are not permitted within 20 feet of a building which is existing or under construction. No building may be constructed within 20 feet of a sediment trap or basin.

17. All inlets in non-sump areas shall have asphalt berms installed at the time of base paving establishment.

18. The sediment control inspector has the option of requiring additional sediment control measures, as deemed necessary.

19. All trap elevations are relative to the outlet elevation, which must be on existing undisturbed ground.

20. Vegetative stabilization shall be performed in accordance with the standards and specifications for soil erosion and sediment control.

21. Sediment trap(s)/basin(s) shall be cleaned out and restored to the original dimensions when sediment has accumulated to the point of one-half (1/2) the wet storage depth of the trap/basin (1/4 the wet storage depth for st-iii) or when required by the sediment control inspector.

22. Sediment removed from traps/basins shall be placed and stabilized in approved areas, but not within a floodplain.

23. All sediment basins and traps must be surrounded with a welded wire safety fence. The fence must be at least 42 inches high, have posts spaced no farther apart than 8 feet, have mesh openings no greater the two inches in width and four inches in height, with a minimum of 14 gauge wire. Safety fence must be maintained in good condition at all times.

24. No excavation in the areas of existing utilities is permitted unless their location has been determined. Call "Miss utility" at 1-800-257-7777, 48 hours prior to the start of work.

25. Off-site spoil or borrow areas must have prior approval by dps.

26. Sediment trap/basin dewatering for cleanout or repair may only be done with the dps inspector's permission. The inspector must approve the dewatering method for each application. The following methods may be considered:

- A. Pump discharge may be directed to another on-site sediment trap or basin, provided it is of sufficient volume and the pump intake is floated to prevent agitation or suction of deposited sediments; or
- B. The pump intake may utilize a removable pumping station and must discharge into an undisturbed area through a non-erosive outlet; or
- C. The pump intake may be floated and discharge into a dirt bag (12 oz. Non-woven fabric), or approved equivalent, located in an undisturbed buffer area.

Remember: dewatering operation and method must have prior approval by the dps inspector.

27. The permittee must notify the department of all utility construction activities within the permitted limits of disturbance prior to the commencement of those activities.

28. Topsoil must be applied to all pervious areas within the limits of disturbance prior to permanent stabilization in accordance with MDE "Standards and Specifications for Soil Preparation, Topsoiling, and Soil Amendments.

29. The contractor shall utilize a concrete washout structure for all concrete work, if the contractor wishes to use an off site concrete washout structure they shall notify the engineer of said location in writing.

STANDARD SYMBOLS

AT-GRADE INLET PROTECTION	AGIP	ROCK OUTLET PROTECTION II	ROPII
BAFFLE BOARDS	ВВ	ROCK OUTLET PROTECTION III	ROPIII
CATCH BASIN INSERT	[]сві	SILT FENCE	⊢——SF——I
CLEAR WATER DIVERSION PIPE	CWD - 12 NOTE: DESIGNATION CWD-12 REFERS TO CLEAR WATER DIVERSION WITH 12 INCH PIPE.	SILT FENCE ON PAVEMENT	⊢—SF0P——I
COMBINATION INLET PROTECTION	[]coip	SOD	* * * * * * * * * * * * * * * * * * * *
CURB INLET PROTECTION	[Z]CIP	STABILIZED CONSTRUCTION ENTRANCE	SCE SCE
DIVERSION FENCE	⊢ DFI	STANDARD INLET PROTECTION	SIP
EARTH DIKE	A-I PLACE D IGNATION (A-I, B-2, etc.) ON OF DIKE.	STOCKPILE AREA	
EMERGENCY SPILLWAY	ES	STONE CHECK DAM	CD
FILTER BAG	⊠FB	STONE/RIPRAP OUTLET SEDIMENT TRAP ST II	ST-II
FILTER BERM	IFB-AI IFB-BI	SUBSURFACE DRAINS	├─ SSD ── ┤
FILTER LOG	FL-18 —— NOTE: DESIGNATION FL-18 REFERS TO FILTER LOG WITH 18 INCH DIAMETER.	SUMP PIT	⊠SP
GABION INFLOW PROTECTION	GP	SUPER SILT FENCE	⊢—SSF——I
GABION INLET PROTECTION	[=]GIP	TEMPORARY ACCESS CULVERT	
LIMIT OF DISTURBANCE	——LOD——	TEMPORARY ASPHALT BERM	T <u>AB</u>
MEDIAN INLET PROTECTION	MIP	TEMPORARY BARRIER DIVERSION	ТВО
MEDIAN SUMP INLET PROTECTION	MSIP	TEMPORARY GABION OUTLET STRUCTURE	TGOS
MOUNTABLE BERM	MB	TEMPORARY SOIL STABILIZATION MATTING-TYP	E A A A
PERIMETER DIKE/SWALE	₽DS-I	TEMPORARY SOIL STABILIZATION MATTING-TYP	E E
PERMANENT SOIL STABILIZATION MATTING	-TYPE B	TEMPORARY SOIL STABILIZATION MATTING-TYP	E D D D
PERMANENT SOIL STABILIZATION MATTING	-TYPE C	TEMPORARY STONE OUTLET STRUCTURE	₹ TS0S
PIPE OUTLET SEDIMENT TRAP ST I	ST-I	TEMPORARY SWALE	ACE DESIGNATION (A-I,B-2, c.) ON FLOW CHANNEL SIDE
PIPE SLOPE DRAIN	PSD - 12 NOTE: DESIGNATION PSD-12 REFERS TO PIPE SLOPE DRAIN WITH 12 IN PIPE	WASH RACK OPTION	WR
PLUNGE POOL	PP	CHESAPEAKE BAY CRITICAL AREA	CBCA
PORTABLE SEDIMENT TANK	⊠PST	DRAINAGE BOUNDARY	D <u>A</u>
REMOVABLE PUMPING STATION	⊠RPS	EXISTING CONTOURS	<u> </u>
RIPRAP INFLOW PROTECTION	RRP	PROPOSED CONTOURS	100
RIPRAP OUTLET SEDIMENT TRAP ST III	ST-III	TREE PROTECTION FENCE	—— TPF ———
ROCK OUTLET PROTECTION I	ROPI	WETLAND	• • • • • •
LIMIT OF CUT SLOPE	<u></u> — с — →	WETLAND BUFFER	— в ——
LIMIT OF FILL SLOPE	⊢— F — →	100-YEAR FLOODPLAIN	

BEFORE BEGINNING CONSTRUCTION CONTACT I-800-257-777° AT LEAST 48 HOURS PRIOR TO EXCAVATION

Bicycle cand Pedestrian Priority Areas

NO.

DESIGNED BY: SMH DATE: FEBRUARY, 2025 APP'D DATE REVISION DRAWN BY: SMH DATE: FEBRUARY, 2025 DATE: FEBRUARY, 2025 CHECKED BY: CC DRAWING NO .: DATE: RECOMMENDED FOR APPROVAL Chief, Design Section **APPROVED** Division of Transportation Engineering

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES EROSION AND SEDIMENT CONTROL NOTES

> > SHEET<u> 33 </u> of <u> 87 </u>

SCALE: NONE

Date

Date

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT LAM A DULY LICENSED
PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE
OF MARYLAND

EXPIRATION DATE:

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

Stantec



LICENSE NO:

SEQUENCE OF CONSTRUCTION

- I. Prior to clearing of trees, installing sediment control measures, or grading a preconstruction meeting must be conducted on-site with the Montgomery County Department of Permitting Services (MCDPS) sediment control inspector (240) 777–0311 (48 hours notice), the Owners representative, and the site Engineer. In order for the meeting to occur, the applicant must provide one paper set of approved sediment control plans to the MCDPS sediment control inspector at the preconstruction meeting. If no plans are provided, the meeting shall not occur and will need to be rescheduled prior to commencing any work.
- 2. The limits of disturbance must be field marked prior to clearing of trees, installation of sediment control measure, construction or other land disturbing activities.
- 3. Weather should be monitored to ensure construction of proposed drainage facilities are done in a day with no expected rainfall. Proposed drainage facilities should be constructed within one working day.
- 4. Place Tree Protection Fence. Tree Protection Fencing is shown offset from the Limit of Disturbance (LOD) line for graphic reasons only. Tree protection fence placement is to be executed at the LOD line.
- 5. Construction can occur coincidentally or any order the contractor chooses as long as approvals are in place.


SITE SPECIFIC SEQUENCE OF CONSTRUCTION


- I. Clear and Grade for Installation of sediment control devices, only disturbing the area needed for installation of the sediment control devices.
- 2. Install Inlet Protection and Tree Protection Fence.
- 3. Once installed, the permittee must obtain written approval from the MCDPS inspector before proceeding with any additional clearing, grubbing, or grading.
- 4. Construct roadway, storm drain improvements, curb, sidewalk, grading, and SWM facilities.
- 5. Permanently stabilize disturbed roadside area with topsoil, seed and mulch as indicated on the Typical Sections and Landscape plans.
- 6. Upon final stabilization and written approval from MCDPS inspector, the permittee shall remove the sediment control devices.


M-NCPPC CONSTRUCTION NOTES


Removal of Existing Pavement within a Tree's Critical Root Zone:

- I. The contractor shall meet with the M-NCPPC Urban Forester and Construction Inspector prior to removal of the pavement to discuss methods to be used to remove pavement. Removal of pavement may be required to be done by hand depending on site conditions.
- 2. The existing top layer of pavement shall be peeled away without disturbing the ground or material beneath. If a base course of rock is beneath the pavement the rock shall be left in place.
- 3. During the removal of the pavement layer great care shall be taken to not disturb existing tree roots along or under existing pavement. Existing tree roots greater than 1.5" in diameter encountered during the removal process shall not be cut unless approved by the M-NCPPC Urban Forester.
- 4. Equipment should remain on existing pavement during the removal process. Equipment shall not traverse over areas where pavement was removed in order to protect exposed tree roots.
- 5. Ground protection such as a 12" mulch layer will be required if equipment is needed to be operated within the critical root zone.
- 6. Removal of the existing pavement shall be done under supervision of the M-NCPPC Urban Forester and the Construction Inspector.
- 7. Stabilize area per approved plan or as directed by Construction Inspector.









Tree Protection Fence Detail

- 1. Practice may be combined with sediment control fencing.
- Location and limits of fencing should be
- coordinated in field with arborist Boundaries of protection area should be staked
- prior to installing protective device.
- Root damage should be avoided. Protection signage is required.
- Fencing shall be maintained throughout construction.

Montgomery County Planning Department • Market Mr. McPPC

MontgomeryPlanning.org





o.	REVISION	BY	APP'D	DATE	DESIGNED BY: SMH DATE	: FEBRUARY, 2025	
					DRAWN BY: SMH DATE	: FEBRUARY, 2025] _
					CHECKED BY: CC DATE	: FEBRUARY, 2025] <u> </u>
					DRAWING NO.: DATE	:	1
					RECOMMENDED FOR APPROVAL Chief, Design Section APPROVED	Date	
					Chief, Division of Transportation Engineering	Date	SCAL

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES EROSION AND SEDIMENT CONTROL NOTES


CALE: NONE

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE


OF MARYLAND. LICENSE NO:

_ EXPIRATION DATE:

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com



27.267.2023 \\US0527-PPFSS0I\shared_projects



2/26/2023 \\US0527-PPFSS0|\shared_projects\20262|3||6\700 CADD\700 She

- 1												
								MATERIAL LIST	- LP-0 ²			
	PLANT LIST LP-01							CATEGORY COL	UNIT	DESCRIPTION	LOCATION	QUANTITY
	SYM	QUANTITY	BOTANICAL NAME	COMMON NAME	SIZE	BALL	REMARKS	701214	SY	PLACING FURNISHED SUBSOIL 18" DEPTH	TREE PIT (4'X10')	45
	LSW	3	Liquidambar styraciflua 'Ward'	Ward Sweetgum	2.5 IN. CAL.	B&B	CENTRAL LEADER	704365	SY	PLACING FURNISHED TOPSOIL 6" DEPTH	TREE PIT (4'X10')	45
	QPA	5	Quercus phellos 'Abundance'	Abundance Willow Oak	2.5 IN. CAL.	B&B	CENTRAL LEADER	710170	SY	CONSTRUCT PLANTING BEDS	TREE PIT (4'X10')	45
	QS	2	Quercus shumardii	Shumard Oak	2.5 IN. CAL.	B&B	CENTRAL LEADER	715015	SY	SHREDDED HARDWOOD BARK MULCHING 3" DEPTH	TREE PIT (4'X10')	45
	TAR	2	Tilia americana 'Redmond'	Redmond Linden	2.5 IN. CAL.	B&B	CENTRAL LEADER	700000	LF	TEMPORARY CHAIN LINK FENCE (TREE PROTECTION)	AS SHOWN	42
		NOTE: SHREDDED HARDWOOD BARK MULCH IS INCIDENTAL TO CONSTRUCT PLANTING BEDS										

REFER TO APPROVED SNRI 42023179E

FOR TREE PROTECTION AND REMOVALS TOP = 264.79 — INV.OUT = 259.44 INV.IN = 259.84 THE FLOWER CENTER 8472 PINEY BRANCH ROAD I-STORY BUILDING - EUONYMUS FLOWER ASSOCIATES L.03723 F.0026 TAX ID 01397363 PLAT 209 SHRUBS TO REMAIN INV. OUT = 262.12 INV. IN = 265.03 62097311240 - CONSTRUCT PLANT BED TYPICAL I-STORY BUILDING 4.5 SY EACH TREE PIT -2 QPA BEJING DELIGHT RESTAURANT **INSTALL 18" SUBSOIL** MΗ 8435 PINEY BRANCH ROAD GATEWAY PROPERTY LLC ASPANDSCAPE-**INSTALL 6" TOPSOIL** PAVEIMIT OF **INSTALL 3" SHREDDED** TAX ID 03682242 WORK HARDWOOD BARK MULCH PLAT 24191 PROPOSED PEPC0 — 798424-8305 RIGHT-OF-WAY CONSTRUCTION FLOWER AVENUE PEPC0 - 798424-9002 FLOWER AVENUE .) WG 4" STL ABANDONED **∥-**-- 100+00 -WABBIHOOPDAY - EX. ROW FLOWER AVENUE - $\frac{(QL-C)}{MG}$ $\frac{MG}{6}$ PEPC0 - 798424-9302 2 LSW---1 TAR ASPHALT Ó 2 QPA PAVEMENT = TOP = 275.01 — INV.04±= 272.26 SHOPPINGTARTER FLOWER AVENUE
SHOPPING CENTER
FLOWER AVOWERHAYENUENTR LTD
FLOWER AVE SHOPE CNTR LTD PINEY BRANCH CENTER E 1311420 8501 PINEY BRANCH ROAD PINEY BRANCH CENTER 8501 PINEY BRANCH ROAD JBG/PINEY BRANCH RETAIL LLC L.51454 F.0371 TAX ID 00978064 PLAT XXXX INV. OUT 271.51 INV. IN (E 18")= 272.0 L086551 F.0361 JBG/PINEY BRANCH RETAIL LLC TAX PbA 5 789 7603 PROPOSED TEMPORARY— L.51454 F.0371 CONSTRUCTION EASEMENT TAX ID 00978064 - CONSTRUCT PLANT BED TYPICAL 4.5 SY EACH TREE PIT PLAT XXXX INSTALL 18" SUBSOIL **INSTALL 6" TOPSOIL INSTALL 3" SHREDDED** HARDWOOD BARK MULCH <u>L</u>P-01 APP'D DATE DESIGNED BY: KRD DATE: FEBRUARY, 2025 BY REVISION DEPARTMENT OF TRANSPORTATION DATE: FEBRUARY, 2025 DRAWN BY: MK DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND DATE: FEBRUARY, 2025 CHECKED BY: CC SCALE: 1" = 20' DATE: DRAWING NO .: RECOMMENDED FOR APPROVAL FLOWER AVENUE Stantec Chief, Design Section Date SEPARATED BIKE LANES PROFESSIONAL CERTIFICATION: APPROVED LANDSCAPE PLAN I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A REGISTERED Bicycle and Pedestrian Priority Areas LANDSCAPE ARCHITECT UNDER THE LAWS OF THE STATE 810 Gleneagles Court, Suite 300 OF MARYLAND.

Date

SCALE: I"=20'

SHEET<u>38</u> of <u>87</u>

Division of Transportation Engineering

LICENSE NO: #3190 EXPIRATION DATE: MAY 7, 2025

Baltimore, MD 21286

www.stantec.com

PLANT LIST LP-02						
SYM	QUANTITY	BOTANICAL NAME	COMMON NAME	SIZE	BALL	REMARKS
LSW	2	Liquidambar styraciflua 'Ward'	Ward Sweetgum	2.5 IN. CAL.	B&B	CENTRAL LEADER
QPA	4	Quercus phellos 'Abundance'	Abundance Willow Oak	2.5 IN. CAL.	B&B	CENTRAL LEADER
QS	5	Quercus shumardii	Shumard Oak	2.5 IN. CAL.	B&B	CENTRAL LEADER
TAR	5	Tilia americana 'Redmond'	Redmond Linden	2.5 IN. CAL.	B&B	CENTRAL LEADER


MATERIAL LIST	- LP-02			
CATEGORY COI	UNIT	DESCRIPTION	LOCATION	QUANTITY
701214	SY	PLACING FURNISHED SUBSOIL 18" DEPTH	TREE PIT (4'X10')	72
704365	SY	PLACING FURNISHED TOPSOIL 6" DEPTH	TREE PIT (4'X10')	72
710170	SY	CONSTRUCT PLANTING BEDS	TREE PIT (4'X10')	72
715015	SY	SHREDDED HARDWOOD BARK MULCHING 3" DEPTH	TREE PIT (4'X10')	72
700000	LF	TEMPORARY CHAIN LINK FENCE (TREE PROTECTION)	AS SHOWN	90

NOTE: SHREDDED HARDWOOD BARK MULCH IS INCIDENTAL TO CONSTRUCT PLANTING BEDS

Date

Date

REFER TO APPROVED SNRI 42023179E FOR TREE PROTECTION AND REMOVALS



SCAPE ARCHION OF MARCHINGS OF M

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A REGISTERED
LANDSCAPE ARCHITECT UNDER THE LAWS OF THE STATE
OF MARYLAND.
LICENSE NO: #3190 EXPIRATION DATE: MAY 7, 2025

Stantec

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com RECOMMENDED FOR APPROVAL

Chief, Design Section

APPROVED

Chief,
Division of Transportation Engineering

FLOWER AVENUE SEPARATED BIKE LANES

SEPARATED BIKE LANES LANDSCAPE PLAN

SCALE: I"=20' SHEET 39 of 87

SHA LANDSCAPE NOTES

- 7.1 LANDSCAPE NOTES. LANDSCAPE CONSTRUCTION WITHIN SHA PROPERTY, INCLUDING RIGHT OF WAYS, EASEMENT AREAS AND LANDS TO BE CONVEYED TO SHA SHALL CONFORM TO THESE NOTES. FOR GUIDANCE REGARDING DESIGN MODIFICATIONS DURING CONSTRUCTION, REFER TO SHA LANDSCAPE DESIGN GUIDE, SHA LANDSCAPE ESTIMATING MANUAL, AND SHA ENVIRONMENTAL GUIDE FOR ACCESS AND DISTRICT PERMIT APPLICANTS AT HTTP://WWW.ROADS.MARYLAND.GOV/INDEX.ASPX?PAGEID=25
- 7.2 SHA STANDARD SPECIFICATIONS. LANDSCAPE CONSTRUCTION SHALL CONFORM TO SECTIONS 701 THROUGH 716, AND LANDSCAPE MATERIALS SHALL CONFORM TO SECTION 920 OF THE MOST RECENT REVISION OF SHA STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, INCLUDING ALL REVISIONS AND SUPPLEMENTS, AND AS SPECIFIED IN THESE NOTES. THESE REQUIREMENTS SHALL SUPERSEDE ALL OTHER SPECIFICATIONS FOR WORK ON SHA PROPERTY. CURRENT SPECIFICATIONS ARE AT HTTP://WWW.ROADS.MARYLAND.GOV/INDEX.ASPX?PAGEID=44
- 7.3 EROSION AND SEDIMENT CONTROL MANAGER (ESCM). SOIL DISTURBANCE SUCH AS GRADING, EXCAVATION, SOIL PLACEMENT OR OTHER ACTIVITIES THAT INVOLVE SOIL DISTURBANCE SHALL BE SUPERVISED BY AN ESCM MANAGER WITH A VALID "SHA YELLOW CARD" IN CONFORMANCE WITH SHA STANDARD SPECIFICATIONS AND ANY APPLICABLE EROSION AND SEDIMENT CONTROL PERMIT.
- 7.4 SHA STANDARD DETAILS FOR TREES, SHRUBS AND PLANTING BEDS. THE INSTALLATION OF TREES, SHRUBS, PLANTING BEDS AND OTHER LANDSCAPE CONSTRUCTION RELATED TO SECTION 710 OF THE SHA STANDARD SPECIFICATIONS SHALL CONFORM TO THE "SHA BOOK OF STANDARDS FOR HIGHWAY & INCIDENTAL STRUCTURES - CATEGORY 7" AT HTTP://APPS.ROADS.MARYLAND.GOV/BUSINESSWITHSHA/BIZSTDSSPECS/DESMANUALSTDPUB /PUBLICATIONSONLINE/OHD/BOOKSTD/TOCCAT7.ASP
- 7.5 TEMPORARY STABILIZATION SHALL BE INSTALLED IN CONFORMANCE WITH SECTION 704 TO ENSURE THAT AREAS OF SOIL DISTURBANCE ARE PROTECTED FROM WIND, RAINFALL AND FLOWING WATER UNTIL PERMANENT STABILIZATION IS INSTALLED.
- 1. TEMPORARY MULCH, EITHER AS TEMPORARY STRAW MULCH OR TEMPORARY MATTING MULCH, SHALL BE INSTALLED AT THE END OF EACH WORKING DAY TO PROVIDE "SAME DAY STABILIZATION" UNLESS OTHER APPROVED STABILIZATION IS
- 2. TEMPORARY STRAW MULCH SHALL BE INSTALLED ON AREAS AND SLOPES FLATTER THAN 4:1 TEMPORARY MATTING MULCH SHALL BE APPLIED ON SLOPES 4:1 AND STEEPER, AND TO AREAS WITIN CHANNELS.
- 7.6 PAVEMENT REMOVAL AND RESTORATION. AREAS OF PAVEMENT REMOVAL SHALL BE EXCAVATED TO REMOVED PAVEMENTS, AGGREGATE BASE, AND COMPACTED SOIL AND OTHER UNUITALBE MATERIALS BEFORE PLACING SOILS IN CONFORMANCE WITH SECTION 701 OF THE SHA STANDARD SPECIFICATIONS.
- 1. ROADWAYS SHALL BE EXCAVATED TO A DEPTH OF 16 INCHES BELOW FINAL GRADE BEFORE PLACING FURNISHED SUBSOIL 12 IN. DEPTH AND PLACING FURNISHED TOPSOIL 4 IN. DEPTH IN CONFORMANCE IWTH NOTE 7.8
- 2. TEMPORARY STAW MULCH SHALL BE INSTALLED ON AREAS AND SLOPES FLATTER THAN 4:1: TEMPORARY MATTING MULCH SHALL BE APPLIED ON SLOPES 4?1 AND STEEPER, AND TO AREAS WITHIN CHANNELS.
- 7.7 EXCAVATION AND DEBRIS REMOVAL. DEBRIS RELATED TO THE DEMOLITION OF SIDEWALKS, DRIVEWAYS, CURBS, TREES, STUMPS, ROOTS, FENCING, PIPES, AND OTHER MATERIALS THAT MAY INTERFERE WITH LANDSCAPE INSTALLATION OR FUTURE MAINTENANCE SHALL BE EXCAVATED AS NECESSARY FOR THEIR COMPLETE REMOVAL AND DISPOSAL.
- 7.13 TREE PRESERVATION AREAS. TEMPORARY ORANGE CONSTRUCTION FENCE (TOCF) SHALL BE INSTALLED IN LOCATIONS DELINEATED ON THE PLANS IN CONFORMANCE WITH SECTION 120 OF THE SHA STANDARD SPECIFICATION TO PROTECT EXISTING TREES AND OTHER VEGETATION DURING CONSTRUCTION. AREAS WITHIN TOCF SHALL BE PROTECTED FROM ALL PROHIBITED AND RESTRICTED ACTIVITIES, AS SPECIFIED IN SECTION 120.
- 7.14 ROADSIDE TREE PERMIT. TREE REMOVAL, TREE INSTALLATION, TREE ROOT AND BRANCH PRUNING, AND OTHER REGULATED IMPACTS TO TREES IN THE SHA RIGHT OF WAY SHALL CONFORM TO THE REQUIREMENTS OF THE ROADSIDE TREE INDIVIDUAL PERMIT (RTIP) OF THE MARYLAND DEPARTMENT OF NATURAL RESOURCES, OR THE APPROVED FOREST CONSERVATION PLAN OF THE LOCAL AUTHORITY.
- 1. A COPY OF THE RTIP OR FCP SHALL BE SUBMITTED TO THE SHA LANDCAPE PROGRAMS DIVISION BEFORE WORK IS PERFORMED, AND A COPY OF THE RTIP OR FCP SHALL BE REPRODUCED IN THE PLANS OR BE IN POSSESSION OF THE APPLICANT AT THE PROJECT SITE WHEN THE PERMITTED WORK IS PERFORMED.
- 2. A MARYLAND LICENSED TREE EXPERT SHALL PERFORM THE SPECIFIED TREE OPERATIONS IN CONFORMANCE WITH THE SHA STANDARD SPECIFICATIONS AND ANSI A300 STANDARDS FOR TREE CARE OPERATIONS
- 7.15 TREES AND OTHER PLANT MATERIAL INSTALLATION. TREES, SHRUBS, PERENNIALS, ANNUALS, BULBS, LANDSCAPE BEDS, BARK MULCH AND SIMILAR MATERIALS SHALL BE INSTALLED IN CONFORMANCE WITH SECTION 710 AND 711 OF THE SHA STANDARD SPECIFICATIONS.
- TREE AND SHRUBS SHALL BE PRUNED AT THE TIME OF INSTALLATION TO ENSURE SIDEWALK CLEARANCE FOR PEDESTRIANS IS MAINTAINED TO A HEIGHT OF 8 FEET. NO TREE OR SHRUB SHALL BE INSTALLED WITHIN 3 FEET OF CURBS, SIDEWALKS, OR PAVEMENT EDGES.
- 7.20 STUMP REMOVAL. STUMP REMOVAL IN TURFGRASS OR MEADOW AREAS SHALL BE PERMFORMED IN CONFORMANCE WITH OPERATION 5 - STUMP REMOVAL OF SECTION 714.
- 7.21 TREE BRANCH PRUNING SHALL BE PERFORMED OR DIRECTLY SUPERVISED BY A MARYLAND LICENSED TREE EXPERT IN CONFORMANCE WITH ANSI A300 STANDARDS PER SECTION 712 AS NECESSARY FOR ANY OF THE FOLLOWING: TO INSTALL TEMPORARY ORANGE CONSTRUCTION FENCE (TOCF) ALONG DELINEATIONS OF PLANS; TO PERFORM TREE ROOT PRUNING ALONG DELINEATIONS ON PLANS; TO PROVIDE 8 FOOT CLEARANCE ABOVE SIDEWALK PAVEMENTS AND 16 FOOT CLEARANCE ABOVE ROADWAY PAVEMENTS: TO REPAIR TREE WOUNDS; AND TO PERFORM OTHER RECOMMENDED CLEANING, THINNING, REDUCING, AND PRUNING NECESSARY TO ACCOMMODATE UTILITIES. ALL DEBRIS SHALL BE REMOVED FROM SHA PROPERTY.
 - 7.22 TREE ROOT PRUNING SHALL BE PERFORMED ALONG THE LINE SHOWN ON THE PLANS IN CONFORMANCE WITH SECTION 1715. TREE ROOT PRUNING SHALL BE COMPLETED BEFORE BEGINNING EXCAVATION OR OTHER CONSTRUCTION ADJACENT TO TREES TO BE PRESERVED.

 \mid 7.25 FUTURE MAINTENANCE. ADDITIONAL MAINTENANCE THAT MAY BE REQUIRED AFTER HARDSCAPE, STREET FUNITURE OR PLANT MATERIALS ARE INSTALLED AND ACCEPTED BY SHA SUCH AS REPLACEMENT, WATERIN, WEEDING, MULCHING OR PEST CONTROL MA BE PROVIDED BY THE APPLICANT WHEN A PERMIT FOR THE PROPOSED WORK IS ISSUED BY THE SHA DISTRICT



810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com



PLANT LIST LP-03						
SYM	QUANTITY	BOTANICAL NAME	COMMON NAME	SIZE	BALL	REMARKS
LSW	1	Liquidambar styraciflua 'Ward'	Ward Sweetgum	2.5 IN. CAL.	B&B	CENTRAL LEADER
TAR	2	Tilia americana 'Redmond'	Redmond Linden	2.5 IN. CAL.	B&B	CENTRAL LEADER

REFER TO APPROVED SNRI 42023179E FOR TREE PROTECTION AND REMOVALS

MATERIAL LIST	- I P-03			
CATEGORY CO		DESCRIPTION	LOCATION	QUANTITY
701214	SY	PLACING FURNISHED SUBSOIL 18" DEPTH	TREE PIT (4'X10')	13.5
704365	SY	PLACING FURNISHED TOPSOIL 6" DEPTH	TREE PIT (4'X10')	13.
710170	SY	CONSTRUCT PLANTING BEDS	TREE PIT (4'X10')	13.
715015	SY	SHREDDED HARDWOOD BARK MULCHING 3" DEPTH	TRFF PIT (4'X10')	13.5

	NOTE: SHREDDED HARDWOOD BARK MULCH IS INCIDENTAL TO CONSTRUCT PLANTING BEDS	
RESIDENTIAL RESIDENTIAL 8812 FLOWER AVENUE PINTO EDWIN R & DELMY F L.28610 F.0298 TAX ID 01008216 PLAT 1150 RESIDENTIAL RESIDEN	RESIDENTIAL RESIDENTIAL 88896 FLEWER AVENUEUE ROJAS KATYA LRED683 F. 62704	
F 1311060	TAX ID 01009288 RESIDENTIAL 8818 FLOWER AVENUE GARTH-JESSICA LOWELL L.54739 F.0170	
O PEPCO (O 798425-6803) O EXAROW	TAX ID 01009814 PLAT 150 TAX ID 01009814 RESIDENTIAL 8818 FLOWER AVENUE GARTH JESSICA LOWELL L.54739 F.0170 TAX ID 01009814 PLAT 1150	
DRIVEWAY ASPHALT ASPHALT	T43 PEPCO 7984256226 7984256226 PEPCO 79842626 PEPCO 79842626 PEPCO 79842626 PEPCO 798426 PEPCO 79842626 PEPCO 7	
	FLOWER AVENUE 400 2B	311060
FLOWER AVENUE	111+00 ₁₈ "RCP +50 112+00 +50	N 486
S H GGR. SIDEWALK TO EACH TO SAGING TO THE S	DBINEWAY CONCRETE WH WH	
1 TAR	FEE TO THE PARTY OF THE PARTY O	
VACANT FLOWER AVENUE ARLYSS AVENUE LLC L.32437 F.0264 TAX ID 0354464 PLAT 209 VACANT CONSTRUCT PLANT BED 4.5 SY EACH TREE PIT INSTALL 18" SUBSOIL INSTALL 6" TOPSOIL INSTALL 3" SHREDDED	TYPICAL TYPICAL WACANI 882 FLOWER AVENUE STATE OF MARYLAND L.46798 F.0162 TAX ID 01397614 PLAT 810	/
HARDWOOD BARK MULC	TREE, SHRUB, AND PERENNIAL INSTALLATION AND ESTABLISHMENT - MASTER PLANT LIST	

TREE, SHRU	B, AND PERE						
SYM	1 Q	QUANTITY	BOTANICAL NAME	COMMON NAME	SIZE	BALL	REMARKS
LSW 6 L		Liquidambar styraciflua 'Ward'	Ward Sweetgum	3.0 IN. CAL.	B&B	CENTRAL LEADER	
QP <i>A</i>			Quercus phellos 'Abundance'	Abundance Willow Oak	3.0 IN. CAL.	B&B	CENTRAL LEADER
QS			Quercus shumardii	Shumard Oak	3.0 IN. CAL.	B&B	CENTRAL LEADER
TAR	l l	9	Tilia americana 'Redmond'	Redmond Linden	3.0 IN. CAL.	B&B	CENTRAL LEADER

Category Code	Unit	Description/Location	LOCATION	QUANTITY
701214	SY	PLACING FURNISHED SUBSOIL 18" DEPTH	TREE PIT	131
704365	SY	PLACING FURNISHED TOPSOIL 6" DEPTH	TREE PIT	131
710170	SY	CONSTRUCT PLANTING BEDS	TREE PIT	131
715015	SY	SHREDDED HARDWOOD BARK MULCHING 3" DEPTH	TREE PIT	131
700000	LF	TEMPORARY CHAIN LINK FENCE (TREE PROTECTION)	AS SHOWN	132
NOTE: SHREDD	ED HAI	RDWOOD BARK MULCH IS INCIDENTAL TO CONSTRUCT PLA	ANTING BEDS	

				11012: 011112001		
REVISION	ВҮ	APP'D	DATE	DESIGNED BY: KRD	DATE: FEBRUARY, 2025	
				DRAWN BY: MK	DATE: FEBRUARY, 2025	
				CHECKED BY: CC	DATE: FEBRUARY, 2025	
				DRAWING NO .:	DATE:	
				RECOMMENDED FOR APPROVAL		
				Chief, Design Section		

APPROVED

Division of Transportation Engineering

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES LANDSCAPE PLAN


SCALE: I"=20'

Date

SHEET<u>40</u> of <u>87</u>

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A REGISTERED LANDSCAPE ARCHITECT UNDER THE LAWS OF THE STATE OF MARYLAND.

LICENSE NO: #3190 EXPIRATION DATE: MAY 7, 2025



Į		EXISTING TREES 8/22/2022							
	SYMBOL	DBH (IN)	CRZ (IN)	COMMON NAME	SCIENTIFIC NAME	CONDITION	TBR	REMARKS	
	T1	5	7.5	MAPLE	ACER SPP.	GOOD	YES		
	T2	13	18.8	ZELKOVA	ZELKOVA SERRATA	GOOD	YES		
	T3	12	18.0	ZELKOVA	ZELKOVA SERRATA	GOOD	NO		
	T5	27	40.1	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T6	10	14.3	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T7	20	30.4	CALLERY PEAR	PYRUS CALLERYANA	FAIR	YES	GENERAL DIE-BACK / DRY	
	T8	16	24.0	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T9	1	1.5	OAK	QUERCUS SPP.	GOOD	NO		
	T10	1	1.5	OAK	QUERCUS SPP.	GOOD	NO		
	T11	24	36.0	CALLERY PEAR	PYRUS CALLERYANA	GOOD/FAIR	YES	MISSING 2 LG LIMBS	
	T12	2	3.0	ZELKOVA	ZELKOVA SERRATA	GOOD	YES		
	T13	2	3.0	LILAC TREE	SYRINGA VULGARIS	GOOD/FAIR	YES	DROUGHT STRESS	
	T14	2	3.0	LILAC TREE	SYRINGA VULGARIS	GOOD/FAIR	YES	DROUGHT STRESS	
	T15	10	15.0	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T16	2	3.0	ZELKOVA	ZELKOVA SERRATA	GOOD	YES		
	T17	21	31.5	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T18	17	25.9	CALLERY PEAR	PYRUS CALLERYANA	FAIR	YES	BRANCH DIE-BACK	
	T19	15	22.5	CALLERY PEAR	PYRUS CALLERYANA	FAIR	YES	BRANCH DIE-BACK	
	T20	13	18.8	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T21	18	27.0	CALLERY PEAR	PYRUS CALLERYANA	FAIR	YES	BROKEN BRANCH / HOLES IN TRUNK	
	T22	3	4.5	CALLERY PEAR	PYRUS CALLERYANA	POOR	YES	BROKEN TRUNK	
	T23	30+	45+	WHITE OAK	QUERCUS ALBA	GOOD	NO	NOT WITHIN ROW	
	T24	20	30.0	STANDING DEAD	OAK	DEAD	YES	TO BE REMOVED	
	T25	18	27.0	RED OAK	QUERCUS RUBRA	FAIR	NO	BRANCH DIE-BACK/ DAMAGE AT BASE	
	T26	12	18.0	WHITE OAK	QUERCUS ALBA	GOOD/FAIR	NO	TOPPED - UTILITY TRIM	
	T27	20	30.0	STANDING DEAD	OAK	DEAD	YES	TO BE REMOVED	
	T28	8	12.0	RED CEDAR	JUNIPERUS VIRGINIANA	GOOD	NO		
	T29	2	3.0	ZELKOVA	ZELKOVA SERRATA	GOOD	YES		
	T30	8	12.0	RED CEDAR	JUNIPERUS VIRGINIANA	GOOD	YES		
	T31	16	24.0	CALLERY PEAR	PYRUS CALLERYANA	FAIR	YES	GENERAL DIE-BACK / DRY	
	T32	14	21.0	CALLERY PEAR	PYRUS CALLERYANA	FAIR	YES	GENERAL DIE-BACK / DRY	
	T33	16	24.0	CALLERY PEAR	PYRUS CALLERYANA	FAIR	YES	GENERAL DIE-BACK / DRY	
	T34	8	12.0	RED CEDAR	JUNIPERUS VIRGINIANA	GOOD	YES		
	T35	12	17.3	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES	GENERAL DIE-BACK / DRY	
	T36	16	23.3	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES	GENERAL DIE-BACK / DRY	
	T37	13	18.8	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES	GENERAL DIE-BACK / DRY	
	T38	25	37.5	TULIP POPLAR	LIRIODENDRON TULIPIFERA	GOOD	NO		
	T39	17	25.5	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T40	13	18.8	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T41	17	25.5	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
	T42	9	13.5	VIRGINIA PINE	PINUS VIRGINIANA	FAIR/POOR	YES	DROUGHT STRESS / THIN CROWN	
	T43	24	36.0	QUERCUS ALBA	WHITE OAK	GOOD	NO		
	T44	12	18.0	ILEX SP.	HOLLY TREE	GOOD / FAIR	NO	DAMAGE AT BASE	
					,	i de la companya de	i e	,	

SPECIMEN / SIGNIFICANT TREE LIST								
SYMBOL	DBH (IN)	CRZ (IN)	COMMON NAME	SCIENTIFIC NAME	CONDITION	TBR	REMARKS	
T5	27	40.1	CALLERY PEAR	PYRUS CALLERYANA	GOOD	YES		
T11	24	36.0	CALLERY PEAR	PYRUS CALLERYANA	GOOD/FAIR	YES	MISSING 2 LG LIMBS	
T23	30+	45+	WHITE OAK	QUERCUS ALBA	GOOD	NO	NOT WITHIN ROW	
T38	25	37.5	TULIP POPLAR	LIRIODENDRON TULIPIFERA	GOOD	NO		
T43	24	36.0	QUERCUS ALBA	WHITE OAK	GOOD	NO		

TREE MITIGATION TABLE					
NUMBE	ER OF SIGNIFIC	CATION / S	PECIMEN TREES REMO	VED: 2	
T5	27 DBH		CALLERY PEAR		
T11	24 DBH		CALLERY PEAR		
MITIGATION REQUIREMENTS: TOTAL REQUIREMENT:			(1) INCH CALIPER TREE		
			(51) INCHES / 4 = 13 IN		
TREE M	1ITIGATION PR	OPOSED:	(31) 3" CALIPER TREES		

REMOVAL OF THESE TREES IS UNAVOIDABLE DUE TO EXPECTED IMPACT FROM PROJECT CONSTRUCTION.

PROPOSED TREES ARE NATIVE AND PER MC DSP RECOMMENDED TREE LIST.

MC DPS APPROVAL OF CHAPTER 55 TREE CANOPY REQUIREMENTS ARE NECESSARY FOR SEDIMENT AND EROSION CONTROL APPROVAL.

Date

1"=40'

REFER TO APPROVED SNRI 42023179E NATURAL RESOURCE INVENTORY AND TREE SAVE PLAN



OF MARYLAND.

LICENSE NO: #3190 EXPIRATION DATE: MAY 7, 2025

Stantec

3.0

ZELKOVA

Bicycle and Pedestrian Priority Areas

ZELKOVA SERRATA

GOOD

YES

REVISION	BY	APP'D	DATE	DESIGNED BY: KRD	DATE: FEBRUARY, 2025	
				DRAWN BY: KRD	DATE: FEBRUARY, 2025	
				CHECKED BY: CC	DATE: FEBRUARY, 2025	
				DRAWING NO .:	DATE:	
				RECOMMENDED FOR APPROVAL		
				Chief, Design Section		

Chief, Division of Transportation Engineering

APPROVED

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES LANDSCAPE PLAN TREE REMOVALS

SCALE: I" = 40'

SHEET\$LD-04\$ of 87

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A REGISTERED LANDSCAPE ARCHITECT UNDER THE LAWS OF THE STATE

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

MDOT SHA - "MARYLAND MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES", 2011 EDITION AND SUBSEQUENT REVISIONS. (MDMUTCD)

A A S H T O - "HIGHWAY SAFETY DESIGN AND OPERATIONS GUIDE" -1997

A A S H T O - "STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS LUMINAIRES AND TRAFFIC SIGNALS", 2001 EDITION (CATEGORY II FOR ALL OVERHEAD AND CANTILEVER SIGN STRUCTURES).

MATERIALS AND CONSTRUCTION

MDOT SHA - "STANDARD SPECIFICATIONS FOR CONSTRUCTION & MATERIALS", MOST CURRENT EDITION AND SUBSEQUENT REVISIONS AND SUPPLEMENTS.

MDOT SHA - "BOOK OF STANDARDS FOR HIGHWAY AND INCIDENTAL STRUCTURES", MOST CURRENT EDITION AND SUBSEQUENT REVISIONS AND SUPPLEMENTS.

DESIGN WIND

100 MPH - WOOD SUPPORTS IO YEAR RECURRENCE INTERVAL

100 MPH - GROUND MOUNT SIGN STEEL SUPPORTS 10 YEAR RECURRENCE INTERVAL

100 MPH - OVERHEAD AND CANTILEVER STRUCTURES 50 YEAR RECURRENCE INTERVAL

ALL DISTRICTS

DESIGN STRESS

SOIL BEARING PRESSURE - S = 3,000 P.S.F. (ASSUMED) SEE MATERIAL & CONSTRUCTION ABOVE AND SPECIAL PROVISIONS FOR DESIGN STRESSES FOR STRUCTURAL STEEL, ALUMINUM, REINFORCING STEEL AND CONCRETE.

CHAMFER

ALL EXPOSED EDGES OF CONCRETE SHALL HAVE A 3/4" X 3/4" CHAMFER.

CLASSIFICATION OF SIGNS

SIGNS ARE DIVIDED INTO TWO (2) GENERAL CATEGORIES. B) PANELS

I. GUIDE SIGNS

A) STRUCTURAL TYPES

OH - OVERHEAD C - CANTILEVER

WOOD SUPPORTS

GM - GROUND MOUNT, BREAKAWAY

OR NON-BREAKWAY BM - BRIDGE MOUNTED

2. STANDARD SIGNS (REGULATORY, WARNING, ETC.) A) STRUCTURAL TYPES

B) PANELS MATERIAL - SHEET ALUMINUM COPY - DIRECT APPLIED

MATERIAL - EXTRUDED ALUMINUM

I) HIGH INTENSITY (NEW SIGNS AND

REVISIONS TO EXISTING SIGNS)

COPY - DIRECT APPLIED

SQUARE TUBE

IDENTIFICATION OF SIGNS AND PANELS

EACH GUIDE SIGN IS IDENTIFIED BY A SIGN NUMBER ON THE PLANS AND IN THE TABULATIONS. (GM-I, GM-2, GM-3, ETC)

SIGNS ON STRUCTURES ARE IDENTIFIED WITH A NUMBER AND WHERE VARIATIONS OCCUR. A LETTER. (OH-IA, OH-IB, OH-IC OR OH-Ia, OH-Ib, OH-Ic)

STANDARD SIGNS

STANDARD SIGNS ARE IDENTIFIED BY PANEL NUMBERS AND ARE CLASSIFIED AS FOLLOWS

R - REGULATORY

W - WARNING

M - ROUTE MARKERS AND ACCESSORIES


D - DESTINATION AND MILEAGE PANELS S - SCHOOL

PANELS SHALL BE DESIGNATED TO AGREE WITH MARYLAND STANDARD SIGN BOOK. EACH STANDARD SIGN IS IDENTIFIED FIRST BY THE SHEET NUMBER, THEN BY THE NUMERICAL ORDER OF THE SIGN AS IT APPEARS ON THE PLAN. FOR EXAMPLE SHEET SN 2.1-101,102,103, ETC. SHEET SN 2.2-201,202,203,ETC.

PANEL LAYOUT AND ALPHABETS

I. GUIDE SIGN PANEL LAYOUTS ARE BASED ON THE A.A.S.H.T.O. MANUALS NOTED ABOVE. 2. STANDARD SIGN PANEL LAYOUTS ARE BASED ON THE MDMUTCD WITH SPECIFICATIONS DETAILED IN THE MARYLAND STATE HIGHWAY ADMINISTRATION PUBLICATION, "STANDARD SIGN BOOK", AVAILABLE ONLINE AT http://apps.roads.maryland.gov/businesswithsha/ bizstdsspecs/desmanualstdpub/publicationsonline/oots/internet_signbook.asp

ORIENTATION OF SIGN FACES



* UNDER 30 FEET FROM TRAVELLED ROADWAY TO NEAR EDGE OF SIGN - 93° AWAY FROM THE ROAD TO AVOID SPECULAR REFLECTION AS INDICATED IN 813.03 OF THE MARYLAND STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS.

OVER 30 FEET FROM TRAVELLED ROADWAY TO NEAR EDGE OF SIGN - 90°

REFLECTORIZATION

BACKGROUNDS, BORDERS, TEXTS AND ALL OTHER ELEMENTS OF SIGN PANELS SHALL BE REFLECTORIZED EXCEPT WHERE NOTED. REFER TO PROJECT REQUIREMENTS FOR MORE DETAIL.

SIGN LOCATIONS

I. GUIDE SIGNS ARE LOCATED ON THE PLANS BY DIMENSION TO SURVEY STATIONS, OR WHEN NECESSARY, TO IDENTIFIABLE PHYSICAL FEATURES.

2. ALL CHANGES IN THE LOCATIONS OF SIGNS AS SHOWN ON THE PLAN SHALL HAVE THE PRIOR APPROVAL OF THE ENGINEER.

EXISTING UTILITIES

THE ENGINEER DOES NOT WARRANT OR GUARANTEE THE ACCURACY OR COMPLETENESS OF UTILITY INFORMATION SHOWN ON THE PLAN.IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO LOCATE AND PROTECT ALL EXISTING FACILITIES WHICH MIGHT BE AFFECTED BY THIS WORK OR HIS OPERATION.

ROADSIDE SIGNS

I. VERTICAL ALIGNMENT

POSITION PANEL SO FACE IS PLUMB.

2. HORIZONTAL ALIGNMENT (SEE DIAGRAM ABOVE)

A) ON STRAIGHT ROADWAY SECTIONS, ANGLE OF SIGN FACE TO ROADWAY VARIES WITH DISTANCE FROM TRAVELLED ROADWAY TO NEAR EDGE OF SIGN - SEE DIAGRAM.

B) ON THE INSIDE OF HORIZONTAL CURVES, POSITION SIGN SO FACE OF PANEL MAKES AN ANGLE OF 90° WITH A CHORD BETWEEN A POINT ON NEAR EDGE OF PAVEMENT AT SIGN LOCATION AND A POINT ON EDGE OF PAVEMENT 500' IN ADVANCE OF SIGN. C) ON THE OUTSIDE OF HORIZONTAL CURVES, POSITION SIGN SO FACE OF PANEL IS AT RIGHT ANGLES TO THE TANGENT OF THE CURVE AT THE SIGN LOCATION.

D) POSITIONING OF SIGNS AT GORES AND RAMP SEPARATIONS IS REFERRED TO THE NORMAL EDGE OF THE MAINLINE ROADWAY.

OVERHEAD SIGNS

I. VERTICAL ALIGNMENT

POSITION PANELS FOR ALL OVERHEAD STRUCTURES SO THAT PANEL FACE IS PLUMB. 2. OVERHEAD SIGN STRUCTURES SHALL NOT BE ERECTED WITHOUT ATTACHING LUMINAIRES,

SUPPORTS, AND/OR SIGNS. 3. HORIZONTAL ALIGNMENT

A) POSITION ALL OVERHEAD SIGNS SO THAT THE FACE OF THE PANEL IS AT RIGHT ANGLES TO THE NORMAL EDGE OF ROADWAY, IF ON A STRAIGHT ROADWAY SECTION.

B) POSITION ALL OVERHEAD SIGNS SO THAT THE FACE OF THE PANEL IS AT RIGHT ANGLES TO THE TANGENT OF THE CURVE AT SIGN LOCATION, IF ON A HORIZONTAL CURVE.

C) POSITIONING OF SIGNS AT GORES AND RAMP SEPARATIONS IS REFERRED TO THE NORMAL EDGE OF THE MAINLINE ROADWAY.

4. VERTICAL CLEARANCE

A) OVERHEAD SIGNS SHALL HAVE A MINIMUM VERTICAL CLEARANCE OF 17'-9" FROM TOP OF ROADWAY TO TO THE BOTTOM OF SIGN LUMINAIRE. ALL SIGN LUMINAIRES ARE TO BE AT THE SAME ELEVATION. B) IF THE CONTRACTOR CANNOT OBTAIN 17'-9" (SEE 3A) CLEARANCE, THEY SHALL CEASE WORK

AND CONTACT THE PROJECT ENGINEER FOR FURTHER INSTRUCTIONS. THE PROJECT ENGINEER

MAY CONTACT THE TRAFFIC ENGINEERING DESIGN DIVISION FOR ASSISTANCE. C) ON ALL OVERHEAD SIGNS, THE MINIMUM CLEARANCE TO BOTTOM OF DESIGN SIGN: 20'-9". PROJECT REQUIREMENTS

ALL NEW SIGNS ON THIS PROJECT SHALL BE FABRICATED FROM SHEETING WHICH MEETS ALL OF THE FOLLOWING REQUIREMENTS, UNLESS OTHERWISE SPECIFIED IN THE CONTRACT DOCUMENTS, OR AS DIRECTED BY THE ENGINEER:

I. SHEETING SHALL MEET THE REQUIREMENTS OF SECTIONS 813 AND 950.03 OF MDOT SHA'S STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS, MOST CURRENT EDITION AND SUBSEQUENT REVISIONS AND SUPPLEMENTS.

2. LISTED ON MDOT SHA OFFICE OF TRAFFIC AND SAFETY'S QUALIFIED PRODUCTS LIST (QPL).

PROJECT REQUIREMENTS CONT'D

3. THE FOLLOWING TYPES OF SHEETING SHALL BE USED FOR THE SPECIFIED SIGN CLASSIFICATIONS:

GENERAL NOTE: ALL COLORS SHALL BE RETROREFLECTIVE EXCEPT BLACK. BLACK TEXT, BORDERS, SYMBOLS OR ANY BLACK ELEMENTS OF ANY SIGN SHALL BE NON-REFLECTIVE. THIS APPLIES TO ALL MDOT SHA SIGNS AS SHOWN BELOW.

A) GUIDE, EXIT GORE, GENERAL INFORMATION, AND SERVICE SIGNS - ALL RETROREFLECTIVE SHEETING ELEMENTS OF THESE SIGNS SHALL MEET OR EXCEED THE REQUIREMENTS FOR ASTM TYPE XI(II).

B) WARNING SIGNS - RETROREFLECTIVE SHEETING FOR WARNING SIGNS (FLUORESCENT YELLOW AND FLUORESCENT ORANGE) SHALL MEET OR EXCEED THE REQUIREMENTS FOR ASTM TYPE XI(II). REGULATORY MESSAGES WITHIN WARNING SIGNS SHALL FOLLOW THE REQUIREMENTS FOR REGULATORY SIGNS.

C) SCHOOL SIGNS - RETROREFLECTIVE SHEETING FOR SCHOOL SIGNS (FLUORESCENT YELLOW AND FLUORESCENT YELLOW-GREEN) SHALL MEET OR EXCEED THE REQUIREMENTS FOR ASTM TYPE XI(II). REGULATORY MESSAGES WITHIN SCHOOL SIGNS SHALL FOLLOW THE REQUIREMENTS FOR REGULATORY SIGNS.

D) REGULATORY SIGNS - FALL INTO THREE SUBCATEGORIES:

(I). "RED" REGULATORY SIGNS; (SPECIFICALLY - STOP, YIELD, DO NOT ENTER AND WRONG WAY). ALL RETROREFLECTIVE SHEETING ELEMENTS OF THESE SIGNS SHALL MEET OR EXCEED THE REQUIREMENTS FOR ASTM TYPE XI(II).

(II). ALL R7 AND R8 SERIES PARKING RELATED SIGNS AND THEIR SUPPLEMENTAL PANELS, NO TRESPASSING SIGNS, AND SIGNS DIRECTED AT PEDESTRIANS AND BICYCLISTS ONLY. ALL RETROREFLECTIVE SHEETING ELEMENTS OF THESE SIGNS SHALL MEET THE REQUIREMENTS FOR ASTM TYPE IV (4).

(III). ALL OTHER REGULATORY SIGNS - ALL RETROREFLECTIVE SHEETING ELEMENTS OF THESE SIGNS SHALL MEET ASTM TYPE IV (4) INCLUDING RED ELEMENTS. WARNING MESSAGES WITHIN REGULATORY SIGNS SHALL FOLLOW THE REQUIREMENTS FOR WARNING SIGNS.

E) ROUTE MARKERS (INDEPENDENT USE AND GUIDE SIGN USE)

INDEPENDENT USE: ALL RETROREFLECTIVE SHEETING ELEMENTS OF THESE SIGNS SHALL MEET BUT NOT TO EXCEED THE REQUIREMENTS FOR ASTM TYPE IV (4).

GUIDE SIGN USE: WHEN INCORPORATED IN THE BODY OF A GUIDE SIGN, ALL RETROREFLECTIVE SHEETING ELEMENTS OF THESE SIGNS SHALL MEET THE SHEETING REQUIREMENTS OF THE GUIDE SIGNS FOR WHICH THEY ARE TO BE APPLIED; ASTM TYPE XI(II).

F) LOGOS AND / OR GRAPHICS - WITHIN SIGNS SHALL FOLLOW THE REQUIREMENTS FOR THE RESPECTIVE SIGN CLASSIFICATION UNLESS OTHERWISE SPECIFIED IN THE CONTRACT DOCUMENTS, OR AS DIRECTED BY THE ENGINEER.

G) SPECIFIC SERVICE (LOGO) SIGNING - ALL COPY, DIVIDER BORDERS, LOGOS AND ARROWS SHALL BE DEMOUNTABLE ALUMINUM OVERLAYS, .032 MINIMUM TO .063 MAXIMUM. ALL RETROREFLECTIVE SHEETING ELEMENTS OF THESE SIGNS SHALL MEET OR EXCEED THE REQUIREMENTS FOR ASTM TYPE XI(II). DISTANCES ON DIRECTIONAL ARROWS WHEN SPECIFIED SHALL BE BLACK. THE OVERLAYS ARE TO BE APPLIED WITH .125 ALUMINUM POP RIVETS TO THE BODY OF THE MAIN SIGN.

H) CIVIL DEFENSE SIGNS AND OTHER SIGNS - NOT SPECIFICALLY FALLING INTO ONE OF THE CATEGORIES ABOVE, SHALL FOLLOW THE GUIDELINES FOR THE SIGN CLASSIFICATION THAT MOST CLOSELY MATCHES THE COLOR(S) OF THE PROPOSED SIGN.

4. THE FOLLOWING MINIMUM THICKNESS SHALL BE USED FOR THE APPROPRIATE WIDTH OF SHEET ALUMINUM BLANKS:

LONGEST DIMENSION MINIMUM THICKNESS UP TO 12"..... ..0.040" GREATER THAN 12" TO 24"... ..0.063" GREATER THAN 24" TO 36" ..0.080" GREATER THAN 36" TO 48"---..0.100" OVER 48".... ..0.125"

	DEPARTMENT OF TRANSPORTATION DIVISION OF TRAFFIC ENGINEER AND OPERATIONS MONTGOMERY COUNTY, MD
	APPROVED
For	
BY	
DATE:	

SND-01

Stantec

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com



١.	REVISION	BY	APP'D	DATE	DESIGNED BY: JRGB	DATE: FEBRUARY,	2025	
					DRAWN BY: JRGB	DATE: FEBRUARY,	2025	_
					CHECKED BY: RJM	DATE: FEBRUARY,	2025	
					DRAWING NO.:	DATE:		
					RECOMMENDED FOR APPROVAL			
					-			
					Chief, Design Section		Date	
					APPROVED			
					Chief,		 Date	
					Division of Transportation Engin	eering		SCA

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

FLOWER AVENUE SEPARATED BIKE LANES SIGNING AND MARKING DETAILS

CALE: NONE


SHEET<u>42</u> of <u>87</u>

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE


OF MARYLAND. LICENSE NO:

EXPIRATION DATE:


TYPICAL CONFLICT ZONE DETAIL
AT DRIVEWAYS ALONG MCDOT ROADWAYS




BIKE LANE SYMBOL DETAIL




POST MOUNTED SIGN DETAIL







TYPICAL CROSSWALK DETAIL SHA



TYPICAL SIGNALIZED CROSSWALK DETAIL MCDOT

NOTE: STOP BARS AT UNSIGNALIZED CROSSWALK SHALL BE 16" FOR MCDOT





YIELD MARKING DETAIL

	DEPARTMENT OF TRANSPORTATION DIVISION OF TRAFFIC ENGINEER AND OPERATIONS MONTGOMERY COUNTY, MD
	APPROVED
For	
BY	
DATE:	

SND-02

REVISION	BY	APP'D	DATE	DESIGNED BY: JRGB DRAWN BY: JRGB	DATE: FEBRUA		DEPARTMENT	OF TRANSPORTATION
				CHECKED BY: RJM	DATE: FEBRUA	•		SPORTATION ENGINEERING Y COUNTY, MARYLAND
				DRAWING NO.:	DATE:		MONTOOMER	I COUNTI, MARTLAND
				RECOMMENDED FOR APPR Chief, Design Section APPROVED	OVAL	Date	SEPARATE	ER AVENUE ID BIKE LANES MARKING DETAILS
				Chief, Division of Transportation	n Engineering	Date	SCALE: NONE	SHEET <u>43</u> of <u>87</u>



810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com



2/26/2025 \\!IS0527-PPFSS0|\shared projects\203

PROFESSIONAL CERTIFICATION:


OF MARYLAND.


LICENSE NO: _

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

_ EXPIRATION DATE: _


\\US0527-PPFSS0|\shared_projects\20262|3||6\700 CADD\700 Sheet\p






2/26/2025 //IIS0527-PPFSS01/shared projects/2026213116/700 CADD/700 Sheetlbsn-Pnn3 Fi

- (A) INSTALL 5 INCH YELLOW LEAD FREE THERMOPLASTIC PAVEMENT MARKING (DOUBLE)
- B INSTALL 5 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING (SOLID)
- (C) INSTALL 5 INCH YELLOW LEAD FREE THERMOPLASTIC PAVEMENT MARKING (SOLID)
- (D) INSTALL 5 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING (3-9-3 DOTTED)
- (E) INSTALL 5 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING (3-3-3 DOTTED)
- (F) INSTALL 5 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING (2-2-2 DOTTED)
- G INSTALL 5 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING (10-30-10 BROKEN) H INSTALL 12 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING
- (I) INSTALL 16 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING
- (J) INSTALL 24 INCH WHITE LEAD FREE THERMOPLASTIC PAVEMENT MARKING
- (K) INSTALL BIKE LANE PREFORMED THERMOPLASTIC PAVEMENT MARKING WITH ARROW
- (L) INSTALL SHARED BIKE LAME PREFORMED THERMOPLASTIC PAVEMENT MARKING
- (M) INSTALL WHITE PREFORMED THERMOPLASTIC PAVEMENT MARKING LEGENDS AND SYMBOLS (N) INSTALL PRE-FORMED THERMOPLASTIC GREEN PAINT (HIGH VOLUME AREAS)
- (O) INSTALL EPOXY-MODIFIED ACRYLIC WATERBORNE GREEN PAINT (LOW VOLUME AREAS)
- (P) REMOVAL OF EXISTING PAVEMENT MARKING LINES





EX. SIGN POST PR. SIGN POST EX. SIGN TO BE REMOVED

	DEPARTMENT OF TRANSPORTATION DIVISION OF TRAFFIC ENGINEER AND OPERATIONS MONTGOMERY COUNTY, MD
	APPROVED
For	
ВҮ	
DATE:	

SIGNING NOTES

- SIGN(S) TO BE REMOVED BY OTHERS





Bicycle and Pedestrian Priority Areas

NO.	REVISION	BY	APP'D	DATE	DESIGNED BY: JRGB	DATE: FEBRUARY,	2025
					DRAWN BY: JRGB	DATE: FEBRUARY,	2025
					CHECKED BY: RJM	DATE: FEBRUARY,	2025
├					DRAWING NO.:	DATE:	
					RECOMMENDED FOR APPROVAL		
					Chief, Design Section APPROVED		Date
						neering	Date

SN-04 DEPARTMENT OF TRANSPORTATION

FLOWER AVENUE

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

SEPARATED BIKE LANES SIGNING AND MARKING PLAN

SHEET<u>47</u> of <u>87</u> SCALE: I"=20'

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT IAM A DULY LICENSED
PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE
OF MARYLAND

LICENSE NO: _

EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

** SIGN(S) TO BE INSTALLED BY OTHERS *** SIGN(S) TO BE RELOCATED BY OTHERS

SN-01

RIDE ON BUS

RI-6a(I)

RI-6a(I)

RI-6a(I)

R3-7R

RI-6a(I)

RI-6a(I)

R7-8(3)

R7-8(3)

R7-I

R6-IR

R5-I, R6-IR

R7-I(I), R7-I08

R7-8(3), FINE

R7-8(3), EXIT, EXIT

R5-I, RI-I, R6-IR, R6-IL

R5-I, RI-I, R6-IR, R6-IL

R7-I(I), R7-I08

R7-I(I), R7-I08

R7-I(I), R7-I08

RI-6a(3)L, RI5-8

RI-6a(3)L, RI5-8

R7-I(I), R7-I08

R7-I(I), R7-I08

R7-I(I), R7-I08

R7-I(I), R7-I08

RI-6a(3)L, RI5-8

SPECIAL, RIO-6a

RI-6a(I)

RI-6a(I)

RI-6a(I)

R3-7R

SPECIAL, RI-2

SPECIAL, RIO-6a

36

DISCOVER LONG BRANCH

M3-I, MI-5, M6-IL, M3-3, MI-5, M6-IR

M3-2, MI-5, M6-IL, M3-4, MI-5, M6-IR

25MPH SPEED LIMIT

SPECIAL, RIO-6a

R5-I

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO: _ _ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

REMARKS



RELOCATE BY OTHERS

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST 4

I - PERFORATED TUBULAR STEEL POST 9

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST | 3

I - PERFORATED TUBULAR STEEL POST 2

I - PERFORATED TUBULAR STEEL POST 2

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST | 17.25

I - PERFORATED TUBULAR STEEL POST 10.75

I - PERFORATED TUBULAR STEEL POST | 10.75

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST 10.75

I - PERFORATED TUBULAR STEEL POST 18.4

I - PERFORATED TUBULAR STEEL POST 3 i - perforated tubular steel post 4

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST | 3

I - PERFORATED TUBULAR STEEL POST | 3

I - PERFORATED TUBULAR STEEL POST 9

I - PERFORATED TUBULAR STEEL POST 2

I - PERFORATED TUBULAR STEEL POST | 4

REMOVE

RELOCATE, I - PERFORATED TUBULAR STEEL POST

I - PERFORATED TUBULAR STEEL POST | 6.25

).	REVISION	BY	APP'D	DATE	DESIGNED BY: JRGB DAT	E: FEBRUARY, 2025	
					DRAWN BY: JRGB DAT	E: FEBRUARY, 2025	
					CHECKED BY: RJM DAT	E: FEBRUARY, 2025	
					DRAWING NO.: DAT	E:	
					RECOMMENDED FOR APPROVAL Chief, Design Section		
					APPROVED	Bare	
					Chief, Division of Transportation Engineering	Date	

CODE NUMBERS *

12

13

14

15

16

19

SEPARATED BIKE LANES SIGNING AND MARKING SCHEDULE

SHEET<u>48</u> of <u>87</u>

FLOWER AVENUE

	* CODE NUMBER DESCRIPTION & UNIT		* CODE NUMBER DESCRIPTION & UNIT					
CODE NUMBERS	DESCRIPTION	UNIT	CODE NUMBERS	DESCRIPTION	UNIT			
	SHEET ALUMINUM SIGNS	S.F.	9	16" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.			
2	FURNISH AND INSTALL PERFORATED TUBULAR STEEL SIGN SUPPORTS	EACH	10	24" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.			
3	FURNISH AND INSTALL ANCHOR BASES FOR SQUARE TUBULAR STEEL POST	EACH		WHITE PREFORMED THERMOPLASTIC PAVEMENT MARKING LEGENDS AND SYMBOLS	S.F.			
4	REMOVE EXISTING SIGNS	S.F.	12	BIKE LANE PREFORMED THERMOPLASTIC PAVEMENT MARKING WITH ARROW	S.F.			
5	RELOCATE EXISTING SIGNS	S.F.	13	SHARROW PAVEMENT MARKING	S.F.			
6	5" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	14	REMOVAL OF EXISTING PAVEMENT MARKING LINE, ANY WIDTH	L.F.			
7	5" YELLOW LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	15	GREEN PAVEMENT MARKING; PREFORMED THERMOPLASTIC	S.F.			
8	12" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	16	GREEN PAVEMENT MARKING; EPOXY	S.F.			

SPECIAL, RIO-6a		I - PERFORATED TUBULAR STEEL POST 4	I	ı				
	* CODE NUMBER DESCRIPTION & UNIT				* ()			
	CODE NUMBERS	DESCRIPTION	UNIT	CODE NUMBERS		DESCRIPTION		UNIT
		SHEET ALUMINUM SIGNS	S.F.	9	16" WHITE LEAD FREE REFLECTIVE	THERMOPLASTIC PAVEMENT MARKINGS		L.F.
	2	FURNISH AND INSTALL PERFORATED TUBULAR STEEL SIGN SUPPORTS	EACH	10	24" WHITE LEAD FREE REFLECTIVE	THERMOPLASTIC PAVEMENT MARKINGS		L.F.
	3	FURNISH AND INSTALL ANCHOR BASES FOR SQUARE TUBULAR STEEL POST	EACH	[]	WHITE PREFORMED THERMOPLAST	IC PAVEMENT MARKING LEGENDS AND S	YMBOLS	S.F.
	4	REMOVE EXISTING SIGNS	S.F.	12	BIKE LANE PREFORMED THERMOPI	ASTIC PAVEMENT MARKING WITH ARROW	1	S.F.
	5	RELOCATE EXISTING SIGNS	S.F.	13	SHARROW PAVEMENT MARKING			S.F.
	6	5" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	14	REMOVAL OF EXISTING PAVEMENT	MARKING LINE, ANY WIDTH		L.F.
	7	5" YELLOW LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	15	GREEN PAVEMENT MARKING; PREF	ORMED THERMOPLASTIC		S.F.
	8	12" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	16	GREEN PAVEMENT MARKING; EPOX	Y		S.F.

9.25

17.25

	* CODE NUMBER DESCRIPTION & UNIT			* CODE NUMBER DESCRIPTION & UNIT	
CODE NUMBERS	DESCRIPTION	UNIT	CODE NUMBERS	DESCRIPTION	UNIT
I	SHEET ALUMINUM SIGNS	S.F.	9	16" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.
2	FURNISH AND INSTALL PERFORATED TUBULAR STEEL SIGN SUPPORTS	EACH	10	24" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.
3	FURNISH AND INSTALL ANCHOR BASES FOR SQUARE TUBULAR STEEL POST	EACH	II	WHITE PREFORMED THERMOPLASTIC PAVEMENT MARKING LEGENDS AND SYMBOLS	S.F.
4	REMOVE EXISTING SIGNS	S.F.	12	BIKE LANE PREFORMED THERMOPLASTIC PAVEMENT MARKING WITH ARROW	S.F.
5	RELOCATE EXISTING SIGNS	S.F.	13	SHARROW PAVEMENT MARKING	S.F.
6	5" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	14	REMOVAL OF EXISTING PAVEMENT MARKING LINE, ANY WIDTH	L.F.
7	5" YELLOW LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	15	GREEN PAVEMENT MARKING; PREFORMED THERMOPLASTIC	S.F.
8	12" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	16	GREEN PAVEMENT MARKING; EPOXY	S.F.
	<u> </u>				- '

SN-05 DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

SCALE: NONE

PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO: _ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com



NO.	REVISION	BY	APP'D	DATE	DESIGNED BY: JRGB	DATE: FEBRUA	ARY, 2025	— DEPA
					DRAWN BY: JRGB	DATE: FEBRUA	ARY, 2025	
					CHECKED BY: RJM	DATE: FEBRUA	ARY, 2025	DIVISION
					DRAWING NO .:	DATE:		MO
					RECOMMENDED FOR APPRO Chief, Design Section APPROVED	OVAL	Date	- S SIGNI
					Chief, Division of Transportation	Engineering	Date	- SCALE: NONE

SEPARATED BIKE LANES SIGNING AND MARKING SCHEDULE

FLOWER AVENUE

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

	* CODE NUMBER DESCRIPTION & UNIT			* CODE NUMBER DESCRIPTION & UNIT	
CODE NUMBERS	DESCRIPTION	UNIT	CODE NUMBERS	DESCRIPTION	UNIT
I	SHEET ALUMINUM SIGNS	S.F.	9	16" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.
2	FURNISH AND INSTALL PERFORATED TUBULAR STEEL SIGN SUPPORTS	EACH	10	24" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.
3	FURNISH AND INSTALL ANCHOR BASES FOR SQUARE TUBULAR STEEL POST	EACH	II	WHITE PREFORMED THERMOPLASTIC PAVEMENT MARKING LEGENDS AND SYMBOLS	S.F.
4	REMOVE EXISTING SIGNS	S.F.	12	BIKE LANE PREFORMED THERMOPLASTIC PAVEMENT MARKING WITH ARROW	S.F.
5	RELOCATE EXISTING SIGNS	S.F.	13	SHARROW PAVEMENT MARKING	S.F.
6	5" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	14	REMOVAL OF EXISTING PAVEMENT MARKING LINE, ANY WIDTH	L.F.
7	5" YELLOW LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	15	GREEN PAVEMENT MARKING; PREFORMED THERMOPLASTIC	S.F.
8	12" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS	L.F.	16	GREEN PAVEMENT MARKING; EPOXY	S.F.

SIGN										CODE	NUMBERS	*									
NO.		REMARKS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
SN-02																					
41)	R7-108	i - perforated tubular steel post	1.5		I																
42	R7-108	REMOVE				1.5															
43	R7-I(I), R7-I08	REMOVE				3															
44)	R7-I(I), R7-I08	I - PERFORATED TUBULAR STEEL POST	3		1																
45)	RI-6a(I), RI-6a(I)	REMOVE				6															
46	R5-I, R6-IR, R6-IL	I - PERFORATED TUBULAR STEEL POST	12.25		I																
47)	RI-6a(2)	RELOCATE					7.5														
48	RI-6a(I)	I - PERFORATED TUBULAR STEEL POST	3		I																
49	R4-7R, OMI-I	REMOVE				7.25															
50	RI-6a(I), RI-6a(I)	REMOVE				6															
51)	RIDE ON BUS	RELOCATED BY OTHERS																			
52	R7-I(I)	REMOVE				1.5															
53	R4-7R, OMI-I	REMOVE				1.5															
54	R5-I, R6-IR, R6-IL	I - PERFORATED TUBULAR STEEL POST	12.25																		
(55)	RI-6a(3)L, RI5-8	MOUNT ON EXISTING POST	10.75																		
56	RI-I	REMOVE																			
57	ADOPT A ROAD, LAW OFC REID M WEINSTEIN LLC	EXISTING																			
58	R7-4(I)	I - PERFORATED TUBULAR STEEL POST	1.5																		
59	R7-I(I)	REMOVE				1.5															
60	R7-8(3), R7-8P	I - PERFORATED TUBULAR STEEL POST	2.5	l																	
61	R7-8(3)	I - PERFORATED TUBULAR STEEL POST	2	l																	
62	RI-6a(3)L, RI5-8	i - perforated tubular steel post	10.75	l	I																
63	RI-I	REMOVE				5															
64	R7-I(I)	REMOVE				1.5															
65	R7-4(I)	i - perforated tubular steel post	1.5																		
66	R7-4(I)	I - PERFORATED TUBULAR STEEL POST	1.5	l	I																
67	R7-4(I)	I - PERFORATED TUBULAR STEEL POST	1.5																		
68	RI-6a(I)	i - perforated tubular steel post	3																		
69	R7-I(I), R7-I08	REMOVE				1.5															
70	RI-6a(2)	i - perforated tubular steel post	7.5		I																
71)	Discover Long Branch	RELOCATE, I - PERFORATED TUBULAR STEEL POST		I	ı		5														
72	RIDE ON BUS	RELOCATED BY OTHERS																			
73	RI-6a(2)	REMOVE				7.5															
74	RI-6a(3)L, RI5-8	I - PERFORATED TUBULAR STEEL POST	10.75																		
75	R7-4(I)	I - PERFORATED TUBULAR STEEL POST	1.5	I																	
76	RI-6a(3)L, RI5-8	I - PERFORATED TUBULAR STEEL POST	10.75																		
SN-03																					
77)	RI-6a(2)	I - PERFORATED TUBULAR STEEL POST	7.5																		
78	RI-6a(I), RI-6a(I)	REMOVE				6															
79	RI-6a(I)	I - PERFORATED TUBULAR STEEL POST	3		I																
80	RI-6a(3)L, RI5-8	I - PERFORATED TUBULAR STEEL POST	10.75																		
81)	RIO-I5BP(R)	I - PERFORATED TUBULAR STEEL POST	7.5																		
82	RI-I, FLOWER AVE, FLOWER AVE, ARLISS ST, ARLISS ST	RELOCATE		1			13														

SN-06

SHEET<u>49</u> of <u>87</u>

SIGN

NO.

SN-03

88

92

SN-04

RI-2, SPECIAL

RIO-I5BP(I)

RI-6a(2), OMI-3

RI-6a(2), RI-6a(2)

RI-6a(I), RI-6a(I)

WII-2, WI6-7L

R7-I(I)

R7-I(I)

R7-4(I)

R3-7(I)R

R4-11

R4-11

R3-7R

CONSTRUCTION SIGN

NO RIGHT TURNS, TRUCK

DO NOT THROW LITTER \$1500 FINE

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO: _ __ EXPIRATION DATE: _

TOTAL

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

REMARKS

I - PERFORATED TUBULAR STEEL POST 3

I - PERFORATED TUBULAR STEEL POST 7.5

I - PERFORATED TUBULAR STEEL POST 9.75

I - PERFORATED TUBULAR STEEL POST 1.5

I - PERFORATED TUBULAR STEEL POST | 12

I - PERFORATED TUBULAR STEEL POST | 6.25

I - PERFORATED TUBULAR STEEL POST | 6.25

I - PERFORATED TUBULAR STEEL POST 9

REMOVE BY OTHERS

EXISTING

EXISTING

REMOVE

REMOVE

REMOVE

REMOVE

EXISTING



NO.	REVISION	BY	APP'D	DATE	DESIGNED BY: JRGB	DATE: FEBRUA	RY, 2025	— DEPA
					DRAWN BY: JRGB	DATE: FEBRUA	RY, 2025	
					CHECKED BY: RJM	DATE: FEBRUA	RY, 2025	DIVISION
			1		DRAWING NO .:	DATE:		MO
					RECOMMENDED FOR APPI Chief, Design Section APPROVED	ROVAL	Date	- S S I GN I
					Chief, Division of Transportation	on Engineering	Date	- SCALE: NONE

SEPARATED BIKE LANES GIGNING AND MARKING SCHEDULE

REVISION	BY	APP'D	DATE	DESIGNED BY: JRGB	DATE: FEBRUARY, 2025	DEPARTMENT OF TRANSPORTATION	NI
				DRAWN BY: JRGB	DATE: FEBRUARY, 2025		
				CHECKED BY: RJM	DATE: FEBRUARY, 2025	DIVISION OF TRANSPORTATION ENGINEER	INC
				DRAWING NO.:	DATE:	MONTGOMERY COUNTY, MARYLAND	
				RECOMMENDED FOR APPROVAL			

		338.2	69	69	141	52	3550	3369	484	77	598	271	144	20	765
	* CODE NUMBER DESCRIPTION & UNIT							* CODE 1	NUMBER DES	SCRIPTION &	UNIT				
CODE NUMBERS	DESCRIPTION		UNIT	CODE NU	JMBERS				DESC	CRIPTION					UNIT
I	SHEET ALUMINUM SIGNS		S.F.	9		16" WHITE LEA	D FREE REF	LECTIVE THE	RMOPLASTIC	PAVEMENT	MARKINGS				L.F.
2	FURNISH AND INSTALL PERFORATED TUBULAR STEEL SIGN SUPPORTS		EACH	10		24" WHITE LEA	AD FREE RE	LECTIVE THE	RMOPLASTI	C PAVEMENT	MARKINGS				L.F.
3	FURNISH AND INSTALL ANCHOR BASES FOR SQUARE TUBULAR STEEL POST		EACH			WHITE PREFOR	RMED THERM	OPLASTIC PA	VEMENT MA	RKING LEGE	NDS AND S'	YMBOLS			S.F.
4	REMOVE EXISTING SIGNS		S.F.	12		BIKE LANE PE	REFORMED T	HERMOPLASTI	C PAVEMEN	T MARKING	WITH ARROW	,			S.F.
5	RELOCATE EXISTING SIGNS		S.F.	13		SHARROW PA	VEMENT MAF	KING							S.F.
6	5" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS		L.F.	14		REMOVAL OF	EXISTING PA	VEMENT MAF	RKING LINE,	ANY WIDTH					L.F.
7	5" YELLOW LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS		L.F.	15		GREEN PAVEN	MENT MARKIN	G; PREFORME	D THERMOP	_ASTIC					S.F.
8	12" WHITE LEAD FREE REFLECTIVE THERMOPLASTIC PAVEMENT MARKINGS		L.F.	16		GREEN PAVEN	MENT MARKIN	G; EPOXY							S.F.

SHEET<u>50</u> of <u>87</u>

FLOWER AVENUE

CODE NUMBERS *

10

12

13

14

15

16


19

5


7.25

15

1.5



PLOTTED: 2/26/2025
FILE: \\US0527-PPFSS01\shared_projects\2026213116\700 CADD\700 Sheet\pSG-P001_FlowerAve.dgn



PROJECT DESCRIPTION

I. GENERAL

THIS PROJECT INVOLVES THE RECONSTRUCTION OF AN EXISTING TRAFFIC CONTROL SIGNAL WITH INTERCONNECT, STREET LIGHTING AND A TRAFFIC SURVEILLANCE CAMERA AT THE INTERSECTION OF MD 320 (PINEY BRANCH RD) AND FLOWER AVE IN MONTGOMERY COUNTY. A NEW MAST ARM TRAFFIC SIGNAL WITH INTERCONNECT, STREET LIGHTING, TRAFFIC SURVEILLANCE CAMERA AND COUNTDOWN PEDESTRIAN SIGNALS WITH AUDIBLE PUSHBUTTONS SHALL BE INSTALLED AT THIS LOCATION. MD 320 (PINEY BRANCH RD) IS ASSUMED TO RUN IN A NORTH-SOUTH DIRECTION.

II. INTERSECTION OPERATION

- 1. THE INTERSECTION SHALL OPERATE IN A NEMA EIGHT-PHASE, SEMI-ACTUATED MODE, WITH THE MD 320 (PINEY BRANCH RD) APPROACHES RUNNING CONCURRENTLY. THE EXCLUSIVE/PERMISSIVE LEFT TURN PHASES FOR BOTH APPROACHES OF MD 320 (PINEY BRANCH RD) SHALL REMAIN IN OPERATION. ALTERNATE LEADING PEDESTRIAN INTERVAL PHASING IS PROVIDED ACROSS THE NORTH AND SOUTH LEGS OF THE INTERSECTION. THE PEDESTRIAN PHASES ACROSS FLOWER AVE SHALL BE ON RECALL. THE FLOWER AVE APPROACHES SHALL HAVE EXCLUSIVE/PERMISSIVE LEFT TURN PHASES FOR BOTH APPROACHES.
- 2. A FULL-TRAFFIC-ACTUATED, EIGHT-PHASE CONTROLLER WITH VIDEO INTERFACE AND ALL NECESSARY EQUIPMENT HOUSED IN A NEMA SIZE "S" BASE-MOUNTED CABINET SHALL BE INSTALLED AT THIS INTERSECTION.
- MONTGOMERY COUNTY SIGNAL SHOP SHALL INSTALL APS CONTROL UNIT INTO CONTROLLER CABINET. THE CONTRACTOR SHALL DELIVER THE CONTROL UNIT AND AUDIBLE PUSHBUTTONS TO MR. KEITH LORD OF THE MONTGOMERY COUNTY SIGNAL SHOP FOR TESTING AND PROGRAMMING.

III. SPECIAL NOTES

- 1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR TERMINATING ALL SIGNAL CABLES, EXCLUDING INTERCONNECT, TO THE APPROPRIATE TERMINALS AND SHALL PROPERLY LABEL EACH CABLE.
- 2. DISCONNECTING AND SPLICING OF INTERCONNECT CABLE SHALL BE PERFORMED BY MONTGOMERY COUNTY FORCES. THE CONTRACTOR SHALL RUN THE INTERCONNECT CABLE INTO THE BASE OF EACH CABINET AND PROPERLY TAG THE CABLE, ALL CONTROLLER CABINET WIRING WILL BE PERFORMED BY MONTGOMERY COUNTY FORCES, CONTACT KAMAI HAMUD AT (240) 777-8761 SEVENTY-TWO HOURS IN ADVANCE OF INTENDED WORK.
- 3. ALL UNDERGROUND AND OVERHEAD UTILITIES SHOWN ON THESE PLANS ARE SCHEMATIC ONLY AND MAY NOT BE COMPLETE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR NOTIFYING MISS UTILITY PRIOR TO CONSTRUCTION SO THAT ALL UTILITIES MAY BE LOCATED IN THE FIELD. IF THE CONTRACTOR PERCEIVES THAT A CONFLICT BETWEEN THE UTILITIES AND THE TRAFFIC SIGNAL WILL OCCUR, THE CONTRACTOR SHALL NOTIFY THE PROJECT ENGINEER IMMEDIATELY SO THAT THE CONFLICT MAY BE RESOLVED.
- 4. CONTACT MR. MIKE KINNEY AT (240) 777-8760 SEVENTY-TWO HOURS IN ADVANCE OF INTENDED WORK FOR WIRING RELOCATING OF TRAFFIC SURVEILLANCE CAMERA EQUIPMENT INCLUDING POLE MOUNT CAMERA CABINET.
- 5. APS WILL FUNCTION AS FOLLOWS:

TO CROSS PINEY BRANCH ROAD

- A. WHEN PEDESTRIAN LOCATES AND PRESSES THE PUSHBUTTON FOR AN EXTENDED TIME, THE PUSHBUTTON UNIT WILL ANNOUNCE THE FOLLOWING MESSAGE "WAIT TO CROSS PINEY BRANCH AT FLOWER, CROSSWALK ANGLES LEFT.
- B. WHEN THE WALK PHASE BEGINS, THE PUSHBUTTON UNIT WILL PROVIDE A RAPID TICK WHICH WILL LAST FOR THE DURATION OF THE WALK PHASE.

TO CROSS FLOWER AVENUE

- A. WHEN PEDESTRIAN LOCATES AND PRESSES THE PUSHBUTTON FOR AN EXTENDED TIME, THE PUSHBUTTON UNIT WILL ANNOUNCE THE FOLLOWING MESSAGE "WAIT TO CROSS FLOWER
- AT PINEY BRANCH. B. WHEN THE WALK PHASE BEGINS, THE PUSHBUTTON UNIT WILL PROVIDE A RAPID TICK WHICH WILL LAST FOR THE DURATION OF THE WALK PHASE.

CONTACT PERSONS

THE CONTACT PERSONS FOR THIS PROJECT ARE AS FOLLOWS:

DISTRICT 3

MS. QIANYU HU ASSISTANT DISTRICT ENGINEER - TRAFFIC 301-513-7317

MR. MARK LOEFFLER DISTRICT ENGINEER - UTILITIES 301-513-7350

MR. JOHN GOVER ASSISTANT DISTRICT ENGINEER - CONSTRUCTION 301-513-7336

MR. GREGORY EDWARDS ASSISTANT DISTRICT ENGINEER - MAINTENANCE 301-513-7304

MONTGOMERY COUNTY

810 Gleneagles Court, Suite 300

Baltimore, MD 21286

www.stantec.com

MR. KAMAL HAMUD MONTGOMERY COUNTY-TRAFFIC ENGINEERING PHONE NUMBER 240-777-8761

[CONTACT NAME] PHONE 202-833-7500

<u>PEPCO</u>

OOTS CONTACTS:

MS. REBECCA LICHTENSTEIN, P.E. CHIEF TRAFFIC OPERATION DIVISION PHONE: (410)-787-7630

MR. ANTOINE YATES ASSISTANT DIVISION CHIEF. TRAFFIC OPERATIONS DIVISION PHONE: (410)-787-7625

MR. MIKE BASSO CHIEF, SIGNAL OPERATIONS PHONE: (410)-787-7652

MR. MICHAEL BOYLE CHIEF, WAREHOUSE SECTION PHONE: (410)-787-7668

MR. DAVID "TODD" JONES SIGN SHOP MANAGER 410-787-7676

EQUIPMENT LIST

A. EQUIPMENT TO BE FURNISHED BY STATE HIGHWAY ADMINISTRATION:

ITEM NO. QUANTITY UNIT DESCRIPTION

NONE

B. EQUIPMENT TO BE FURNISHED AND/OR INSTALLED BY CONTRACTOR CATEGORY QUANTITY UNIT DESCRIPTION CODE NO.

549419 117 LF 24 INCH WHITE THERMOPLASTIC PAVEMENT MARKING STOP LINE 801004 22.1 CY CONCRETE FOR SIGNAL FOUNDATION

SF SHEET ALUMINUM SIGNS 801605 209

LF NO. 6 AWG STRANDED BARE COPPER GROUND WIRE 802501 1066 LF 1 CONDUCTOR #3/O AWG CABLE 802575 205

805050 EA WEATHER HEAD, 3 INCH 805121 486 LF UP TO 4 INCH SCHEDULE 80 RIGID PVC CONDUIT-BORED OR SLOTTED

LF 2 INCH SCHEDULE 80 RIGID PVC CONDUIT-TRENCHED 805125 200 805135 67 LF 3 INCH SCHEDULE 80 RIGID PVC CONDUIT-TRENCHED 805140 54 LF 4 INCH SCHEDULE 80 RIGID PVC CONTUIT-TRENCHED

807206 EA UP 200 AMP EMB MT SER PED CON COL/GR ROD 811001 EA FURNISH AND INSTALL ELECTRICAL HANDHOLE 816003 EA HD IP-BASED VIDEO DETECTION CAMERA AND ANY LENGTH LEAD-IN CABLE

816125 EA POLE MOUNTED SPLICE CABINET EA 10 FOOT BREAKAWAY PEDESTAL POLE 818004 EA STEEL POLE WITH A SINGLE 38 FOOT MAST ARM 818030

818036 EA STEEL POLE WITH A SINGLE 50 FOOT MAST ARM 822002 141 LF 12-PAIR COMMUNICATION CABLE, JELLYFILLED (UNDERGROUND)

822510 120 LF DISCONNECT, PULL BACK AND REROUTE EXISTING CABLE OR DUCT CABLE EA GROUND ROD - 3/4 INCH DIAMETER X 10 FOOT LENGTH 837001 860284 52 EA 12 INCH LED VEHICULAR TRAFFIC SIGNAL HEAD SECTION

EA 16 INCH LED COUNTDOWN PEDESTRIAN SIGNAL HEAD 860285 8 860289 12 EA SIGNAL HEAD BACK PLATE, ANY SIZE 861105 1175 LF ELECTRICAL CABLE - 2 CONDUCTOR (NO. 14 AWG) LF ELECTRICAL CABLE - 5 CONDUCTOR (NO. 14 AWG) 861107 1306

861108 1504 LF ELECTRICAL CABLE - 7 CONDUCTOR (NO. 14 AWG) 861117 10 LF ELECTRICAL CABLE - 3 WIRE (NO. 4 AWG) 865210 8 EA AUDIBLE/TACTILE PEDESTRIAN PUSHBUTTON STATION AND SIGNS 865300 EA 2-WIRE APS CENTRAL CONTROL UNIT, APS PANEL AND HARNESS

866110 3 EA ANY SIZE LIGHTING ARM ON SIGNAL POLE WITH LED ROADWAY LUMINAIRE 871210 1 EA INSTALL CONTROLLER AND CABINET BASE MOUNT (ANY SIZE) WITH FURNISH AND INSTALL FOUNDATION AND GROUND ROD

873002 LS REMOVE AND DISPOSE OF EXISTING SIGNAL EQUIPEMENT 971043 EA CABINET EXTENSION BASE, SIZE "S"

971044 1 EA UPS EQUIPMENT FOR "S" CABINET 971047 1 EA CONTROLLER CABINET, SIZE "S" WITH CONTROLLER AND HD IP-BASED VIDEO DETECTION COMMUNICATION MANAGER INTERFACE PANEL

MAINTENANCE OF TRAFFIC NOTE

MAINTENANCE OF TRAFFIC WILL BE HANDLED BY THE CONTRACTOR UTILIZING THE FOLLOWING STANDARD PLATES FOR TRAFFIC CONTROL:

STANDARD NO. 104.02-14 (INTERSECTION FLAGGING OPERATION 2-LANE, 2-WAY EQUAL/LESS THAN 40 MPH)

STANDARD NO. 104.03-01 (MULTI-LANE UNDIVIDED SHOULDER WORK)

STANDARD NO. 104.03-10 (INTER. FAR-LEFT LANE CLOSURE/MULTILANE UNDIV. EQUAL/LESS THAN 40 MPH)

STANDARD NO. 104.03-12 (INTER. FAR-RIGHT LANE CLOSURE/MULTILANE UNDIV. EQUAL/LESS THAN 40 MPH)

STANDARD NO. 104.03-14 (INTER. FAR-SIDE CLOSURE/MULTILANE UNDIV. EQUAL/LESS THAN 40 MPH)

STANDARD NO. 104.04-01 (MULTI-LANE DIVIDED SHOULDER WORK)

STANDARD NO. 104.04-14 (LEFT-TURN BAY CLOSURE/DIVIDED UNCON. GREATER THAN 40 MPH) STANDARD NO. 104.04-16 (INTER. (LEFT LANE, TURN BAY) CLOSURE/DIVIDED UNCON.

ADDITIONAL TRAFFIC CONTROL STANDARDS MAY BE USED AS DIRECTED BY THE ENGINEER.

GREATER THAN 40 MPH)

PHASE CHART

PHASE 1 AND 5

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20

OFFICE OF TRAFFIC & SAFETY

TRAFFIC ENGINEERING DESIGN DIVISION

AND FLOWER AVE.

TACOMA PARK, MARYLAND

MONTGOMERY

15032001.63

SHEET NO. 53 OF **87**

CONTRACT NO.

COUNTY

LOGMILE

TIMS NO.

TOD NO.

JM


DRAWING SG-03 OF 03

DRAWN BY CHECKED BY

MDE/PRD

TS NO. 2684B

THREE TRIVE O	' ' ' ' '	' 4 ' ('`	' 4 ' ('	'`	'`	'`		'`	'`	١,	5 * *	"		5,,	"	5,,	5 ,,	- ' '	
CHANGE TO PHASES 1 AND 6	, 2 AN	D 5, C	R 2	AND 6	5	1	1	•			1				ı		1				7
PHASE 1 AND 6	← G/G	← G/G	G	R	R	R	R	R	R	R	R	R	DW	W/K	W/K	DW	DW	DW	DW	DW	
1 AND 6 CHANGE	← Y/G	← Y/G	G	R	R	R	R	R	R	R	R	R	DW	W/K	W/K	DW	DW	DW	DW	DW 7	<u> </u>
PHASE 2 AND 5	R	R	R	← G⁄G	← G/G	G	R	R	R	R	R	R	W/K	DW	DW	W/K	DW	DW	DW	DW S	\bigvee_{\vdash}
2 AND 5 CHANGE	R	R	R	← Y/G	← Y/G	G	R	R	R	R	R	R	W/K	DW	DW	W/K	DW	DW	DW	DW	4 \(\frac{1}{4} \)
PHASE 2 AND 6	G	G	G	G	G	G	R	R	R	R	R	R	W/K	W/K	W/K	W/K	D/W	D/W	D/W		
PED CLEARANCE	G	G	G	G	G	G	R	R	R	R	R	R	FL⁄DW	FL⁄DW	FL⁄DW	FL⁄DW	DW	DW	DW	DW	$\sqrt{}$
2 AND 6 CHANGE	Υ	Υ	Υ	Υ	Υ	Υ	R	R	R	R	R	R	DW	DW	DW	DW	DW	DW	DW	DW	<u></u>
PHASE 3 AND 7	R	R	R	R	R	R	← G-	← G-	R	← G-	← G-	R	DW	DW	DW	DW	DW	DW	DW	DW	
CHANGE TO PHASES 3 AND 8	3, 4 AN	ID 7, 0	OR 4	AND	8					•	•	•									\downarrow
PHASE 3 AND 8	R	R	R	R	R	R	← G/G	← G/G	G	R	R	R	DW	DW	DW	DW	DW	DW	DW	DW	<u> </u>
3 AND 8 CHANGE	R	R	R	R	R	R	← Y/G	← Y/G	G	R	R	R	DW	DW	DW	DW	DW	DW	DW	DW	- - - - - - -
PHASE 4 AND 7	R	R	R	R	R	R	R	R	R	← G/G	← G⁄G	G	DW	DW	DW	DW	DW	DW	DW	DW	\prod
4 AND 7 CHANGE	R	R	R	R	R	R	R	R	R	← Y/G	← Y/G	G	DW	DW	DW	DW	DW	DW	DW	DW	4 🗸
PHASE 4 AND 8	R	R	R	R	R	R	G	G	G	G	G	G	DW	DW	DW	DW	DW	DW	DW	DW	7
4 AND 8 CHANGE	R	R	R	R	R	R	Υ	Υ	Υ	Υ	Υ	Υ	DW	DW	DW	DW	DW	DW	DW	DW	$\dashv \bigvee$ <
PHASE 4 AND 8 LPI	R	R	R	R	R	R	R	R	R	R	R	R	DW	DW	DW	DW	W/K	W/K	W/K	W/K	
PHASE 4 AND 8 ALT	R	R	R	R	R	R	G	G	G	G	G	G	DW	DW	DW	DW	W/K	W/K	W/K	W/K	 ۲ ار _۱
PED CLEARANCE	R	R	R	R	R	R	G	G	G	G	G	G	DW	DW	DW	DW	FL⁄DW	′FL⁄DW	FL⁄DW	I I	
	R	R	R	R	R	R	Υ	Υ	Υ	Υ	Υ	Υ	DW	DW	DW	DW	DW	DW	DW	DW	⊣ ?^<
4 AND 8 ALT CHANGE	'`	1			1		+	+	 	<u> </u>	<u> </u>	1						+	+	+	$\overline{}$



PHASING NORTH

<u>\$SG04\$</u> () F <u>87</u>

WIRING KEY

A,B,C,D - ELECTRICAL CABLE - 3 CONDUCTOR (NO. 14 AWG)


E,F - ELECTRICAL CABLE - 2 CONDUCTOR (NO. 14 AWG)

GW - NO. 6 AWG STRANDED BARE COPPER GROUND WIRE

G - 1 CONDUCTOR #3/O AWG CABLE

H - 3 WIRE #4 AWG

+ - NEW GROUND ROD




DEPARTMENT OF TRANSPORTATION


EQUIPMENT LIST

A. EQUIPMENT TO BE FURNISHED AND/OR INSTALLED BY CONTRACTOR CATEGORY QUANTITY UNIT DESCRIPTION CODE NO. 801004 1.4 CY CONCRETE FOR SIGNAL FOUNDATION 801605 44 SF SHEET ALUMINUM SIGNS LF NO. 6 AWG STRANDED BARE COPPER GROUND WIRE 802501 119 802575 53 LF 1 CONDUCTOR #3/O AWG CABLE 805105 32 LF 2 INCH SCHEDULE 80 RIGID PVC CONDUIT-BORED 805125 77 LF 2 INCH SCHEDULE 80 RIGID PVC CONDUIT-TRENCHED 807206 1 EA UP TO 200 AMP EMBEDDED METERED SERVICE PEDESTAL. CONCRETE COLLAR & GROUND RODS 811001 1 EA FURNISH AND INSTALL ELECTRICAL HANDHOLE 816125 1 EA POLE MOUNTED SPLICE CABINET 818010 2 EA 14 FOOT BREAKAWAY PEDESTAL POLE 837001 2 EA GROUND ROD - 3/4 INCH DIAMETER X 10 FOOT LENGTH 860284 4 EA 12 INCH LED VEHICULAR TRAFFIC SIGNAL HEAD SECTION 860289 4 EA SIGNAL HEAD BACK PLATE, ANY SIZE 861105 69 LF ELECTRICAL CABLE - 2 CONDUCTOR (NO. 14 AWG) 861106 143 LF ELECTRICAL CABLE - 3 CONDUCTOR (NO. 14 AWG) LF ELECTRICAL CABLE - 3 WIRE (NO. 4 AWG) 861117 65 865210 2 EA AUDIBLE/TACTILE PEDESTRIAN PUSHBUTTON STATION AND SIGNS 971016 1 EA EIGHT PHASE (FULLY ACTUATED CONTROLLER AND CABINET POLE MOUNT

PROPOSED SIGNS



REVISION



- A. INSTALL 14' PEDESTAL POLE (MD 818.17), WITH BREAKAWAY TRANSFORMER BASE (MD 821.01), SIGNAL HEADS, SPLICE CABINET, PUSHBUTTON, AND SIGNS.(NOTE: ONE 2 IN. PVC SCHEDULE 80 CONDUIT BEND).
- B. INSTALL 14' PEDESTAL POLE (MD 818.17), WITH BREAKAWAY TRANSFORMER BASE (MD 821.01), SIGNAL HEADS, PUSHBUTTON, AND SIGNS. (NOTE: ONE 2 IN. PVC SCHEDULE 80 CONDUIT BEND).
- C. INSTALL 2 IN. PVC SCHEDULE 80 ELECTRICAL CONDUIT TRENCHED. D. INSTALL 2 IN. PVC SCHEDULE 80 ELECTRICAL CONDUIT BORED.
- E. INSTALL EMBEDDED METERED SERVICE PEDESTAL (100 AMPS). (NOTE: INSTALL 2-2 IN. 90° CONDUIT BENDS)

GENERAL NOTES

1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR TERMINATING ALL SIGNAL CABLE TO THE APPROPORIATE TERMINALS AND PROPERLY LABEL EACH CABLE.
2. THE CONTRACTOR SHALL VERIFY ALL UNDERGROUND UTILITIES PRIOR TO INSTALLING PROPOSED SIGNAL EQUIPMENT.

IF ANY UTILITY CONFLICTS SHOULD ARISE THE CONTRACTOR SHALL CONTACT THE PROJECT ENGINEER. 3. ALL TRAFFIC SIGNAL FOUNDATIONS SHALL BE INSTALLED AT THE FINAL SIDEWALK OR CURB GRADE FOR

	LUSEL) SE	しロロ	1N2 •	HI	JHE S	IKU	JAUW	ΑΥ	PRUF	I L L	GKA	VDE I	- UK	UPEN	SECT	I UN 5 •	IU MEEI	CLEARANC	ES AS
S	PECIF	IED	IN	MD	816	.03,	MD	818	.02	• MD	81	8.04	. TI	ΗE	CONTRA	ACTOR	SHALL	VERIFY	ULTIMATE	GRADES
Ρ	RIOR	TO	THE	INS	STALL	_ATI	ON C	OF A	LL	SIGN	ΑL	EQUI	PME	NT.						

	Stantec	
PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED		
PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO: EXPIRATION DATE:	810 Gleneagles Court, Suite 300 Baltimore, MD 21286	

E GRADES			DRAWN BY: JM DATE: JAN., 2025 CHECKED BY: RJM3 DATE: JAN., 2025 DRAWING NO.:	DEPARTMENT OF TRANSPORTATION DIVISION OF TRAFFIC ENGINEERING & OPERATIONS MONTGOMERY COUNTY, MARYLAND
			Approved: Division of Traffic Engineering and Operations	TRAFFIC SIGNAL PLAN
tec			Reviewed: Manager, Transportation Systems Engineering	
			Reviewed: Manager, Traffic Engineering Studies Section	FLOWER AVENUE
			Recommended: Engineer, Transportation Systems Engineering	SCALE: I"=IO'

DATE: JAN., 2025

DESIGNED BY: RJM

APP'D

DATE

F. INSTALL HANDHOLE.

GEOMETRIC LEGEND

=== == EXISTING

PROPOSED

<u>UTILITY LEGEND</u>

— E — E — ELECTRIC CABLES —— A —— A —— AERIAL CABLES

----T----TELEPHONE CABLES

— F —— F —— F IBER-OPTIC


——SD———SD——— STORM DRAIN

---- G ---- GAS MAIN

----W------WATER MAIN -----S------SEWER MAIN

2/26/2025

NOTE: FLOWER AVENUE IS CONSIDERED TO



Date

SHEET<u>55</u> of <u>87</u>

Division of Transportation Engineering

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:


OF MARYLAND.

LICENSE NO:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286

www.stantec.com



Date

SHEET<u>56</u> of <u>87</u>

Division of Transportation Engineering

Bicycle and Pedestrian Priority Areas

2/26/2025

OF MARYLAND.

LICENSE NO:

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:

810 Gleneagles Court, Suite 300


Baltimore, MD 21286

www.stantec.com

CONSTRUCTION DETAILS

- (1) FURNISH AND INSTALL CONCRETE FOUNDATION, GROUND ROD, AND 13-FOOT DECORATIVE BETHESDA CAST STREETLIGHT POST WITH BREAK-AWAY COUPLINGS, AND 150 WATT LED DECORATIVE WASHINGTON GLOBE STYLE LUMINAIRE. (SEE DETAILS ON LT-02).
- (2) FURNISH AND INSTALL CONCRETE FOUNDATION, SALVAGE EXISTING RECTINLINEAR LIGHTING STRUCTURE AND INSTALL ONTO NEW FOUNDATION, AS SHOWN (SEE DETAIL ON LT-02).
- (3) REMOVE EXISTING LIGHT POLE, LUMINAIRE AND FOUNDATION 12" BELOW GRADE.
- FURNISH AND INSTALL (13 IN. X 24 IN. X 24 IN.) POLYMER CONCRETE SPLICE BOX. (SEE DETAIL ON LT-02).

- 5 FURNISH AND INSTALL (2–WAY) 4 IN. SCHEDULE 40 PVC RIGID ELECTRICAL CONDUIT TRENCHED.
- (6) FURNISH AND INSTALL 2 IN. SCHEDULE 40 PVC RIGID ELECTRICAL CONDUIT - TRENCHED.
- (7) USE EXISTING STREETLIGHT SPLICE BOX.
- (8) EXISTING LIGHTING STRUCTURE AND LUMINAIRE TO REMAIN.



LEGEND

- ⁺0.0 EXISTING NIGHTTIME LIGHT LEVEL
- EXISTING STREETLIGHT TO BE REMOVED
- EXISTING STREETLIGHT TO REMAIN
- PROPOSED STREETLIGHT
- EXISTING LUMINAIRE TO REMAIN
- → PROPOSED 100W LED LUMINAIRE
- PROPOSED SPLICE BOX
- PROPOSED MAST-ARM MOUNTED LIGHT

20'	0	20'	40'
	SCALE	i: 1"=20'	

(10) REMOVE EXISTING SPLICE BOX AND

CAP AND ABANDON CONDUITS.

LT-03

Bicycle and Pedestrian Priority Areas

NO.	REVISION	BY APP'D	DATE	DESIGNED BY: RJM	DATE: FEBRUARY, 2025	DEPARTMENT OF TRANSPORTATION
				DRAWN BY: JM	DATE: FEBRUARY, 2025	
				CHECKED BY: RJM	DATE: FEBRUARY, 2025	DIVISION OF TRANSPORTATION ENGINEERING
_				DRAWING NO.:	DATE:	MONTGOMERY COUNTY, MARYLAND
				RECOMMENDED FOR APPROVAL		
				Chief, Design Section	 Date	FLOWER AVENUE
				APPROVED		SEPARATED BIKE LANES
5_				Chief.		LIGHTING PLAN
				Division of Transportation Engir		SHEET <u>57</u> of <u>87</u>

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

OF MARYLAND. LICENSE NO:

EXPIRATION DATE:

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _

LIGHT

NO.

LP-101

LP-102

LP-104

LP-105

LP-108

LP-110

LP-111

LP-112

LP-113

LP-114

LP-116

LP-118

LP-119

LP-120

LP-121

LP-201

LP-203

LP-204

LP-205

LP-206

LP-207

LP-208

LP-209

LP-210

LP-211

LP-301

LP-302

LP-303

LP-304

LP-305

LP-401

LP-402

LP-403

LP-404

LP-405

LP-406

LP-407

STATION | OFFSET

99 + 88.56 | 27.03 | RT

100 + 41.29 | 33.67 | RT |

101 + 21.38 | 38.53 | RT |

102 + 04.86 | 41.99 | RT |

103 + 08.80 | 25.31 | RT

110 + 39.96 | 24.22 | RT |

106 + 27.93 | 23.39 | RT

107 + 90.33 | 23.25 | RT

1109 + 39.78 | 24.07 | RT

110 + 24.12 | 24.28 | RT

| 101 + 31.36 | 27.20 | LT |

101 + 83.42 | 44.44 | LT

102 + 32.27 | 23.80 | LT

102 + 61.07 | 24.95 | LT

103 + 32.27 | 32.14 | LT

103 + 63.38 | 33.16 | LT

104 + 31.66 | 34.68 | LT

104 + 72.95 | 24.23 | LT

105 + 36.68 | 24.84 | LT

| 105 + 76.93 | 24.84 | LT |

102 + 28.82 | 27.02 | RT | ALUMINUM |

103 + 22.45 | 25.22 | RT | ALUMINUM |

107 + 47.19 | 23.07 | RT | ALUMINUM |

108 + 28.45 | 22.73 | RT | ALUMINUM |

100 + 98.96 | 23.38 | RT | ALUMINUM |

101 + 83.03 | 66.64 | LT | ALUMINUM |

99 + 80.23 | 12.48 | LT | WOOD

111 + 26.66 | 46.86 | RT | WOOD

107 + 05.84 | 26.28 | LT

107 + 91.00 | 24.80 | LT 109 + 12.75 | 26.52 | LT

110 + 14.22 | 28.62 | LT |

LP-408 | 111 + 24.45 | 25.92 | LT | WOOD |

105 + 15.99 | 32.85 | RT | WOOD

105 + 79.38 | 22.83 | RT | WOOD

106 + 86.92 | 23.16 | RT | WOOD

109 + 12.33 | 23.56 | RT | WOOD

www.stantec.com

EXISTING STREETLIGHT POLE INFORMATION

WATTS

70

70

70

70

250

250

250

250

70

250

70

70

70

70

70

70

70

70

70

70

70

100

100

100

100

100

100

250

250

250

250

250

250

FIXTURE

TYPE

WASHINGTON GLOBE

WASHINGTON GLOBE

WASHINGTON GLOBE

WASHINGTON GLOBE

COBRAHEAD

COBRAHEAD

COBRAHEAD

COBRAHEAD

WASHINGTON GLOBE

COBRAHEAD

WASHINGTON GLOBE

|WASHINGTON GLOBE|

WASHINGTON GLOBE

WASHINGTON GLOBE

COBRAHEAD

70 TWIN | WASHINGTON GLOBE |

70 TWIN | WASHINGTON GLOBE

70 TWIN | WASHINGTON GLOBE

70 TWIN | WASHINGTON GLOBE |

POLE

ONDITION

GOOD

POLE

TYPE

13CA

13CA

13CA

13CA

13CA

WOOD

13CA

WOOD

WOOD

WOOD

WOOD

LIGHT

SOURCE

LED

LED

LED

LED

LED

LED

HPS

HPS

HPS

HPS

LED

HPS

LED

HPS

HPS

HPS

THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE Baltimore, MD 21286

EXPIRATION DATE:

) Stantec 810 Gleneagles Court, Suite 300

Bicycle and Pedestrian Priority Areas

NO.	REVISION	BY	APP'D	DATE	DESIGNED BY: RJM	DATE: FEBRUARY,	2025	
					DRAWN BY: JM	DATE: FEBRUARY,	2025] ,
					CHECKED BY: RJM	DATE: FEBRUARY,	2025	
					DRAWING NO .:	DATE:		
					RECOMMENDED FOR APPROVAL			
					Chief, Design Section APPROVED		Date	
					Chief, Division of Transportation Engir	neering	Date	

o.	REVISION	BY	APP'D	DATE	DESIGNED BY: RJM	DATE: FEBRUARY,	2025
					DRAWN BY: JM	DATE: FEBRUARY,	2025
			+		CHECKED BY: RJM	DATE: FEBRUARY,	2025
					DRAWING NO.:	DATE:	
					RECOMMENDED FOR APPROVAL Chief, Design Section		Date
					APPROVED		
					Chief, Division of Transportation Engine	ering	Date

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

> FLOWER AVENUE SEPARATED BIKE LANES LIGHTING PLAN

> > SHEET<u>58</u> of <u>87</u>

- ELECTRONIC MODULE

WITH TWISTLOCK RECEPTACLE

HINGED DOOR

BALLAST HOUSING

LUMINAIRE SPECIFICATIONS:

WATTAGE: 69W LED (EQUIVALENT 150W HPSV)

3500K CCT LEDS, 70 CRI

TYPE 3 FULL CUT-OFF

NOMINAL LUMENS: 6500

BUG RATING: B2-U0-G1

NEMA TWISTLOCK DIMMING

STATE LIGHTING (120–277V)

THE LIGHT POLE SHALL BE

INSTALLED ON BREAKAWAY

DECORATIVE STREET LIGHT

POST FOUNDATION DETAIL)

COUPLINGS (REFER TO

OPENING

Ø 12" BOLT CIRCLE

(4) 3/4" HOT DIP GALVANIZED L-TYPE

ANCHOR BOLTS

ANCHORAGE DETAIL

PROPOSED DECORATIVE STREET LIGHT POST AND LUMINAIRE

AUTO-SENSING VOLTAGE (120-277)

PHOTOCONTROL RECEPTACLE - 7 PIN

TWISTOFF PHOTOCONTROL FOR SOLID

CAST ALUMINUM

- OPTICAL ASSEMBLY

- LUMINAIRE HOUSING

- PHOTOCELL WINDOW

OPPOSITE DOOR OPENING

- 15A /120V GFCI DUPLEX RECEPTACLE

COVER. (POSITION ON POLE SHALL

BE PER MCDOT DIRECTION)

WITH SMALL, IN-USE WET LOCATION

-COVER LATCH

-SET SCREWS

POLE SPECIFICATIONS:

17" DIA. BASE, SQUARE

PATTERN BOLT CIRCLE

POLE, FIXTURE AND RECEPTACLE

FINISH, FEDERAL GREEN COLOR

SHALL HAVE A POWERCOAT

TAPERED SHAFT

595B #14036

BASE

HANDHOLE LOCATION

_____5_3/4" DIA.

__ 17" DIA. _

CAST ALUMINUM FUTED

SPIKE FINIAL

(a) (22) (23) (23) (23) (23) (23)

→ 3–1/2" DIA.

	NO.	REVISION	BY	L APP.D	DATE	DESIGNED DI: KUN	DAIL
						DRAWN BY: JM	DATE: FE
						CHECKED BY: RJM	DATE: FE
						DRAWING NO.:	DATE:
						RECOMMENDED FOR APPROVAL	
						Chief, Design Section APPROVED	
an Priority Areas							
						Chief,	

							I I	
LP-106	102 + 47.88	35.91	RT	13CA	LED	70	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-107	103+00.06	35.83	RT	13CA	LED	70	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-108	103 + 66.71	35.92	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-109	104 + 16.61	35.96	RT	13CA	LED	70	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-110	104 + 56.85	36.02	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-111	105 + 25.28	35.86	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-112	105 + 81.78	34.28	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-113	106 + 41.35	29.22	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-114	106 + 84.72	28.28	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-115	107 + 48.41	24.43	RT	13CA	LED	70	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-116	107 + 91.59	24.33	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-117	108 + 48.96	24.07	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-118	108 + 88.78	24.18	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-119	109 + 39.78	24.07	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-120	109 + 69.57	24.04	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-121	110 + 24.12	24.28	RT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-202	101 + 13.18	50.14	LT	13CA	LED	70 TWIN	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-203	101 + 83.28	35.80	LT	13CA	LED	70 TWIN	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-204	102 + 22.11	34.66	LT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-205	102 + 75.72	33.51	LT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-206	103 + 35.56	33.43	LT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-207	103 + 84.03	33.60	LT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-209	104 + 74.60	28.13	LT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-210	105 + 31.59	22.10	LT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-211	105 + 77.76	31.04	LT	13CA	LED	70	WASHINGTON GLOBE	RELOCATE POLE AND FIXTURE
LP-212	106 + 17.92	30.95	LT	13CA	LED	70	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-213	106 + 56.20	26.09	LT	13CA	LED	70	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-214	107 + 45.60	29.58	LT	13CA	LED	70	WASHINGTON GLOBE	NEW POLE AND FIXTURE
LP-404	107 + 05.84	26.28	LT	WOOD	LED	100	COBRAHEAD	REPLACE FIXTURE; POLE TO REMAIN
LP-405	107 + 91.00	24.80	LT	WOOD	LED	100	COBRAHEAD	REPLACE FIXTURE; POLE TO REMAIN
LP-406	109 + 12.75	26.52	LT	WOOD	LED	100	COBRAHEAD	REPLACE FIXTURE; POLE TO REMAIN
LP-407	110 + 14.22	28.62	LT	WOOD	LED	100	COBRAHEAD	REPLACE FIXTURE; POLE TO REMAIN
LP-408	111 + 24.45	25.92	LT	WOOD	LED	100	COBRAHEAD	REPLACE FIXTURE; POLE TO REMAIN
			1					

POLE

TYPE

13CA

13CA

13CA

STATION | OFFSET

100 + 41.29 | 33.67 | RT

100 + 95.64 | 36.38 | RT

101 + 21.38 | 38.53 | RT |

NO.

LP-102

LP-103

LP-104

PROPOSED

RELOCATE POLE AND FIXTURE

RELOCATE POLE AND FIXTURE

POLE AND FIXTURE TO REMAIN

RELOCATE POLE AND FIXTURE

RELOCATE POLE AND FIXTURE

GOOD | REPLACE FIXTURE; POLE TO REMAIN

GOOD | REPLACE FIXTURE; POLE TO REMAIN

GOOD | RELOCATE POLE AND FIXTURE

GOOD | RELOCATE POLE AND FIXTURE

GOOD POLE AND FIXTURE TO REMAIN

GOOD POLE AND FIXTURE TO REMAIN

GOOD | RELOCATE POLE AND FIXTURE

GOOD | RELOCATE POLE AND FIXTURE

GOOD POLE AND FIXTURE TO BE REMOVED

GOOD POLE AND FIXTURE TO BE REMOVED

GOOD | POLE AND FIXTURE TO BE REMOVED

POLE AND FIXTURE TO REMAIN

GOOD POLE AND FIXTURE TO REMAIN

GOOD POLE AND FIXTURE TO REMAIN

GOOD | REPLACE FIXTURE; POLE TO REMAIN

GOOD | REPLACE FIXTURE; POLE TO REMAIN

POLE AND FIXTURE TO BE REMOVED

POLE AND FIXTURE TO BE REMOVED

REPLACE FIXTURE; POLE TO REMAIN

REPLACE FIXTURE; POLE TO REMAIN

REPLACE FIXTURE: POLE TO REMAIN

| REPLACE FIXTURE; POLE TO REMAIN

REPLACE FIXTURE; POLE TO REMAIN

REPLACE FIXTURE; POLE TO REMAIN

GOOD POLE AND FIXTURE TO REMAIN

ACTION

LIGHT

SOURCE

LED

LED

LAMP

WATTS

70

70

FIXTURE

TYPE

PROPOSED

ACTION

| WASHINGTON GLOBE | RELOCATE POLE AND FIXTURE

WASHINGTON GLOBE | NEW POLE AND FIXTURE

70 TWIN | WASHINGTON GLOBE | RELOCATE POLE AND FIXTURE

LT-04

MAINTENANCE OF TRAFFIC GENERAL NOTES:

I. STANDARDS

All work along Piney Branch Road shall be conducted in accordance with the latest versions of the Maryland State Highway Administrations (MD SHA) Standard Specifications and Book of Standards for Highway and Incidental Structures. All work along Flower Avenue shall be conducted in accordance with the latest version of the Montgomery County Temporary Traffic Control Plan standards. All signs, channelizing devices, and other traffic control devices shall conform with the latest version of the Maryland Manual on Uniform Traffic Control Devices (MUTCD).

2. PRE-CONSTRUCTION

The contractor shallarrange and host a pre-construction meeting at least two weeks prior to starting construction and establishing the work zone. The following offices shall be notified of this pre-construction

- Montgomery County Division of Transportation Engineering at 240-777-7220
 Montgomery County Division of Traffic Engineering and Operations at 240-777-6000
 Montgomery County Transit at 240-777-5800
 Montgomery County Public Schools, Local Depot Manager
 Montgomery County Fire and Rescue, Local Fire Department Captain
 Montgomery County Police, Local Traffic Sergeant.
 Montgomery County Department of Permitting Services, Permit Inspection at 240-777-6300
 WMATA, Jamie Cepler at 202-962-6085

Maryland State Highway Administration (SHA) Offices:

Assistant District Engineer - Traffic (Montgomery County) qhu@sha.state.md.us, (301) 513-3717

*Gregory Edwards Assistant District Engineer - Maintenance gedwards@sha.state.md.us, (301) 513-7304

Assistant District Engineer - Construction jgover@sha.state.md.us, (301) 513-7336

Assistant District Engineer - Utilities mloeffler@sha.state.md.us, (301) 513-7350

Contact the MCDOT Transportation Management Center at 240-777-2100 between 5:00 AM and II:00 PM to inform them of temporary lane closures in the vicinity of any traffic signals.

The permittee shallcontact the Transportation Systems Engineering Team at 240-777-2100 at least two weeks in advance to coordinate any minor traffic signal work. Major traffic signal work shall be coordinated a minimum of thirty (30) days in advance of the project. The permittee shall contact the Montgomery County Transportation Management Center at 240-777-2100 a minimum of 72 hours prior to beginning work to have existing traffic signal equipment marked.

The permittee shallcontact the Traffic Engineering Design & Operations Section (TEDO) at 240-777-6000 at least ten (IO) working days in advance of the final paving operation to schedule the installation of permanent pavement markings

The permittee shallcontact the Director at 301-565-7300 of the Silver Spring Regional Services Center and the Silver Spring Traffic Sergeant at 301-565-7740 of the Montgomery County Police Department, a minimum of one week prior to the beginning of any work activities within the Silver Spring Business District.

3. SIGNS

a) ROAD WORK AHEAD signs shallbe installed on all side streets that intersect roads within the work zone. The signing shallbe placed along the intersection approach to the right of the travellane. Refer to Standard Detail MD 104.01-02 for guidance on sign placement.

b) Warning signs mounted on wood posts, and those mounted on approved portable supports, shall be mounted in conformance with Standard Detail MD 104.01-17.

c) The contractor shall cover temporary signs that are not applicable during non-working hours.

d) The contractor shall cover existing traffic signs in conflict with the work zone traffic control.

e) Signs shall not block pedestrian and cyclist access along any path that are open to pedestrian and cyclist traffic.

f) Contractor to ensure that signs are adequately visible to target users. If the Engineer deems signs are blocked by trees, other signs or trees, Contractor to reposition signs.

4. PORTABLE VARIABLE MESSAGE SIGNS

a) No more than two displays shall be used within any message cycle unless approved by the Engineer.

b) For a list of standard messages/abbreviations, contact the Engineer. All customized messages shall be approved by the Engineer.

c) Refer to Standard Detail MD 104.00-08 and -09 for more info.

d) Refer to Standard Detail MD 104.01-22 for traffic control devices associated with PVMS.

e) Two (2) PVMS will be made available by the contractor throughout duration of the project and placed at strategic locations prior to/during work activities, including any night time closures. PVMS to display messages approved by the Engineer. Finallocations are to be determined by the Engineer.

5. CHANNELIZING DEVICES

a) Taper formulas:

L = WS for speeds greater than (>) 40 mph. L = WS^2/60 for speeds equal to or less than (<) 40 mph. Where L = minimum length of taper; S = prevailing travelspeed or speed limit (MPH), whichever is higher, prior to work starting.
W = width of offset (ft)

b) Maximum spacing between channelizing devices

Taper channelization - Shallbe equalin feet to the posted speed limit for posted speeds eq/less than 40 mph and 40 feet for posted speeds greater than 40 mph.

Tangent channelization - Shallbe equalin feet to twice the posted speed limit in the buffer and equalin feet to the posted speed adjacent to the work area for posted speeds eql/less than 40 mph. Spacing shallbe 80 feet in the buffer and 40 feet adjacent to the work area for posted speeds greater than 40 mph.

6. PAVEMENT MARKINGS

a) Temporary pavement markings should be installed according to Section 104.02-03(f).

b) Pavement markings that are no longer necessary shall be completely removed or obliterated using grinding method.

7. FLAGGING OPERATIONS

a) Radio communication shall be required between flaggers at the discretion of the County Inspector or under the following conditions
-If the flaggers cannot see each other
-If the lane closure exceeds 200 feet.

b) Flaggers shall be Maryland State Hlghway Administration or AATSA approved flaggers and shall be used at the discretion of the County Inspector. Flaggers shall use STOP/SLOW paddles to direct traffic.

8. VEHICLES

a) Non-essential work vehicles are to be pulled as far off the road as possible or be otherwise parked in a manner that does not inhibit the movement of traffic.

b) All work zone vehicles entering/exiting or operating within the work zone shall display flashing safety lights (amber in color) as specified in Standard Detail MD 104.01-18A & B.

c) Coordinate deliveries of materials with proposed lane/shoulder closures, preferably when traffic volumes are low.

9. WORK HOUR RESTRICTIONS

a) Unless permitted by the Engineer, work within a lane, or within 2 feet of the face of curb (closed section roadway), is prohibited during peak hours 6 am - 9 am and 3 pm - 7 pm, Monday - Friday. Also, such work is not permitted on weekends, National/State holidays, or days preceding and following holidays.

b) Any night time work willrequire a noise waiver permit which shall be obtained from the Dept. of Environmental Protection (DEP). Night time work activities shall be between 10pm and 5am.

IO. RESIDENTIAL/COMMERCIAL ACCESS

a) Contractor shall maintain access to residences including mail delivery and trash/pick up at all times during construction. For driveways requiring temporary closure to vehicular access due to proposed improvements, and exclusive of emergency work, the contractor shall notify impacted property owner at least 2 weeks in advance of planned construction dates/times, confirm 24 hours in advance, and coordinate closely for the duration of construction activities. The contractor shall take all reasonable measures to provide access during construction activities.

b) Contractor to coordinate with property owners about locking doors as required to block access to sidewalks during construction.

c) Access shall be maintained to all driveways unless permission for closure is granted by the property owner/manager. However, accessibility for emergency vehicles shall be maintained at all times.

II. POSTED SPEED LIMITS

MD 320 (Piney Branch Road) is classified as an Urban Minor Arterial. Fenton Street is classified as an Urban Major Collector.

Posted speed limit

Flower Avenue Piney Branch Road (MD 320)

The posted speed limits will be maintained during the construction.

12. SPECIAL EVENTS

Contractor shall maintain sidewalk access during special events.

13. ADJACENT PROJECTS

Contractor shall coordinate construction activities with adjacent projects. Contractor shall not impede other projects.

14. TEMPORARY IMPACTS TO TRANSIT SERVICE

The contractor shall coordinate temporary bus stop relocations with Montgomery County Transit Service. Contact Phil McLaughlin (240-777-5800) at least 2 weeks in advance of construction. Ride-On bus stops are located along Flower Avenue and Piney Branch Road and are noted on the MOT sheets.

15. PARKING RESTRICTIONS

The permittee shallcontact Veeda Wilkinson with MCDOT, Division of Parking Management at 240-777-8740 a minimum of 48 hours in advance to arrange for payment and the bagging of allparking meters within the work zone. Meter numbers and location must be specified.

All existing Montgomery County Parking signs shall be covered or bagged by the contractor for the duration of work; and a temporary No Parking Anytime (R7-4) sign shall be installed in the affected parking space(s). Existing Montgomery County parking meter pipes/poles shall not be used fortemporary installation.

When it is necessary to restrict parking in a non-metered area to facilitate work activity, the permittee shall contact the appropriate County Police Station for temporary "No Parking" signs.

SEQUENCE OF CONSTRUCTION:

Remove concrete island between Sta.106+00 and 107+00
Remove concrete island between Sta.110+00 and 111+00
Construct drainage improvements, curb, sidewalk and roadway improvements along the west side of roadway between Piney Branch Avenue (MD 320)

and Arliss Street.
Construct drainage improvements, curb, sidewalk and roadway improvements along the east side of roadway between Piney Branch Avenue (MD 320) and Arliss Street. Install temporary striping at end of this phase but prior to

and Arliss Street. Install temporary striping at end of this phase but prior to start of next phase.
Construct drainage improvements, curb, sidewalk, signal, and roadway improvements along the southwest corner of the signalized intersection of Piney Branch Avenue (MD 320) and Flower Avenue. Install temporary striping.
Construct drainage improvements, curb, sidewalk, signal, and roadway improvements along the southeast corner of the signalized intersection of Piney Branch Avenue (MD 320) and Flower Avenue. Install temporary striping.
Following completion of Phase 5, mill and overlay roadway. Install temporary striping, including eradication of existing pavement markings beyond limits of mill and overlay as shown on the plans.

overlay as shown on the plans.

Note the Contractor may work on multiple segments at the same time within each phase, however may not work on adjacent segments at the same time.

CONSTRUCTION SCHEDULE:

Phase IA: single phase - 0.5 weeks Phase IB: single phase - 0.5 weeks

Phase 2: single phase - 16 weeks

Phase 3: single phase - 16 weeks

Phase 4: single phase - 4 weeks

Phase 5: single phase - 4 weeks

(Refer to Sequence of Construction for additional details on specific activities in each Phase.)

Stantec




10.	REVISION	BY	APP'D	DATE	DESIGNED BY: UMK DRAWN BY: UMK CHECKED BY: CC DRAWING NO.:	DATE: FEBRUARY, DATE: FEBRUARY, DATE: FEBRUARY, DATE:	2025	DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND
					RECOMMENDED FOR APPROVAL Chief, Design Section APPROVED		Date	FLOWER AVENUE SEPARATED BIKE LANES MAINTENANCE OF TRAFFIC GENERAL NOTES
					Chief, Division of Transportation Engir	neering	Date	SHEET <u>59</u> of <u>87</u>


LICENSE NO:

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

_ EXPIRATION DATE:

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com





<u>LEGEND</u> WORK AREA TYPE III BARRICADE CHANNELIZATION DEVICE POST SIGN FLAGGER ∞ ARROW PANEL TRAFFIC FLOW ARROW) Stantec

SCALE: 1" = 20'

Bicycle and Pedestrian Priority Areas

DATE: FEBRUARY, 2025 CHECKED BY: JRGB DATE: DRAWING NO .: RECOMMENDED FOR APPROVAL Chief, Design Section Date APPROVED

DESIGNED BY: JM

Chief, Division of Transportation Engineering

DRAWN BY: JM

BY

REVISION

APP'D DATE

FLOWER AVENUE SEPARATED BIKE LANES MAINTENANCE OF TRAFFIC PLAN

DEPARTMENT OF TRANSPORTATION

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

PHASE 01A

SHEET<u>61</u> of <u>87</u>

MT-02

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

OF MARYLAND. LICENSE NO: _ _ EXPIRATION DATE: _


810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com


Date

DATE: FEBRUARY, 2025

DATE: FEBRUARY, 2025

SCALE: I"=20'





<u>LEGEND</u> WORK AREA TYPE III BARRICADE CHANNELIZATION DEVICE POST SIGN FLAGGER ∞ ARROW PANEL TRAFFIC FLOW ARROW) Stantec

SCALE: 1" = 20'

Bicycle and Pedestrian Priority Areas

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND DATE: FEBRUARY, 2025 CHECKED BY: JRGB DATE: DRAWING NO .: RECOMMENDED FOR APPROVAL Date Chief, Design Section

Date

DATE: FEBRUARY, 2025

DATE: FEBRUARY, 2025

APP'D DATE

DESIGNED BY: JM

DRAWN BY: JM

APPROVED

Chief, Division of Transportation Engineering

BY

REVISION

FLOWER AVENUE SEPARATED BIKE LANES

MT-04

SHEET<u>63</u> of <u>87</u>

SCALE: I"=20'


MAINTENANCE OF TRAFFIC PLAN PHASE 01B

DEPARTMENT OF TRANSPORTATION

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO: _ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com



REVISION

WORK AREA TYPE III BARRICADE CHANNELIZATION DEVICE POST SIGN FLAGGER ARROW PANEL TRAFFIC FLOW ARROW

SCALE: 1" = 20'

	DRAWN BY: JM	DATE: FEBRUARY,	2025
	CHECKED BY: JRGB	DATE: FEBRUARY,	2025
	DRAWING NO.:	DATE:	
	RECOMMENDED FOR APPROVAL		
	Chief, Design Section		Date
	APPROVED		
	_		
	Chief, Division of Transportation Engir	neering	Date

DESIGNED BY: JM

DATE: FEBRUARY, 2025

DATE

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

FLOWER AVENUE SEPARATED BIKE LANES MAINTENANCE OF TRAFFIC PLAN PHASE 01B

PROFESSIONAL CERTIFICATION: I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

OF MARYLAND. LICENSE NO: _

EXPIRATION DATE:


) Stantec 810 Gleneagles Court, Suite 300 Baltimore, MD 21286


www.stantec.com

SCALE: I"=20'

SHEET<u>64</u> of <u>87</u>

MT-05






CONSTRUCTION NOTES

1. WHEN FEASIBLE, CONTRACTOR SHALL CONSTRUCT NO MORE THAN ONE-HALF OF DRIVEWAY AT ANY GIVEN TIME FOR SINGLE DRIVEWAYS. FOR SITES WITH TWO OR MORE DRIVEWAYS, NO MORE THAN ONE DRIVEWAY SHALL BE UNDER CONSTRUCTION AT ANY GIVEN TIME. FOR SINGLE LANE DRIVEWAYS, CONTRACTOR SHALL COORDINATE WITH LANDOWNER.

DATE: FEBRUARY, 2025



SCALE: 1" = 20' Bicycle and Pedestrian Priority Areas NO.

REVISION

	DRAWN BY: JM	DATE: FEBRUARY, 2	2025
	CHECKED BY: JRGB	DATE: FEBRUARY, 2	2025
	DRAWING NO .:	DATE:	
	RECOMMENDED FOR APPROVAL		
	Chief, Design Section		Date
	APPROVED		
	Chief, Division of Transportation Engir	ooring	Date
	I DIVISION OF THANSPORTATION ENGIN	ieei ii ig	

APP'D DATE DESIGNED BY: JM

BY

DEPARTMENT OF TRANSPORTATION DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND

FLOWER AVENUE SEPARATED BIKE LANES MAINTENANCE OF TRAFFIC PLAN PHASE 02

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

OF MARYLAND. LICENSE NO: _


__ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com

SCALE: I"=20'

SHEET<u>66</u> of <u>87</u>

MT-07



PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED
PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE
OF MARYLAND.

UNDER THE LAWS OF THE STATE

810 Gleneagles Court

Baltimore, MD 21286

www.stantec.com

MENTS WERE PREPARED
A A DULY LICENSED
E LAWS OF THE STATE
810 Gleneagles Court, Suite 300

TRAFFIC FLOW ARROW

SCALE: 1" = 20'

Bicycle and Pedestrian Priority Areas

	I			
		CHECKED BY: JRGB	DATE: FEBRUARY,	2025
		DRAWING NO.:	DATE:	
		RECOMMENDED FOR APPROVAL		
		Chief, Design Section APPROVED		Date
		Chief, Division of Transportation Engin	neering	Date

DEPARTMENT OF TRANSPORTATION
DIVISION OF TRANSPORTATION ENGINEERING
MONTGOMERY COUNTY, MARYLAND


FLOWER AVENUE
SEPARATED BIKE LANES
MAINTENANCE OF TRAFFIC PLAN
PHASE 02


SCALE: I"=20'

SHEET<u>67</u> of <u>87</u>

2/26/2025

LICENSE NO: _






SHEET<u>69</u> of <u>87</u>

SCALE: I"=20'

LICENSE NO: _

_ EXPIRATION DATE: _

www.stantec.com



CONSTRUCTION NOTES

1. WHEN FEASIBLE, CONTRACTOR SHALL CONSTRUCT NO MORE THAN ONE-HALF OF DRIVEWAY AT ANY GIVEN TIME FOR SINGLE DRIVEWAYS. FOR SITES WITH TWO OR MORE DRIVEWAYS, NO MORE THAN ONE DRIVEWAY SHALL BE UNDER CONSTRUCTION AT ANY GIVEN TIME. FOR SINGLE LANE DRIVEWAYS, CONTRACTOR SHALL COORDINATE WITH LANDOWNER. 2. ERADICATE EXISTING MARKINGS

PAVEMENT MARKING LEGEND

DATE: FEBRUARY, 2025

- (A) TEMPORARY 5 INCH SOLID WHITE LINE
- B TEMPORARY 16 INCH SOLID WHITE LINE
- (C) TEMPORARY 24 INCH SOLID WHITE LINE
- (D) TEMPORARY 5 INCH SOLID DOUBLE YELLOW LINE

TRAFFIC FLOW ARROW
Stantec

WORK AREA

POST SIGN

ARROW PANEL

FLAGGER

TYPE III BARRICADE

CHANNELIZATION DEVICE

SCALE: 1" = 20' Bicycle and Pedestrian Priority Areas

			DRAWN BY: JM	DATE: FEBRUARY, 3	2025
			CHECKED BY: JRGB	DATE: FEBRUARY, 2025	
			DRAWING NO.:	DATE:	
			RECOMMENDED FOR APPROVAL		
					 Date
			APPROVED		
			Chief, Date Division of Transportation Engineering		

DESIGNED BY: JM

APP'D DATE

REVISION

DIVISION OF TRANSPORTATION ENGINEERING MONTGOMERY COUNTY, MARYLAND FLOWER AVENUE

DEPARTMENT OF TRANSPORTATION

SEPARATED BIKE LANES MAINTENANCE OF TRAFFIC PLAN PHASE 03

SCALE: I"=20'

SHEET<u>70</u> of <u>87</u>

MT-II

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

OF MARYLAND. LICENSE NO:


__ EXPIRATION DATE: _

www.stantec.com

810 Gleneagles Court, Suite 300 Baltimore, MD 21286

<u>LEGEND</u>

 ∞



LICENSE NO: _

PROFESSIONAL CERTIFICATION: THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

_ EXPIRATION DATE: _

810 Gleneagles Court, Suite 300 Baltimore, MD 21286 www.stantec.com


Bicycle and Pedestrian Priority Areas

APPROVED Date Division of Transportation Engineering

MAINTENANCE OF TRAFFIC PLAN PHASE 03

SCALE: I"=20'

SHEET<u>71</u> of <u>87</u>



Bicycle and Pedestrian Priority Areas

SEPARATED BIKE LANES

MAINTENANCE OF TRAFFIC PLAN

PHASE 03

SHEET<u>72</u> of <u>87</u>

Date

Date

SCALE: I"=20'

Chief, Design Section

Chief, Division of Transportation Engineering

APPROVED

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED


PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE


_ EXPIRATION DATE: _


810 Gleneagles Court, Suite 300


Baltimore, MD 21286

www.stantec.com









Division of Transportation Engineering

SCALE: I"=20'


SHEET<u>76</u> of <u>87</u>


OF MARYLAND.


LICENSE NO: _

_ EXPIRATION DATE: _

Baltimore, MD 21286







Date

Date

SCALE: I"=20'

APPROVED

Division of Transportation Engineering

SEPARATED BIKE LANES

ROADWAY CROSS SECTIONS

SHEET<u>79</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _


THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286



APPROVED

Chief,
Division of Transportation Engineering

Date

SCALE: I"=20'

ROADWAY CROSS SECTIONS

SHEET<u>80</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO:


I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286



Chief, Design Section

Division of Transportation Engineering

APPROVED

Date

Date

SCALE: I"=20'

SEPARATED BIKE LANES

ROADWAY CROSS SECTIONS

SHEET<u>81</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _


THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286



Chief, Design Section

Chief,
Division of Transportation Engineering

APPROVED

Date

Date

SCALE: I"=20'

FLOWER AVENUE

SEPARATED BIKE LANES

ROADWAY CROSS SECTIONS

SHEET<u>82</u> of <u>87</u>

\\US0527-PPFSS0|\shared_projects\20262|3||6\700 CADD\700 Sr

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO:

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:


Stantec

810 Gleneagles Court, Suite 300

Baltimore, MD 21286

www.stantec.com

Bicycle and Pedestrian Priority Areas



PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

OF MARYLAND. LICENSE NO: _ EXPIRATION DATE: 810 Gleneagles Court, Suite 300

Baltimore, MD 21286


www.stantec.com

10'	0 SCALE: 1"	=10'	20'
Bicycle and	Pedestri	an Priority	Areas

	DRAWN BY: UMK	DATE: FEBRUARY,	2025
	CHECKED BY: CC	DATE: FEBRUARY, 2025	
	DRAWING NO.:	DATE:	
	RECOMMENDED FOR APPROVAL		
	Chief, Design Section		 Date
	APPROVED		
	APPROVED		
	Chief,		 Date
	Division of Transportation Engineering		

FLOWER AVENUE SEPARATED BIKE LANES ROADWAY CROSS SECTIONS

SCALE: I"=20' SHEET<u>83</u> of <u>87</u>



Date

Date

SCALE: I"=20'

APPROVED

Chief,
Division of Transportation Engineering

SEPARATED BIKE LANES

ROADWAY CROSS SECTIONS

SHEET<u>84</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO:


I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286



PROFESSIONAL CERTIFICATION:
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED
OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND.

LICENSE NO: _ EXPIRATION DATE:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286


www.stantec.com

SCALE: 1" =10'	
Bicycle and Pedestrian Priority Areas	

		DRAWN BT: UMK	DATE: FEBRUART,	2025
		CHECKED BY: CC	DATE: FEBRUARY,	2025
		DRAWING NO.:	DATE:	
		RECOMMENDED FOR APPROVAL		
				 Date
				Daie
		APPROVED		
		Chief,		 Date
		Division of Transportation Engin	neering	

SEPARATED BIKE LANES ROADWAY CROSS SECTIONS

SHEET<u>85</u> of <u>87</u> SCALE: I"=20'



Chief, Design Section

Division of Transportation Engineering

APPROVED

Date

Date

SCALE: I"=20'

SEPARATED BIKE LANES

ROADWAY CROSS SECTIONS

SHEET<u>86</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _


I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT IAM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286



Chief, Design Section

Chief,
Division of Transportation Engineering

APPROVED

Date

Date

SCALE: I"=20'

SEPARATED BIKE LANES

ROADWAY CROSS SECTIONS

SHEET<u>87</u> of <u>87</u>

PROFESSIONAL CERTIFICATION:

OF MARYLAND.

LICENSE NO: _

THEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED

PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE

EXPIRATION DATE:

810 Gleneagles Court, Suite 300

Baltimore, MD 21286